

Stair Tread Installation Guide

Thank you for purchasing our stair treads. The installation process is easy and straight forward. Remove treads from packaging and allow pile yarn to open in full before placing onto desired area. Brushing the pile would speed up the process in relaxing the yarn.

On most surfaces the treads will slide and we recommend the use of double sided carpet tape to keep them in place. Another more permanent option is available. Please see suggestions below:

- 1) Home Depot carries a number a number of double-sided carpet tape options and if you are unable to locate them in store, they are available online. Simply follow instructions provided by the tape supplier and see below for reference:



2) A more permanent option is to secure the treads with staples or tacks / nails. We recommend securing them $\frac{1}{4}$ of an inch inward from the serging into the pile, as this would avoid serging damage and yarn unravel. Keep in mind this solution will leave holes in the floor under the treads. We and/or Home Depot are not responsible for damaged floors underneath the treads if using this method.



Apply 1/4 inch inside the rug to avoid damage to serging
see white circles below as a suggestion



If there are any questions or comments please reach out to Home Depot or to Concord Global. You can email
sales@concordglobal.net

We carry **red** stair treads in most stores and they can be ordered online. Ivory & Black colors are also available. We carry other products to support this design if you want to expand your décor!

Scatter size in a variety of colors: <https://www.homedepot.com/p/TrafficMaster-Marash-Red-31-in-x-48-in-Area-Rug-59303/325526098>

Custom cut roll to length (the instore rolls are raw cuts, online orders are cut to length by linear foot and serged for a perfect finished custom length runner: <https://www.homedepot.com/p/TrafficMaster-Marash-Red-26-in-W-x-600-in-L-Stair-Runner-Rug-Covers-110-Sq-Ft-59309/325526169>

Disclaimer: Check your state's guidelines and precautions/warnings for installation