



# WATER-BASED PRE STAIN CONDITIONER

## NO. B2080 CLEAR

### PRODUCT INFORMATION

BEHR® Premium Water-Based Pre Stain Conditioner is a clear sealer designed to promote uniform stain application on soft woods, such as pine, fir, birch and maple. Generally, softer woods accept stain in varying degrees creating an uneven and blotchy appearance. This product helps to minimize the variation and prepares wood surfaces for staining with water-based stains.

### RECOMMENDED USES:

Ideal for properly prepared interior bare or stripped wood surfaces prior to applying BEHR Water-Based Wood Stains.

### PRODUCT SPECIFICATIONS:

**Resin Type:** Acrylic

**Weight per Gallon:** 8.5 lb

**% Solids by Volume:** 7.5% ± 2%

**% Solids by Weight:** 9% ± 2%

**VOC:** < 50 g/L

**Flash Point:** N/A

**Viscosity:** 25 – 30 s (#1 Zahn Cup)

**Recommended Film Thickness:** N/A

**Coverage:** Up to 400 sq ft/gal, depending on application method and substrate porosity.

### APPLICATION:

Stir thoroughly before using. Do not shake or thin. Use a nylon or nylon/polyester brush or a saturated clean cloth and apply liberally to all areas of the wood surface including edges. Allow to penetrate for 5 to 10 minutes, then remove any excess with clean, dry cloth. Apply BEHR Water-Based Wood Stain or BEHR Water-Based Stain & Poly In One. Allow Pre Stain to dry for 20 minutes before applying Wood Stain. Sand lightly prior to staining to remove grain raise.

**Brush:** Nylon/Polyester

**Thinning:** DO NOT THIN. Product is formulated for use at package consistency only.

**Dry Time:** @77°F & 50% RH

Longer dry time may be required in cooler temperatures and higher humidity.

**To Touch:** After 10 mins

**To Apply Stain:** After 10 mins

### SURFACE PREPARATION:

All surfaces must be clean, free of dust, oil, grease, wax, polish, glue and all other foreign substances.

**New Wood:** Sand the wood thoroughly with medium grit sandpaper and progress to fine grit sandpaper. Always sand in the direction of the wood grain. Sand smooth and remove all dust prior to stain application.

**Previously Finished Wood:** Strip the surface completely down to bare wood with a paint or varnish remover such as BEHR® Premium Wood Stain & Finish Stripper No. 64, making sure all previous finishes are removed. Surface must be sanded smooth and remove all dust prior to stain application.

**WARNING!** If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Center at 1-800-424-LEAD or log on to [www.epa.gov/lead](http://www.epa.gov/lead).

### CLEAN-UP/DISPOSAL:

Clean all tools and equipment with warm, soapy water. Do not dispose of this product down a drain. If spilled, contain material and remove with an inert absorbent. Dispose of contaminated absorbent, container and unused product in accordance with all current federal, state and local regulations. For recycling or disposal of empty containers, unused product and soiled rags, contact your household refuse collection service.

COMPLIES WITH THE BELOW AS OF 9/1/2021			
SCAQMD	YES	OTC	YES
CARB SCM 2007	YES	LADCO	YES
OTC Phase II	YES	AIM	YES

### CAUTIONS/LIMITATIONS:

- Protect from freezing.
- Not for use with oil-based stains. For oil-based stains pretreat wood with BEHR OIL-BASED PRE STAIN WOOD CONDITIONER.
- Shelf life under normal conditions is 2 years unopened.

### GENERAL INFORMATION:

**WARNING! IRRITANT. CAUSES EYE AND SKIN IRRITATION. MAY CAUSE RESPIRATORY TRACT IRRITATION.** Avoid contact with skin and eyes and avoid breathing vapors, spray mist and sanding dust. Sanding, grinding or abrading may release sanding dust, which may be harmful if inhaled and has been shown to cause lung damage or cancer with long term exposure. Do not breathe dusts, vapor, or spray mist. To avoid breathing in dust, vapors, and spray mist, open windows and doors or use other means to ensure fresh air entry during application, drying, sanding, and/or abrading. If properly used, a respirator (NIOSH approved with particulate pre-filter) may offer additional protection and should be used if adequate ventilation cannot be provided; obtain professional advice before using. If you experience eye watering, headaches, or dizziness during application or drying, increase fresh air or leave the area. Avoid contact with eyes and skin. Wash thoroughly after handling. Close container after each use.

**FIRST AID:** If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical assistance immediately. In case of eye contact, flush immediately with plenty of water for at least 20 minutes and get medical attention; for skin, wash thoroughly with soap and water. If swallowed, get medical attention immediately.

**KEEP OUT OF REACH OF CHILDREN – DO NOT TAKE INTERNALLY.**

