



INSTALLATION

1. Remove the existing shower head from the shower arm. Clean the shower arm threads with a soft brush.
2. Hand-tighten the shower filter onto the threaded shower arm.
3. Hand-tighten the shower head onto the shower filter.
4. If leakage occurs, wrap the shower arm pipe threads with Teflon tape.
5. Do Not Use With a Shut-Off Valve.

OPERATION

BEFORE ENTERING THE SHOWER

1. Activate and flush the filter by running hot water through the shower filter for 1 minute before using.

2. COOL TO DESIRED TEMPERATURE BEFORE ENTERING SHOWER.

MAINTENANCE

1. Replace the filter cartridge (model SLC) every 4-6 months or 10,000 gallons, whichever comes first.

FILTER CARTRIDGE REPLACEMENT (MODEL SLC)

1. Unscrew the 2-piece filter housing assembly.
2. Remove the used filter cartridge.
3. Lubricate the O-rings with petroleum jelly.
4. Install a new SLC filter cartridge.
5. Reassemble and tighten the filter housing

PERFORMANCE DATA: MODEL SLC FILTER CARTRIDGE

Maximum Rated Service Flow – 2.5 gallons per minute / 9.5 liters per minute

Maximum Rated Service Life – 4-6 months or 10,000 gallons / 37,854 liters (whichever comes first)

Maximum Working Pressure – 125 pounds per square inch / 860 kilo pascals

Maximum Operating Temperature – 120° Fahrenheit / 40° Celsius.

NOTE:

- While testing was performed under standard laboratory conditions, actual performance may vary.
- This system is to be used with potable water only. -This system is not Intended to be used as a drinking water treatment unit.
- Both the system and installation must comply with applicable state and local regulations This Sprite Shower Filtration System has been tested for reduction of free chlorine.

The concentration of free available chlorine in water entering the system was reduced to a concentration less than or equal to the permissible limit for water leaving the system. This system has not been evaluated for free chlorine reduction in the presence of chloramines. Free chlorine reduction performance may be impacted by the presence of chloramines in the water supply.



1791 Railroad St., Corona, CA 92880 U.S.

Phone: 800-327-9137 (US Toll Free)
or 951-735-1015

1791 Railroad St, Corona, CA 92880 EE. UU.

Teléfono: 800-327-9137 (gratis en EE. UU.)
o 951-735-1015

1791 Railroad St, Corona, CA 92880 États-Unis

Téléphone: 800-327-9137 (appel gratuit)
ou 951-735-1015



USE & CARE INSTRUCTIONS

Slim-Line Shower Filter

Instrucciones de uso y cuidado PARA SLIM-LINE FILTRO DE DUCHA

Instructions d'utilisation et d'entretien POUR LE FILTRE DE DOUCHE SLIM-LINE

LIMITED ONE YEAR WARRANTY

Sprite Industries warrants the shower filter housing only (not the cartridge) to be free of defects for a period of one year when used under normal operating conditions. At the time of purchase, it is the owner's responsibility to complete the product warranty information available on-line, to keep proof of purchase of the unit and all replacement cartridge(s) and to demonstrate that proper cartridge replacement and filter maintenance was performed as specified in the owner's instructions. The provision of this warranty shall not apply to any product that was not installed and used as intended as per the Installation and Use and Care instructions included with the product. And to any product that has been subjected to misuse, neglect, over-tightening, lack of, or improper periodic filter replacement, repaired or altered by anyone other than an authorized Sprite Industries service representative, and will VOID the warranty in its entirety. Transportation changes on units submitted for repair or replacement under warranty to Sprite Industries, Inc. 1791 Railroad St, Corona, CA 92880-2511 shall be

paid by the registered owner. This is the exclusive remedy and liability to consequential damages. There are no other warranties, either expressed or implied, limited to the extent permitted by law.

FOR MORE INFORMATION AND ON-LINE REGISTRATION

Go to: www.spriteshowers.com