

# CATALOG NO. WN2060


**MAXIMUM HORSEPOWER – 10 HP**  
**RAIN PROOF PULLOUT SWITCH**  
**60 AMPS 240 VOLTS A-C, 1 PHASE**  
**TYPE 3R ENCLOSURE**

**USE ONLY 60 DEG. C/75 DEG. C CONDUCTORS ON ALL FIELD INSTALLED LINE AND LOAD TERMINATIONS.**

**THIS SWITCH IS SUITABLE FOR USE ON A CIRCUIT CAPABLE OF DELIVERING NOT MORE THAN 10,000 AMPERES, RMS SYMMETRICAL, 240 VOLTS MAXIMUM WHEN PROTECTED BY 60 AMPERE MAXIMUM FUSES, OR A CIRCUIT BREAKER RATED 60 AMPERES MAXIMUM WITH A 10,000 AMPERE MINIMUM SHORT CIRCUIT RATING.**



**LISTED  
ENCLOSED  
PULLOUT  
SWITCH**



**Use CU/AL Wire**  
 RAINPROOF TYPE 3R

Siemens Energy & Automation, Inc.  
 Alpharetta, Georgia U.S.A.

MADE IN MEXICO PLANT SAL

**LUG TIGHTENING TORQUE (LB-IN)**

SCREW TYPE	WIRE SIZE	TORQUE
SLOTTED	14-10	32-35
	8	36-40
	6-4	41-45
	3-2/0	45-50

**⚡ DANGER**

HAZARD OF ELECTRICAL SHOCK OR BURN. TURN OFF POWER BEFORE WORKING INSIDE THIS EQUIPMENT.

**CAUTION:  
DOES NOT  
CONTAIN  
FUSES**

**WIRE RANGE**

CONNECTOR	COPPER		ALUMINUM	
	SOI	STR	SOI	STR
LINE	14-8	14-2	12-8	12-2
LOAD	14-8	14-2	12-8	12-2
EQUIP. GRND.	12-8	12-2	12-8	12-2

**MNP601587**

NOTE: LABEL STOCK AND PRINTING SYSTEM MUST MEET REQUIREMENTS DOCUMENTED IN UNDERWRITERS LABORATORIES FOLLOW UP SERVICE PROCEDURE FILE MH 11169

**REVISIONS**

REV.1 CR B0200234 RW 07/01/02

REV. 2 CR R0417989 DKB 11/03/04

**TITLE:**  
 4 X 3 WIRE DIAGRAM  
 MODEL WN2060

**DRAWING NO.**  
**MNP601587**

**MIDWEST ELECTRIC  
 PRODUCTS, INC.  
 MANKATO, MN**

