



60" TroposAir Solara

Weight = 20 lbs. in box

Weight = 18 lbs. out of box



REQUIREMENTS

MECHANICAL:

Fan must be attached to a securely anchored electrical junction box that is rated for ceiling fans. Fan must also be mounted at least 10 feet above floor level due to metal blades.

ELECTRICAL:

Requires a grounded electrical supply line of 120 volts, 60Hz, 1 amp circuit.

FEATURES

MOTOR SPECS:

DC Motor: FK37-1616

LOCATION USE:

This fan is rated ETLus and meets the standard for UL-507

WARRANTY:

Lifetime Indoor & 10-Year Outdoor

Dimensions:

Canopy Diameter	Sweep Diameter
5 15/16"	60"

Downrod Length	Blade Depth	All Depth
6"	12"	12"
12"	18"	18"
24"	30"	30"
36"	42"	42"
48"	54"	54"
72"	78"	88"

OPTIONS

AVAILABLE FINISHES:

Oil Rubbed Bronze	Part #88481
Driftwood	Part #88480

BLADES:

Engineered Plastic

CONTROL:

Remote control with 6-speeds, reverse and light control

LIGHTING:

Shown with "Optional" #630 Light": 15-Watt LED, 3000 Kelvin, 1000-Lumens and Dimmable (ORB Part #66301, Driftwood Part #36306)

DOWNROD:

The fan comes with a nom. 1/2" diameter x 6" long down-rod. Optional down-rods are available in 12", 24", 36", 48", 60" and 72" lengths. A down-rod coupler is available for installations requiring a down-rod longer than 72". Fan can be mounted on a sloped ceiling up to 35°.

PERFORMANCE

AIRFLOW/ENERGY EFFICIENCY INFO

Fan Speed	RPM	CFM/ Watt	WATT	CFM
High	195	201	37	7473