

**TECHNICAL DATA****KRK-09****KRUD KUTTER® GLOSS-OFF
PRE-PAINT SURFACE PREPARATION****DESCRIPTION AND USES**

Krud Kutter® Gloss-Off Pre-paint Surface Preparation is a no rinse, one-step formula is specially designed to prepare high gloss and other hard-to-stick-to surfaces for repainting or refinishing. Specially formulated to help new paint and varnish bond to old finishes, or as a wall preparation prior to wallpapering. It removes dirt, grease, grime, smoke, mildew, food stains, heel marks, crayon, old wallpaper paste, and wax from painted or unpainted wood, metal or vinyl wallpaper. **DO NOT USE** on porous or non-washable wallpaper. Always test first on surfaces not to be refinished, as it will de-gloss most surfaces.

MAY BE COATED OVER ANYTIME AFTER 10 MINUTES!

Cleans paintbrushes and roller covers between colors. Removes gritty residue left by removers and strippers.

PRODUCTS

| SKU | Description |
|-------|---------------------|
| GO326 | 32 oz. Spray Bottle |
| GO012 | 1-Gallon Bottle |

PRODUCT APPLICATION**DIRECTIONS**

Do not dilute. Use full strength. Saturate a coarse, lint-free cloth, and apply to surface in a circular motion. Fold and re-saturate cloth frequently. Wipe off with a clean cloth, turning cloth often to avoid smears. When the clean, de-glossed surface is dry to the touch (usually about 10 minutes), new finish can be applied. May be coated over anytime after 10 minutes (clean the surface today, recoat even a week later).

CAUTION: EYE AND SKIN IRRITANT. In case of contact with eyes or skin, flush with water for 15 minutes. If irritation persists, seek medical attention. If swallowed, take large amounts of water. **Do not induce vomiting.** Get medical attention.

**NO PETROLEUM SOLVENTS, BLEACH OR AMMONIA.
KEEP OUT OF REACH OF CHILDREN.**

PHYSICAL PROPERTIES

| GLOSS-OFF PREPAINT SURFACE PREPARATION | |
|--|---|
| Composition | Proprietary Blend of Biodegradable Surfactants, Detergents and Emulsifiers |
| Color | Clear |
| pH | <12 |
| VOC % by Weight | 0% |
| Practical Coverage | 32 ounces – 50-75 square feet 1-Gallon – 200-300 square feet |
| Shelf Life | NA |
| Flash Point | Non-flammable |
| Caution! | CAUTION: EYE AND SKIN IRRITANT. In case contact with eyes and skin, flush with water for at least 15 minutes. If irritation persists, seek medical attention. If swallowed, take large amounts of water. Do not induce vomiting. Get medical attention immediately. KEEP OUT OF REACH OF CHILDREN. |
| Safety Information | For additional information, see SDS |

The technical data and suggestions for use contained herein are correct to the best of our knowledge, and offered in good faith. The statements of this literature do not constitute a warranty, express, or implied, as to the performance of these products. As conditions and use of our materials are beyond our control, we can guarantee these products only to conform to our standards of quality, and our liability, if any, will be limited to replacement of defective materials. All technical information is subject to change without notice.



Rust-Oleum Corporation
11 Hawthorn Parkway
Vernon Hills, Illinois 60061

Phone: 877-385-8155
www.rustoleum.com

Form: GDH-528
Rev: 101016