

WHITE

WHITE



DYNAFLEX®

ULTRA

ADVANCED EXTERIOR SEALANT

• Lifetime Mold, Mildew & Algae Resistant

• 1 Hour Paint & Rain Ready


EASY WATER CLEAN-UP & LOW ODOR

Window, Door, Siding & Trim

Read back panel for cautions!
¡Lea las precauciones en el
panel posterior!

5.5 FL OZ (162 mL)

DAP® DYNAFLEX® ULTRA Advanced Exterior Sealant with WeatherMax™ Technology resists UV fading, chalking, crumbling, cracking & dirt build up. Sealant stays looking clean & new. Permanently flexible for a long-lasting, weatherproof seal that stands up to the elements and provides All Weather Protection. Exterior/Interior use.

FOR BEST RESULTS: Apply in temperatures above 40°F. Not for continuous underwater use, high temp surfaces or surface defects. Priming not usually necessary. Priming only required if testing indicates a need or where the sealant will be subjected to constantly high levels of moisture after cure. Joint size should not exceed 1/2" wide by 1/2" deep. For joints deeper than 1/2", use backer rod. Store away from extreme heat/cold.

INSTRUCTIONS: 1. Surface must be clean, dry & free of old caulk & foreign material. 2. Remove cap & cut nozzle at 45° angle to desired bead size. 3. Squeeze sealant into gap or crack. 4. Smooth/tool bead within 10 minutes. 5. Clean excess wet sealant with damp sponge before it skins over. Dried sealant must be cut or scraped away. 6. Paintable in 1 hour (depending on joint depth, temp & humidity) with most latex or oil-based paints. Use a latex primer prior to oil-based paints. 7. Reseal tube for storage & reuse.

COVERAGE: 30 linear ft at 3/16" diameter bead.

CAUTION! Contains ethylene glycol. Use in well-ventilated area. Do not get in eye or on skin. Do not ingest. Use gloves and safety glasses. **For emergencies,** call your poison control center at 800-222-1222. See Safety Data Sheet (SDS) for additional information. For an SDS, contact your supplier or visit dap.com. **KEEP OUT OF REACH OF CHILDREN.**

⚠ WARNING Cancer and Reproductive Harm – www.P65warnings.ca.gov

¡PRECAUCIÓN! Contiene etilenglicol. Utilice en un área bien ventilada. No permita el contacto con los ojos o la piel. No lo ingiere. Use guantes y gafas de seguridad. **En caso de emergencia,** llame a un centro de control de envenenamiento al 800-222-1222. Para más información, consulte la Hoja de datos de seguridad (SDS). Para obtener una SDS, comuníquese con su proveedor o visite dap.com. **MANTENGA FUERA DEL ALCANCE DE LOS NIÑOS.**

⚠ ADVERTENCIA Cáncer y Daños al Sistema Reproductor - www.P65warnings.ca.gov

NCCS Calif. ARB VOC < 1.5% wt/wt. (27 g/L)

LIFETIME MOLD, MILDEW & ALGAE RESISTANCE GUARANTEE:

DAP guarantees that the product when properly applied will remain free of mold, mildew and algae during the lifetime of your home. If mold, mildew and/or algae appear when product is used as directed within one year of purchase, provide evidence of mold, mildew & algae and sales receipt to DAP Products Inc., 2400 Boston Street, Suite 200, Baltimore, MD 21224 for replacement product or sales price refund. DAP will not be liable for incidental or consequential damages.

Para obtener las instrucciones y garantía en español, llame al 888-DAP-TIPS o visite dap.com.

QUESTIONS?/¿PREGUNTAS? Call 888-DAP-TIPS or visit/o visite dap.com & click on/y pulse en "Ask the Expert."

DAP Products Inc.
Baltimore, MD 21224
Made in the USA with U.S.
and globally sourced materials.
dap.com

