

BAMBOO BEIGE



DRYLOK®

CONCRETE FLOOR PAINT

LATEX
NON-SLIP LOW SHEEN



OUTDOOR
PATIOS



GARAGE
FLOORS



BASEMENT
FLOORS

| | |
|--------------------------|--|
| High traffic areas | No primer needed |
| Resists hot tire pick-up | NEW Cross-linking formula for better adhesion & chemical resistance |

WARNING!
Harmful if inhaled.
Read other cautions on back panel.

1 GALLON (3.785 L)



DOES NOT EXCEED
MAXIMUM VOC 50 g/L



DRYLOK® CONCRETE FLOOR PAINT is a specially formulated smooth latex paint for interior and exterior concrete garage floors, patios, sidewalks, steps, and wooden surfaces and trim. Perfect for decorative concrete stenciling.

GENERAL SURFACE PREPARATION: Surfaces must be thoroughly clean. If using a pressure washer, do not use a setting above 1750 PSI to avoid damaging the concrete. Surface must be thoroughly dry before painting. To verify the surface is thoroughly dry and free of residual trapped moisture, tape a 1ft. by 1ft. square piece of plastic onto the surface and let stand for 24 hours. If moisture is present on the concrete side of the plastic, the surface has not dried sufficiently. Allow additional drying and retest. Surface porosity is important for proper product adhesion. Before application, test concrete porosity by sprinkling a few drops of water onto the surface in several areas. If water is readily absorbed, you are ready to paint. If it beads or lays on the surface, additional cleaning and etching is required. Refer to "ACID ETCHING INSTRUCTIONS" below.

NOTE: Multiple cans of the same color should be mixed together for uniformity.

INTERIOR BARE & PREVIOUSLY PAINTED CONCRETE OR WOOD:

PREPARATION: Surfaces must be thoroughly clean. Remove loose or flaking paint by wire brushing or scraping. Dull glossy, previously painted surfaces with sandpaper. For bare surfaces that are highly troweled or smooth, acid etching is required. Refer to "ACID ETCHING INSTRUCTIONS" below.

APPLICATION: Stir thoroughly before and during application. Air and surface temperatures must be above 50°F (10°C) during application and remain there for 4 hours after application for proper film formation to occur. Apply first coat by brush (a good quality nylon/polyester blend) or 1/4" (6.35 mm) nap roller. For unpainted surfaces, the first coat should be thinned with one pint of water per gallon of paint. For previously painted surfaces in good condition, apply full strength. Allow 4 hours drying time and apply a second coat.

GARAGE FLOORS & EXTERIOR CONCRETE:

PREPARATION: Surfaces must be thoroughly clean and all previous coatings must be removed. Previous coats of DRYLOK® Concrete Floor Paint in good condition do not have to be removed. Freshly poured concrete and new concrete must cure 30 days before painting. All surfaces subject to vehicle traffic, highly troweled or extremely smooth concrete, must be acid etched. Refer to "ACID ETCHING INSTRUCTIONS" below. Concrete surface profile 4 and above required.

APPLICATION: Stir thoroughly before and during application. Air and surface temperatures must be above 50°F (10°C) during application and remain there for 4 hours after application for proper film formation to occur. Thin the first coat with one pint of water per gallon of paint and apply by brush (a good quality nylon/polyester blend) to ensure good adhesion. Allow to dry 4 hours. Apply a second coat full strength by brush or 1/4" (6.35 mm) nap roller.

ACID ETCHING INSTRUCTIONS: Treat with DRYLOK® powder or liquid Concrete and Masonry Etch & Cleaner according to manufacturer's directions. Properly prepared concrete should look and feel like medium grit sandpaper. If concrete remains smooth, repeat etching procedure. Surface must be free of all residual etching compounds. Rinse thoroughly and allow to dry. Do not etch painted surfaces.

WARNING! If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

DRYING: Allow to dry for 4 hours before subjecting to light foot traffic and 24 hours before subjecting to heavy foot traffic. Allow 5 days before subjecting to automobile use. If air and surface temperatures are below 50°F (10°C), the relative humidity is above 60%, or the coating is applied too thick, the drying time may increase.

COVERAGE: 300 to 400 sq. ft. (27.87-37.16 m²) per gallon.
DO NOT OVER APPLY.

CLEAN UP: Warm soapy water.

IMPORTANT: If floors (other than garages) are subjected to hydrostatic pressure (water seeping from underneath the floor) or are continually damp, apply DRYLOK® Floor & Wall Masonry Waterproofer according to directions before topcoating with DRYLOK® Concrete Floor Paint. Moisture caused by water seeping through floor-wall joints or cracks must also be eliminated. Use DRYLOK® Fast Plug®, a fast setting hydraulic cement, to fill floor-wall joints or cracks before painting.

WARNING! Cancer hazard: Contains Crystalline Silica, which can cause cancer. (Risk of cancer depends on duration and level of exposure.) Overexposure may cause lung and kidney damage. Close container after each use.

Use only with adequate ventilation. Do not breathe vapors. Ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness or if air monitoring demonstrates vapor levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH approved) during and after application. Follow respirator manufacturer's directions for respirator use. Avoid contact with eyes, skin and clothing. Wash thoroughly after handling.

First Aid: If you experience difficulty breathing, leave the area to obtain fresh air. If continued difficulty is experienced, call poison control center, hospital emergency room, or physician immediately.

KEEP OUT OF REACH OF CHILDREN.
DO NOT TAKE INTERNALLY.
KEEP FROM FREEZING.

WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov.

UNITED GILSONITE LABORATORIES, 1396 Jefferson Ave., Dunmore, PA 18509
Order No. 43513 UFI : HSGV-U3F5-A002-DMJH L422 www.DRYLOK.com



R8460

