

Popcorn Ceiling Remover



Remove all types of painted textures from drywall and other hard surfaces!

- ✓ Strip thick multiple paint layers and painted drywall mud textures safely from drywall and other hard surfaces!
- √ The only DIY friendly painted texture remover in the world that is dust free and works!
- ✓ A weekend project starter that updates your whole house.
- ✓ Generates start to finish adding on sales throughout your stores.
- ✓ Customers will save 60% over cost of hiring a contractor.
- ✓ The average contractor will save 60% in labor hours.
- ✓ Skin safe, fume free, no drip easy to use gel formula!
- ✓ Completely indoor safe with a very low VOC% that's great for all year-round projects!



Popcorn Ceiling Remover

Technical Data Sheet

Description

This painted drywall texture coating remover is a non-toxic water-based remover with a neutral PH suitable for all woods, metals (including aluminium), concrete, stone, brick, and drywall. EZ Strip Popcorn Ceiling Remover is designed to remove painted ceiling/wall textures & multi-layered paints from surfaces safely, and dust free.

Physical Properties

This 100% cling gel gives a slight almond odour but without any fumes. Gel is easily cleaned up with just water and is skin safe. Product is tinted blue to ensure even application.

Typical Performance

Paint 30 minutes to 1 hour

Multi-layered paint 1-12 hours Painted Spray Textures (Popcorn) 4-12 hours Painted Hand Textures (Swirl) 4-12 hours

The above times are approximations and subject to substrate, thickness of texture, and layers of paint.

If possible, always test a small area first for best removal time. Coverage is approximately 20 – 25 square feet per liter

Environmental

VOC content of this product is minimal, 0.000004%.

All materials are readily biodegradable & water soluble

EZ Strip Popcorn Ceiling Remover is not a marine pollutant and can enter water-courses and drains, care must be taken to ensure that any paint solids do not enter surface water drains. Disposal of this product or any by-

products should at all times comply with the requirements of the Environmental Protection Act and its subsidiary regulations and any regional Local Authority requirements.



Popcorn Ceiling Remover

See our how-to videos on MAXstrip.ca For detailed instructions and project demos!

<u>Instructions for Use</u>



Shake well before use. Use painters' tape and drop sheets to cover any surfaces you don't intend to strip. Apply (brush or roll on) a liberal coating of MAX Strip. For extra thick coatings, apply a second coat after 10 minutes. Cover area with plastic film to prevent product from drying. Do not let MAX Strip dry out as it will stop working, if MAX Strip does dry out, re-apply.



Allow plastic covered MAX Strip to work for 4 to 12 hours, depending on thickness of paint & coating. Using a scraper blade, test a small area. Coating should remove easily from drywall. If not, re-cover with plastic and allow more time for MAX Strip to penetrate before testing again.



Use a scraper blade to remove softened texture, taking care not to damage underlying surface. Catch the removed softened texture in a painter's tray and discard safely.



To finish, wipe entire area clean with a damp cloth to ensure good paint adhesion. Must be neutralized with water or MAX Strip will continue to work. Allow surface to dry completely before patching, sanding or painting.