

BLACK

BLACK

BLACK

BLACK

BLACK



100% SILICONE

CONTIENE: Destilados de petróleo, etiltriacetoxisilano y metiltriacetoxisilano. Se genera ácido acético durante el período de curado. Evite el contacto con los ojos, la piel y la ropa. Puede causar irritación en los ojos, piel y tracto respiratorio. Dañino si se traga. Evite respire los vapores. Utilice en un área bien ventilada. Cerciérese de que exista entrada de aire fresco. Use guantes y gafas de seguridad. Retire los lentes de contacto antes de utilizar el producto. **PRIMEROS**

AUXILIOS: PIEL: Lávese con agua y jabón. No utilice solventes ni limpiadores abrasivos para retirar el producto de la piel. OJOS: Enjuague inmediatamente con abundante cantidad de agua. INHALACION: Trasládese al aire fresco. INGESTION: NO INDUZCA EL VÓMITO. Obtenga atención médica si surgen complicaciones debido a la exposición. **En caso de emergencia,** llame al centro de control de envenenamiento al 1-800-222-1222. Consulte la Hoja de datos de seguridad (HDS) para más información. Para obtener una HDS, comuníquese con su proveedor o visite dap.com. **MANTENGA FUERA DEL ALCANCE DE LOS NIÑOS.**

⚠ ADVERTENCIA Cáncer y Daños al Sistema Reproductivo – www.P65warnings.ca.gov

Para obtener las instrucciones y garantía en español, llame al 1-888-327-8477 o visite dap.com.

QUESTIONS?/¿PREGUNTAS?
Call/Llame al 1-888-DAP-TIPS or visit/o
visite dap.com & click on
"Ask the Expert."

DAP Products Inc.,
Baltimore, MD
21224

Made in the USA
for DAP Products
Inc. with U.S.
and globally
sourced
materials.

dap.com

Silicone

ALL PURPOSE 100% SILICONE

**100% WATERPROOF
& WEATHERPROOF**

- Flexible
- Minimal Shrinkage
- Lifetime Guarantee
- Interior/Exterior

Window, Door, Siding & Trim

WARNING! CONTACT WITH UNCURED PRODUCT MAY
CAUSE EYE, SKIN & RESPIRATORY TRACT IRRITATION.
Read back panel carefully for other cautions.

¡ADVERTENCIA! EL CONTACTO CON PRODUCTOS
NO CURADOS PUEDE CAUSAR IRRITACIÓN EN LOS
OJOS, LA PIEL Y LAS VÍAS RESPIRATORIAS. Lea
cuidadosamente el panel posterior para otras precauciones.

9.8 fl oz (290 mL)

100% SILICONE

Meets the ASTM C920 requirements for
Grade NS, Class 25. Uses A, O and NT.

FOR BEST RESULTS: Apply when surface
temps are between -35°F to 140°F. Not
recommended for continuous underwater
use, surface defects, tuck-pointing, chimneys,
stovepipes or fireplace applications. Corrodes
some metals. Not for oily woods or
cementitious surfaces. Joint width should not
exceed 1/2". If joint depth exceeds 1/2", use
foam backer rod. **Not paintable.** Store below
90°F in a dry place.

INSTRUCTIONS: 1. Prepare a clean, dry
surface. 2. Cut nozzle at 45° angle to desired
bead size. 3. Puncture inner foil seal. 4. Load
into caulk gun. 5. Fill gap with sealant.
6. Smooth bead. 7. Allow at least 12 hours
before exposing sealant to water. Do not touch
or clean sealant for 24 hours. 8. Clean up
excess uncured sealant from surface & tools
with mineral spirits. Excess cured sealant
must be cut or scraped away. Wash hands
with soap & water.

COVERAGE: 53 linear ft at 3/16" diameter bead.

CONTAINS: Petroleum distillates &
methyltriacetoxysilane. Acetic acid is
evolved during cure. Avoid contact w/
eyes, skin & clothing. May cause eye,
skin and respiratory tract irritation. May
be harmful if swallowed. Do not ingest.
Avoid breathing vapors. Use only w/
adequate ventilation. Ensure fresh air
entry. Wear gloves & safety glasses.
Remove contact lenses before using
product. **FIRST AID:** SKIN: Wash
thoroughly w/ soap & water. Do not use
solvents or abrasive cleansers to
remove product from skin. EYES:
Immediately flood w/ large quantities
of water. INHALATION: Remove to fresh
air. INGESTION: DO NOT INDUCE
VOMITING. Get medical attention if
complications arise from any exposure.
For emergencies, call your poison
control center at 1-800-222-1222. See
Safety Data Sheet (SDS) for additional
information. For an SDS, contact your
supplier or visit dap.com. **KEEP OUT
OF REACH OF CHILDREN.**

⚠ WARNING Cancer and
Reproductive Harm –
www.P65warnings.ca.gov

CCCS Calif. ARB VOC <3 wt/wt% (VOC 30 g/L)
WARRANTY: DAP will provide replacement
product or refund sales price if product fails
to perform when used as directed, within
one year of the purchase date. Call
1-888-DAP-TIPS, with your sales receipt
and product container available, to arrange
for warranty fulfillment. DAP is not liable for
incidental or consequential damages.