Model:

Traditional Reach-In's:

S-23F

Reach-In Solid Swing Door Freezer





S-23F

- Stainless steel interior and exterior retains attractive finish longer.
- Rounded corner design inside of the cabinet makes it easy to clean the inside storage room
- Standard door features:
 Heavy-duty pull handle
 Each door with two spring hinges, this make the door self-closing with with enduring quality
- R290 Refrigeration system holds -8°F to 0°F (-22°C to -18°C) for the best in food preservation.
- Electronic control system:
 Adjustable temperature set point and defrost frequency
 Error codes to diagnose service issues
- Shelf: Adjustable, heavy duty PVC coated shelves.
- Standard heavy-duty casters make it easy to move and clean underneath

Bottom mounted units feature:

- "No stoop" lower shelf.
- Storage on top of cabinet.
- Easily accessible condenser coil for cleaning, and easy service access
- Simple installation with no plumbing required

Rough-In Data

Specifications subject to change without notice.

Chart dimensions rounded up to the nearest 1/8" (millimeters rounded up to next whole number).

			Cabinet Dimensions (inches) (mm)			CAP. CU.FT.				
Model	Doors	Shelves	L	D	Н	LITER	HP	Voltage	Amps	NEMA Config.
S-23F	1	3	29 736	32-1/4 818	82-1/2 2095	23 650	1/2+	115/60/1	7.92	5-15P

Plug type varies by country.





CONFORMS TO NSF/ANSI STD. 7

5\2\

S-23F Plan View





