

CLEAR

CLEAR

CLEAR

CLEAR

CLEAR



BASEBOARDS

WINDOWS

DOORS

MOLDING

TRIM

¡PRECAUCIÓN! Contiene etilenglicol. Usela sólo con la ventilación adecuada. Evite el contacto con los ojos y la piel. No lo ingiere. Utilice guantes y gafas de seguridad. **En caso de emergencia,** llame a un centro de control de envenenamiento al 1-800-222-1222. Refiérase a la Hoja de datos de seguridad (SDS) para más información. Para obtener una SDS, comuníquese con su proveedor o visite dap.com. **MANTENGASE FUERA DEL ALCANCE DE LOS NIÑOS.**

⚠️ ADVERTENCIA Cáncer y Daños al Sistema Reproductivo – www.P65warnings.ca.gov

GUARANTEE: If product fails to perform when used as directed, within one year of date of purchase, call **1-888-DAP-TIPS**, with your sales receipt and product container available, for replacement product or sales price refund. DAP Products, Inc. will not be responsible for incidental or consequential damages.

QUESTIONS?/¿PREGUNTAS? Call/Llame al **1-888-DAP-TIPS** or visit/o visite dap.com & click on "Ask the Expert."

Para obtener las instrucciones y garantía en español, llame al **1-888-327-8477** o visite dap.com.

DAP Products Inc.,
Baltimore, MD 21224
Made in the USA with U.S.
and globally sourced materials.
dap.com

ALEX PLUS

Exceeds ASTM C834

**ALL PURPOSE
ACRYLIC
LATEX
CAULK PLUS
SILICONE**

40 YR.

- **PAINTABLE**
- **FLEXIBLE**
- **STRONG MULTI-SURFACE ADHESION**
- **100% WATERPROOF**
- **EASY WATER CLEAN-UP & LOW ODOR**
- **INTERIOR/EXTERIOR**



Paint Projects

Read back panel for cautions!
¡Lea las precauciones en el panel posterior!

10.1 fl oz (300 mL)

DAP® ALEX PLUS® ACRYLIC LATEX CAULK PLUS SILICONE is an excellent quality, all purpose caulk for sealing a wide variety of interior & exterior surfaces. It contains silicone additives for greater flexibility & adhesion. It won't shine through or discolor the paint finish for superior paint results. Provides a durable, waterproof seal that is easy to apply & tool, low in odor & cleans up easily with water.

FOR BEST RESULTS: Apply in temps. above 40°F. Don't apply when rain/freezing temps. are forecasted before full cure can occur. Do not use below waterline, for filling butt joints, surface defects or tuck-pointing. Joint size should not exceed 1/2" wide x 1/2" deep. If joint depth exceeds 1/2", use backer rod material. **Caulk applies white & dries clear in 7-14 days (depending on joint depth, temperature & humidity).** Store away from extreme heat/cold.

INSTRUCTIONS: 1. Surface must be clean, dry & free of old caulk, dirt, dust, debris & grease. 2. Cut nozzle at a 45° angle to desired bead size. 3. Puncture inner foil seal. 4. Load cartridge into caulk gun. 5. Fill gap with caulk. 6. Smooth bead. 7. Clean up excess uncured caulk with damp sponge before it skins over. Cured caulk must be cut or scraped away. 8. Allow to dry clear before painting with latex or oil-based paints. Cool or humid conditions or type of paint used may require longer dry time. 9. Reseal cartridge for storage & reuse.

COVERAGE: 55 linear ft at 3/16" diameter bead.

CAUTION! Contains ethylene glycol. Use in well-ventilated area. Do not get in eyes or on skin. Do not ingest. Use gloves and safety glasses. **For emergencies,** call your poison control center at 1-800-222-1222. See Safety Data Sheet (SDS) for additional information. For an SDS, contact your supplier or visit dap.com. **KEEP OUT OF REACH OF CHILDREN.**

⚠️ WARNING Cancer and Reproductive Harm – www.P65warnings.ca.gov

NCCS Calif. ARB VOC
<1.5 wt/wt% (VOC 44 g/L)

