



52" TropoAir Titan II

MODEL #6HE52

Weight = 27.6 in box
Weight = 23.8 out of box



REQUIREMENTS

MECHANICAL:

Fan must be attached to a securely anchored electrical junction box that is rated for ceiling fans. Fan must also be mounted at least 10 feet above floor level.

ELECTRICAL:

Requires a grounded electrical supply line of 120 volts, 60Hz, 1 amp circuit.

FEATURES

MOTOR SPECS:

35W DC Motor

LOCATION USE:

This fan is rated cETLus and meets the standard for UL-507 and CAN/CSA-C22.2 No. 113.

WARRANTY:

Limited Lifetime Indoor & 10-Year Outdoor

OPTIONS

AVAILABLE FINISHES:

Extruded Aluminum Blades:

Brushed Nickel	Part #88254-88261
Oil Rubbed Bronze	Part #88253-88262
Pure White	Part #88255-88260

Resin Blades:

Brushed Nickel	Part #88254-88264
Oil Rubbed Bronze	Part #88253-88265
Pure White	Part #88255-88263

BLADES:

Match Fan Finish and also available in 82", 72" and 66" Sweeps.

CONTROL:

Six speeds and reversing function is controlled by the included Hand Held remote control. An In-Wall Transmitter is also available.

LIGHTING:

Optional light kit available at additional cost. #610 Light is an 18-watt LED Array with 1400 Lumens and 3000 Kelvin.

DOWNROD:

The fan comes with a nom. 3/4" diameter x 9" long down-rod. Optional down-rods are available in 12", 24", 36", 48", 60" and 72" lengths. A down-rod coupler is available for installations requiring a down-rod longer than 72". Fan can be mounted on a sloped ceiling up to 35°.

PERFORMANCE

AIRFLOW/ENERGY EFFICIENCY INFO

Fan Speed	RPM	CFM/Watt	WATT	CFM
High	181/150	231	34.7/18.9	7171
Med	126/100	415	12.2/7.7	5062
Low	75/50	750	4.8/3.0	2250

