

Technoflex — TechnoWall Acoustic Mass Loaded Vinyl (MLV) Barrier is a premium, multi-use soundproofing material that reduces sound wave transmission.

Suitable for use in walls, floors, ceilings, cars, and many other places, TechnoWall Acoustic MLV offers a premium acoustic barrier that can help reduce the sound level of many sources of noise pollution.

TechnoWall Acoustic MLV uses a proprietary blend of acoustical PVC compound and select inert materials to produce a high-quality Mass Loaded Vinyl product that is non-toxic and odorless, allowing ease of mind when installing!

TechnoWall Acoustic MLV is offered in rolls, making it both easy to move and store. Our TechnoWall MLV is also simple to install with the help of our step-by-step installation guide!

## **Physical Properties**

Tensile Strength	Elongation	Tear Resistance	FMVSS Standard NO 302	Thickness	STC Rating	Color
600 psi ASTM D412	125% ASTM D412	100 lb/f ASTM D412	Pass	<b>0.75 lb</b> - 3/32"	<b>0.75 lb</b> - 22	Black
				<b>1.00 lb</b> - 1/8"	<b>1.00 lb</b> - 26	
				2.00 lb - 1/4"	<b>2.00 lb</b> - 32	

## **Noise Reduction Characteristics**

MLV Weight	125 HZ	250 HZ	500 HZ	1000 HZ	2000 HZ	4000 HZ
0.75 lb	6 dB Loss	12 dB Loss	18 dB Loss	24 dB Loss	30 dB Loss	36 dB Loss
1.00 lb	9 dB Loss	15 dB Loss	21 dB Loss	27 dB Loss	33 dB Loss	39 dB Loss
2.00 lb	12 dB Loss	18 dB Loss	24 dB Loss	30 dB Loss	36 dB Loss	42 dB Loss