

## **Cabinet, Furniture and More**

BEYOND PAINT® is a revolutionary line of refinishing paints that use the most advanced Nano Technology; which allow you to complete your home projects in less time, with less effort, for less money.

Perfect for experts and beginners alike, leaving a lightly textured finish, with professional, durable results.

Surface must be CLEAN, DRY, GREASE, OIL and WAX FREE. BEYOND PAINT® is lightly textured to eliminate brush marks, provides a finish that conceals imperfections and offers versatility in application. Use less BEYOND PAINT® for a smoother finish; apply thicker for a more textured effect.

Recommended Tools:

1. Tray 2. Fabric or woven roller nap (3/8 inch nap) and handle. 3. Brush for stippling creviced areas.

Easy to Use Indoor Directions:

1. Using a soft bristle brush, simply “mush” or “stipple” into crevice areas. 2. Roll all possible areas (an all-purpose fabric roller is preferred.) 3. Avoid traditional brush strokes when using BEYOND PAINT® Furniture, Cabinets and More. 4. Two coats are recommended; allow 2-4 hour drying time between coats. 5. Clean up with soap and water.

Easy Outdoor Directions:

1. Follow above directions. 2. Allow to dry for at least 24 hours. 3. Apply two LIGHT coats of BEYOND PAINT® Multi-Purpose Sealer.

Easy Care Directions:

After 30 days curing time, maintain with mild soap and water as needed.

Finally ! Gorgeous Durable Countertops as easy as 1-2-3  
Roll, Fleck, Seal!

## **Countertop**

Surface must be CLEAN, DRY, GREASE, OIL, and WAX FREE. BEYOND PAINT® Countertop is slightly textured to eliminate the worry of brush marks, provide a finish that conceals imperfections and offers versatility in application. Use less BEYOND PAINT® Countertop for a smoother finish; apply thicker for a more textured effect.

**DIRECTIONS:** 1. Using a soft bristle brush, simply “mush” or “stipple” into crevice or hard to reach areas. 2. Roll as many areas as possible (a 5/8” fabric roller is preferred). 3. Traditional brush stroke techniques are not preferred when using BEYOND PAINT® Countertop. 4. Two coats are preferred; allow 1 -2 hour drying time between coats. 5. For design options see below. 6. Allow to cure for 24 hours before applying BEYOND PAINT® Multipurpose Sealer (see Sealer for directions).

## **DESIGN OPTIONS FOR APPLICATION**

1. **One color application:** apply 2+ coats as directed above
2. **One color plus BEYOND PAINT® Color Flecks:** Roll on your final coat of BEYOND PAINT® Countertop in small (approx 1 x 2') sections. Immediately shake the BEYOND PAINT® Color Flecks into the wet BEYOND PAINT® Countertop (see BEYOND PAINT® Color Flecks for directions).
3. **Two color granite finish:** Roll on 2 coats of one color. When dry, sponge on another color of BEYOND PAINT® Countertop. Work in small sections and shake the BEYOND PAINT® Color Flecks into the wet sponged BEYOND PAINT® Countertop.

**Seal all BEYOND PAINT® Countertop and outdoor projects with BEYOND PAINT® Multipurpose Sealer as directed.**

For 16 oz jar  
Drying time 1-2 hrs/coat  
Covers 50 sq ft with 2 coats

**BEYOND PAINT® Multipurpose Sealer** is a safe, water-based, interior/exterior sealer formulated to protect your most challenging BEYOND PAINT® projects. Use on outdoor furniture, countertops, and any project that requires extra-strength durability. Self-leveling for a smooth finish and renewable due to easy touch up technology.

#### **EASY TO USE DIRECTIONS**

1. BEYOND PAINT® Multipurpose Sealer may be applied to any BEYOND PAINT® or BEYOND PAINT® Countertop surface that has dried for at least 24 hours.
2. Stir thoroughly.
3. Roll as many areas as possible (a 5/8" fabric roller is preferred).
4. Brush out crevice areas with a high quality synthetic or natural bristle brush. (Note: BEYOND PAINT® Multipurpose Sealer will roll on milky but dry clear)
5. 2<sup>nd</sup> coat may be applied after 2 -4 hours.
6. Allow to dry overnight (minimum 8 hours) before using.
7. Reapply BEYOND PAINT® Multipurpose Sealer as needed.

\*Initial curing period is 3 days; during this time standing moisture will cause surface to cloud but will clear when moisture is removed from surface. Allowing each applied layer of BEYOND PAINT® Countertop and BEYOND PAINT® Multipurpose Sealer to dry for as long as possible will add to quick cure time and optimal durability. Protect your BEYOND PAINT® Countertop from extreme heat and direct cutting as you would on any Countertop surface.

#### **Proper Use and Ingredients:**

Use and application of this product are beyond the control of the manufacturer, distributor and dealer. Liability, if any, is limited to replacement only if product is proven to be defective in manufacturing.