

Gorilla Waterproof Patch & Seal Spray is a flexible, rubberized coating that seals out water, air and moisture. The applicator nozzle has a controlled spray pattern providing a clean, even coat. Once applied, the self-leveling formula smoothly covers small gaps and cracks ensuring a watertight seal. When dried, Gorilla Waterproof Patch & Seal Spray is paintable and temperature/UV resistant resulting in lasting repairs!

GREAT FOR:

Metal, Concrete, Wood, Aluminum, Brick, Tile,
Fabric, Rubber**, Glass & More!

FEATURES & BENEFITS:

Creates a Protective Coating	Self-leveling
Seals Out Water, Air & Moisture	Flexible
Temperature & UV Resistant	Paintable
Controlled Spray Pattern	

DIRECTIONS:

1. Clean surface of dirt, dust, grease and oil.
Make sure surface is dried completely.
2. Shake well. Spray 8" - 12" from surface, covering evenly.
A test spray on a disposable object is recommended before applying to your project.
3. Apply multiple coats to ensure all cracks and holes have been filled. Allow to cure in between coats and before water exposure. Full cure at 24 hours.

NOTE: Test finished project with light water exposure to ensure all cracks have been filled. If test fails, apply additional coats. Do not use for gaps larger than 1/4". Apply between 50°F & 120°F.

PAINTING: Works with both latex and oil based paints. When coating with oil based paints, use a primer first before painting.

TIP: To avoid possible clogging, turn can away from body towards a disposable object, turn upside down and spray a short jet of clear gas after completing job.

*For exterior use only. Not intended for inside of firebox or chimney stack.

**May not work for all types of plastics and rubbers