
WAC FANS LIMITED





PRODUCT DESCRIPTION

Mocha renders a youthful take on a timeless model that has something every generation can agree on. This smart-looking fan stands out in a stainless steel aesthetic or blend into a time honored style with a versatility matched by high performance in large spaces. Make it smart by downloading the app for additional functionality.

SPECIFICATIONS

Construction: Aluminum Blade: 14° Pitch, 54" sweep, ABS Downrod: 3/4"W X 4.5"H included Mounting Slope: Up to 30°

Wire: 80"

Hanging Weight: 17 lbs **Total Power**: 45W

Standards: UL/cUL Wet Location listed, Title 24 Compliant, Title 20 Compliant, Energy Star Rated

FEATURES

- 6 fan speeds through both Summer and Winter Modes
- Silent DC motor
- Optional luminaire cover included
- Includes remote control with wall cradle
- Wall control for 3, 4-way control sold separately
- Compatible with WAC app

LUMINAIRE PERFORMANCE

Light Source: LED Light Wattage: 20W **Dimming**: Integrated **Color Temperature**: 3000K Rated Life: 50,000 Hours

AIRFLOW/ENERGY EFFICIENCY

Airflow CFM: 4122 (weighted-average)/6477 (high) Energy Use (W): 17 (weighted-average)/22.5 (high) Estimated Yearly Energy Cost (\$): 5 (weighted-average) Efficiency (CFM/W): 241 (weighted-average)/288 (high)

Motor Type

DC-125NS sensorless DC motor

ORDER NUMBER

Model	LED Lumens	Delivered Lumens	Housing			Blade
F-001L	1600	846	BA MB MW	Brushed Aluminum Matte Black Matte White	TT MB MW	Titanium Silver Matte Black Matte White

Example: F-001L-MB

The WAC app synchronizes seamlessly with smart home devices you already own













WAC FANS LIMITED

F-001L

OPTIONAL ACCESSORIES									
Bluetooth Wall Control RC20			wt	White	Control fan speed and light brightness, and switch between Summer and Winter Modes. Additional Wall Controls can be purchased separately for multiple location control.				
Riuteaath Remate Control									
	WC20		wt	White	Control fan speed and light brightness, and switch between Summer and Winter Modes. Compatible with WAC Smart Fans. Includes easy-to-install wall cradle and batteries.				
Downrod	XF-12	12in			All our downrods are 1" O.D. and are threaded on the				
	XF-18	18in		Brushed Aluminum	motor end to create an extra layer of security and allow for adjustments in the field.				
	XF-24	24in							
	XF-36	36in							
	XF-48	48in	BA						
	XF-60	60in							
100	XF-72	72in							
Downrod Couplers	XF-I		BN MB MW	Brushed Nickel Matte Black Matte White	Connects two downrods together.				
Sloped Ceiling Kit XF-SCK					Designed to accommodate buildings with steeper sloped ceilings up to 45° or 12/12 pitch.				

Examples: Wall Control - WC20-WT, Remote Control - RC20-WT, Downrod - XF-12-BN, Downrod Coupler - XF-I-MB, Sloped Ceiling Kit - XF-SCK-MW

SUGGESTED DOWNROD HEIGHT USAGE

Ceiling Height	15′	14′	13'	12'	11′	10′	9′
Downrod	72"	60"	48"	36"	24"	18"	12"

SLOPED CEILING DEGREE CONVERSION CHART

Degree	4-8°	9-13°	14-17°	18-21°	22-25°	26-29°	30-32°	33-35°	36-38°	39-41°	42-44°	45°
Ceiling Slope	1/12	2/12	3/12	4/12	5/12	6/12	7/12	8/12	9/12	10/12	11/12	12/12
Pitch	pitch	pitch	pitch	pitch	pitch	pitch	pitch	pitch	pitch	pitch	pitch	pitch

Supplied mounting brackets allow mounting on ceiling slopes up to 30° (7/12 pitch). Optional slope kit allows mounting on ceilings up to 45° (12/12 pitch). The receiver will mount inside canopy up to 45°.

NOTE: Recommended maximum downrod length of 72" with 80" lead wire

**Carbon Fiber downrods available in 12", 18", 24" and 36"

www.WACLighting.comHeadquarters/Eastern Distribution CenterPhone (866) 810.661544 Harbor Park DriveFax (800) 526.2585Port Washington, NY 11050

Central Distribution Center 1600 Distribution Ct Lithia Springs, GA 30122 Western Distribution Center 1750 Archibald Avenue Ontario, CA 91760

[†]Koa downrods available in 12", 18", 24" and 36"