

Read carefully before application. Thank you for purchasing Timeline Oak Shiplap.

There are a variety of ways that this product can be applied. Here is an overview:

NAILING:

Each panel is easy-to-install with a pneumatic brad nailer or micro nailer. Brad nailers use 18 gauge nails that have low visibility while micro nailers use 24 gauge nails. When nailing over a substrate such as drywall, you should purchase a brad nail that will penetrate the thickness of the shiplap, drywall, and then into a framing stud if you are not using panel adhesive on the back. If you can't nail into a framing stud, this is where panel adhesive helps!

PANEL ADHESIVE:

Our shiplap products can be applied over 1/2" shearing gypsum or any wood paneling with a wood paneling adhesive. Follow the adhesive manufacturer's suggested instructions in regards to the proper application of the adhesive. Apply a zig-zag bead of panel adhesive on the back of the board. Apply the board to the wall and hold until it is set, or for faster installation, use a nail to hold it while the panel adhesive dries. The shiplap edge will overlap and cover up the nail holes if you only nail into the tongue portion.

HORIZONTAL INSTALLATION:

Begin in one corner of the floor and install your first panel using a level. This ensures your paneling will be level. Install the first board leaving 1/4" space between the floor and the board for expansion. If you are nailing, you can nail into the tongue portion of the board so the next board overlaps and covers the nail hole. This helps limit the need for nails on the face of each board.

VERTICAL INSTALLATION:

Begin in one corner of the floor and install your first panel using a level. This ensures your paneling will be level. Install the first board leaving 1/4" space between the floor and the board for expansion. If you are nailing, you can nail into the tongue portion of the board so the next board overlaps and covers the nail hole. This helps limit the need for nails on the face of each board.

TOUCH-UP PAINT& TRIM OPTIONS:

We have matching touch-up paint for each of our colors that works perfect for small nicks or any mistakes made while cutting. We also have several trim options available for all your installation needs. Please visit timelinewood.com.

CARE & USE:

For our products that are pre-painted, use a smooth rag with water and lightly wipe boards to clean minor spills, . If you need to clean a spill that has dried, use mild soap and water. Do not use oil-based cleaning supplies or wipe aggressively. For products that are unfinished/raw lumber, do not use water or any cleaning materials for spills. Products that are unfinished require a finish to be applied before cleaning spills.

LIMITED LIFETIME WARRANTY

For interior use only. Not recommended as a flooring application. If this Timeline Shiplap product, when applied in accordance with label instructions, fails to perform due to peeling or flaking for as long as you, the original owner, have it installed in the original installation location, then we will either replace the single wooden panel free of charge or refund the purchase price, upon presentation of proof of purchase and damaged board. This warranty, which excludes failure due to deterioration of the underlying surface, structural defects or any additional paint or coatings applied during or after installation, extends only to the original owner to which the product was originally installed during such owner's occupancy, may not be transferred or assigned, and is your sole remedy.

THIS WARRANTY DOES NOT INCLUDE LABOR OR THE COST OF LABOR FOR THE APPLICATION OF ANY PRODUCT, AND EXCLUDES ANY INCIDENTAL OR CONSEQUENTIAL DAMAGES