



CAN BE USED AS A TRAILER OR CART

LG600

SPECIFICATIONS:

Model Number	10539	
Part Number	110539	
Load Capacity:	600 lbs	
Level Load Size:	7 Cubic Feet	
Overall Dimensions:	71" x 33" x 30"	
Overall Weight:	55 lbs.	
Body Dimensions:	45" x 33" x 12"	
Tire Size:	15"x4.8"	
Instruction P/N	104834	



NOTICE: Once used, this trailer cannot be returned to the store. If you have a warranty claim, please read and follow Warranty Information directions below.

WARRANTY INFORMATION

CLAM OUTDOORS INC. warrants to the original retail purchaser its product be free from manufacturers defects for (3) years from the date of the original purchase. Clam Outdoors Inc will replace or repair any part found defective within the (3) years time limit. All parts must be returned to Clam Outdoors Inc. Before returning any parts, you must first call or write and acquire a return authorization. All returns must be returned postage-prepaid and include the original cash register receipt (date and purchase price).

To submit a warranty claim request, please use one of the following methods:

- Customer Service Hrs: 9am to 4pm, Monday Friday Central Standard Time
 - Clam Corporation Attn: Customer Service – Warranty Department 12135 Brockton Lane Rogers, MN 55369 Phone: 763-231-4120
- Fax: 763-231-4121
- Email: customerservice@clamcorp.com
- Website: Clamoutdoors.com

The warranty does not apply to any Polar Trailer which has been subjected to an accident, improper installation, modification, adjustment, repair, misuse, misapplication, neglect, including but not limited to improper maintenance, or use of unauthorized parts or attachments.

LIMITATION OF LIABILITY

It is expressly understood that Clam Outdoors Inc. liability for its products, whether due to breach of warranty, negligence, strict liability, or otherwise, is limited to the repair of the product as stated above. Clam Outdoor Inc. is not liable for any injury, loss, damage, or expense, whether direct or consequential, including but not limited to loss of use, income, profit, or damage to material arising in connection with the sale, installation, use of, inability to use, or the repair or replacement of Clam Outdoor Inc. products. Clam Outdoor Inc. reserves the right to make alterations or modifications in its products at any time, which in its opinion, may improve the performance and efficiency of the product. It shall not be obligated to make such alterations or modifications to products already in service.

WARNING:

- THIS ATTACHMENT IS INTENDED FOR USE IN LAWN CARE AND HOME APPLICATIONS.
- **DO NOT TOW BEHIND A VEHICLE ON A HIGHWAY OR IN ANY HIGH SPEED APPLICATION.**
- THIS PRODUCT HAS BEEN DESIGNED FOR OFF-ROAD USE ONLY.
- MAXIMUM TOW SPEED IS 10 MPH.

THE FOLLOWING STATEMENTS ARE SUGGESTIONS AND DO NOT SUPERCEDE OR ELIMINATE ANY TOWING AND SAFETY INSTRUCTIONS LISTED IN ANY OWNERS MANUALS FOR ANY PRODUCT BEING USED FOR THE PURPOSE OF TOWING ANY CLAM OUTDOORS INC. PRODUCTS. ALWAYS REFER TO THE TOWING VEHICLES MANUAL, GUIDELINES OR INSTRUCTIONS.

Transporting Loads Safely

- Stopping distance increases with speed and weight of towed load. Travel slowly and allow extra time and distance to stop.
- Total towed weight must not exceed limits specified in towing vehicle operator's manual.
- Excessive towed load can cause loss of traction and loss of control on slopes. Reduce towed weight when operating on slopes.
- Never allow children or others in or on towed equipment.
- Use only approved hitches. Tow only with a machine that has a hitch designed for towing. Do not attach towed equipment except at the approved hitch point.
- Follow the manufacturer's recommendations for weight limits for towed equipment and towing on slopes.
- Do not turn sharply. Use additional caution when turning or operating under adverse surface conditions. Use care when reversing.
- Do not shift to neutral and coast downhill

Protect Bystanders

- Keep bystanders away when you operate a towed attachment.
- Before you back machine and attachment, look carefully behind attachment for bystanders.

Keep Riders off Towed Attachment

- Keep riders off of a towed attachment.
- Riders on a towed attachment are subject to injury, such as being struck by objects and being thrown off the attachment during sudden starts, stops and turns.
- Riders obstruct the operator's view, resulting in the attachment being used in an unsafe manner.
- Keep riders off of the hitch bracket or trailer tongue.

PARTS LIST

QTY.	PART NO.	DESCRIPTION
1	104856	WLDMT, LG600 STAND
1	104834	INSTRUCTION, LG600 TRAILER
1	104864	BASE, LG600, HYBRID
1	104851	ASSY, TUBE CAP, HANDLE
1	104833	INNERPACK, LG600 TRAILER
2	104839	ASSY, 8" RIM/TIRE
1	104849	ASSY, TONGUE, PEDAL RELEASE
1	102564	ASSY, U-FRAME WELDMENT AND END CAPS
1	103826	AXEL WELDMENT
1	102569	PIVOT TUBE CONNECTOR
1	104866	KIT, HDWR, LG600
8	101740	NUT, 3/8-16 NYLOCK
8	101741	WASHER, 3/8" FLAT REG
3	102576	BOLT, 3/8-16 X 2.50 CH GR2 CZ
1	101802	BOLT, 3/8-16 X 3.25 CH GR2 CZ
3	102201	SPRING COTTER PIN
2	102589	PLUG, TUBE, 1.5 SQUARE
4	103280	WASHER, SQUARE, TRAILERS
4	102582	SCREW, 3/8-16 X 1.75 PTHMSCZ GR. 2
4	102607	WASHER, .75 USS SAE STANDARD CZ
4	102605	SCREW,5/16-18 X 1.75 THMSCZ
4	102035	WASHER, 5/16 WIDE FLAT
4	102606	5/16 - 18 THIN NYLOCK CZ
1	102200	BENT ARM PIN

STEP 1



Attach the Pivot Tube, (102569), Hitch Tube Assembly, (104849) and Tires (102607) as shown.

TIP: Leave all of the fasteners slightly loose until the end of the assembly, this will aid greatly in the assembly process.

STEP 2

Attach the U-Frame Weldment, (102564) to the assembly from Step 1.



STEP 3

Attach the Base, (103824) to the assembly from Step 2. *Tighten all of the fasteners at this time.*



STEP 4





REVERSE OPERATIONS TO CHANG BACK TO TRAILER

VISIT OUR WEB-SITE FOR ADDITIONAL ACCESSORIES THAT MAY BE AVAILABLE FOR YOUR TRAILER

Cover your trailers load with the Trailer Travel Cover, PN 108382.

