



Technical Data Sheet

Ryobi Lithium-Ion Battery Pack

Battery Voltage: 40V

Battery Capacity: 6Ah / 216Wh

SECTION 1: PRODUCT AND COMPANY IDENTIFICATION

Product Name: Lithium-Ion Battery – Rechargeable

Model Number:

GP40602

Issue Date:

August 2019

Techtronic Industries Power Equipment

P.O. Box 1288

Anderson, SC 29622

Company Phone Number:

1-800-860-4050

Emergency Contact Number:

Chemtrec (United States only): 1-800-424-9300

(International): +1-703-741-5970

SECTION 2: HAZARDS IDENTIFICATION

Refer to battery cell SDS for more information.

No exposure to hazards during routine handling of product.

▲ WARNING:

- To reduce the risk of injury, user must read operator's manual.
- Risk of fire and burns.
- Do not open, crush, heat above 50°C, incinerate, or short terminals.
- Follow manufacturer's instructions.
- Use only with charger listed in operator's manual.
- Remove battery from tool when storing, changing attachments, or making adjustments.
- To reduce the risk of explosion and possible injury, do not place battery near fire or heat.
- Do not crush, drop, or damage battery pack.
- Do not use a battery pack that has been dropped or received a sharp blow. A damaged battery is subject to explosion. Properly dispose of a dropped or damaged battery immediately.
- Under extreme usage or temperature conditions, battery leakage may occur. If fluid comes in contact with your skin, wash immediately with soap and water. If fluid gets into your eyes, flush them with clean water for at least 10 minutes, then seek immediate medical attention. Following this rule will reduce the risk of serious personal injury.
- Battery cells and battery pack assembly will burn if incinerated.

SECTION 3: COMPOSITION/INFORMATION OF INGREDIENTS

Refer to battery cell SDS for more information.

SECTION 4: FIRST AID MEASURES

Refer to battery cell SDS for more information.

No exposure to hazards during routine handling of product.

▲ WARNING:

- To reduce the risk of injury, user must read operator's manual.
- Risk of fire and burns.
- Do not open, crush, heat above 50°C, incinerate, or short terminals.
- Follow manufacturer's instructions.
- Use only with charger listed in operator's manual.
- Remove battery from tool when storing, changing attachments, or making adjustments.
- To reduce the risk of explosion and possible injury, do not place battery near fire or heat.
- Do not crush, drop, or damage battery pack.
- Do not use a battery pack that has been dropped or received a sharp blow. A damaged battery is subject to explosion. Properly dispose of a dropped or damaged battery immediately.
- Under extreme usage or temperature conditions, battery leakage may occur. If fluid comes in contact with your skin, wash immediately with soap and water. If fluid gets into your eyes, flush them with clean water for at least 10 minutes, then seek immediate medical attention. Following this rule will reduce the risk of serious personal injury.
- Battery cells and battery pack assembly will burn if incinerated.
- No exposure during routine handling of product. Risk of exposure occurs only if the battery is mechanically or electrically abused.
- No effect under routine handling and use to eyes, skin, or if inhaled. Ingestion is not likely, given the physical size and state of the cell. If swallowed, seek medical attention immediately.
- If exposure to internal materials within cell due to damaged outer casing, the following actions are recommended:

EYE CONTACT:

Flush with water for 10 minutes without rubbing and immediately seek medical attention.

SKIN CONTACT:

Wash area immediately with soap and water. If irritation continues, seek medical attention.

INHALATION:

Leave area immediately, move to fresh air, and seek medical attention.

INGESTION:

If swallowed, contact POISON CONTROL CENTER immediately.

SECTION 5: FIRE FIGHTING MEASURES

Refer to battery cell SDS for more information.

SECTION 6: ACCIDENTAL RELEASE MEASURES

PERSONAL PRECAUTIONS:

- Use standard industrial clothing in normal use.
- If handling large containers of cells, wear steel-toed footwear.

ENVIRONMENTAL PRECAUTIONS:

No special precautions necessary.

METHODS FOR CONTAINMENT:

- Transport container outdoors.
- Always consult and obey all international, federal, and local environmental laws.

METHODS FOR CLEANUP:

No data available

OTHER INFORMATION:

No data available

SECTION 7: HANDLING AND STORAGE

HANDLING:

- Use only approved charging equipment.
- Do not disassemble battery or battery pack.
- Do not puncture, crush, or dispose of in fire.

STORAGE:

To obtain the longest possible battery life, we suggest the following:

- Remove the battery pack from the charger once it is fully charged and ready for use.

For battery pack storage longer than 30 days:

- Store the battery pack where the temperature is below 80°F and away from moisture.
- Store battery packs in a 30%-50% charged condition.
- Every six months of storage, charge the pack as normal.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

Refer to battery cell SDS for more information.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Battery pack consists of battery cells assembled in resin enclosure and is a solid odorless product that will burn if incinerated.

SECTION 10: STABILITY AND REACTIVITY

Refer to battery cell SDS for more information.

No exposure to hazards during routine handling of product.

▲ WARNING:

- To reduce the risk of injury, user must read operator's manual.
- Risk of fire and burns.
- Do not open, crush, heat above 50°C, incinerate, or short terminals.
- Follow manufacturer's instructions.
- Use only with charger listed in operator's manual.
- Remove battery from tool when storing, changing attachments, or making adjustments.
- To reduce the risk of explosion and possible injury, do not place battery near fire or heat.
- Do not crush, drop, or damage battery pack.
- Do not use a battery pack that has been dropped or received a sharp blow. A damaged battery is subject to explosion. Properly dispose of a dropped or damaged battery immediately.
- Under extreme usage or temperature conditions, battery leakage may occur. If fluid comes in contact with your skin, wash immediately with soap and water. If fluid gets into your eyes, flush them with clean water for at least 10 minutes, then seek immediate medical attention. Following this rule will reduce the risk of serious personal injury.
- Battery cells and battery pack assembly will burn if incinerated.

SECTION 11: TOXICOLOGY INFORMATION

Refer to battery cell SDS for more information.

No exposure to hazards during routine handling of product.

▲ WARNING:

- To reduce the risk of injury, user must read operator's manual.
- Risk of fire and burns.
- Do not open, crush, heat above 50°C, incinerate, or short terminals.
- Follow manufacturer's instructions.
- Use only with charger listed in operator's manual.
- Remove battery from tool when storing, changing attachments, or making adjustments.
- To reduce the risk of explosion and possible injury, do not place battery near fire or heat.
- Do not crush, drop, or damage battery pack.
- Do not use a battery pack that has been dropped or received a sharp blow. A damaged battery is subject to explosion. Properly dispose of a dropped or damaged battery immediately.
- Under extreme usage or temperature conditions, battery leakage may occur. If fluid comes in contact with your skin, wash immediately with soap and water. If fluid gets into your eyes, flush them with clean water for at least 10 minutes, then seek immediate medical attention. Following this rule will reduce the risk of serious personal injury.
- Battery cells and battery pack assembly will burn if incinerated.

SECTION 12: ECOLOGICAL INFORMATION

ECOTOXICOLOGICAL INFORMATION:

None in routine handling of product.

TOXICITY:

No data available

PERSISTENCE AND DEGRADABILITY (BIOPERSISTENCY & BIODEGRADABILITY):

None in routine handling of product.

POTENTIAL OF BIOACCUMULATION:

None in routine handling of product.

MOBILITY IN SOIL:

None in routine handling of product.

OTHER ADVERSE EFFECTS:

No data available

DISPOSAL:

Follow guidelines in Section 13.

SECTION 13: DISPOSAL CONSIDERATIONS

This product contains Lithium-ion batteries. Local, state or federal laws may prohibit disposal of batteries in ordinary trash. Consult your local waste authority for information regarding available recycling and/or disposal options.

DISPOSAL:

- Dispose in accordance with appropriate regulations.
- Always consult and obey all international, federal, provincial/state, and local hazardous waste disposal laws. Some jurisdictions require recycling of this spent product. Battery recycling is encouraged.
- Lithium-ion batteries are safe for disposal in the normal municipal waste stream since they are not defined by the federal government as hazardous waste. However, Lithium-ion batteries are recyclable.
- To preserve natural resources, please recycle or dispose of batteries properly.

▲ WARNING:

- Upon removal, cover the battery pack's terminals with heavy-duty adhesive tape.
- Do not attempt to destroy or disassemble battery pack or remove any of its components.
- Batteries must be recycled or disposed of properly.
- Also, never touch both terminals with metal objects and/or body parts as short circuit may result.
- Keep away from children. Failure to comply with these warnings could result in fire and/or serious injury.
- This product does not contain mercury, cadmium or Lithium (metal).
- DO NOT INCINERATE battery cells.

SECTION 14: TRANSPORTATION INFORMATION

U.S. DOT Hazardous Material Regulations (Re: Ground Transport)

UN3480 Lithium-ion batteries over 101 watt hours or UN3481 Lithium-ion batteries packed with equipment over 101 watt hours when packaged correctly can travel under 49 CFR 173.185 when travelling by ground in the continental U.S. Must have the IACO label (UN3480 for batteries only, UN3481 for batteries packed with equipment).

Canada Transport Dangerous Goods (Re: Ground Transport)

UN3480 Lithium-ion batteries over 101 watt hours or UN3481 Lithium-ion batteries packed with equipment over 101 watt hours when traveling by ground in Canada must be declared as Dangerous Goods. The batteries must be packaged according to Packing Instruction 965. The following labels must be on the package: DG9 diamond, Red Bordered Lithium-ion warning label (ICAO). The package must also include a UN3480 Lithium-ion batteries label with the net weight of the batteries in kgs. The BOL must also state UN3480, Lithium-ion batteries,9,PGII or UN3481 Lithium-ion batteries packed with equipment,9,PGII.

International Dangerous Goods Regulations (Re: Air, Sea, Ground Transport)

UN3480 Lithium-ion batteries over 101 watt hours or UN3481 Lithium-ion batteries over 101 watt hours packed with equipment when shipped by sea will be considered Class 9 Dangerous Goods must be packaged according to Packing Instruction 965, and contain the following labels: DG9 diamond, Red Bordered Lithium-ion warning label (ICAO), and UN3480/3481 label with the kg of lithium label.

UN3480 Lithium-ion batteries over 101 watt hours or UN3481 Lithium-ion batteries over 101 watt hours packed with equipment when shipped by air will be considered Class 9 Dangerous Goods must be packaged according to Packing Instruction 965, and contain the following labels: DG9 diamond, Red Bordered Lithium-ion warning label (ICAO), Cargo Aircraft Only, and a label stating the amount of kgs of lithium in the box.

This rechargeable Lithium-ion battery has passed the relevant transportation test requirements as described in the UN Manual of Tests and Criteria, Part III, section 38.3. UN 38.3 Test Reports are maintained by the company.

SECTION 15: REGULATORY INFORMATION

Compliant with relevant transportation test requirements as described in the UN Manual of Tests & Criteria, Part III, Sub section 38.3.

CALIFORNIA PROPOSITION 65

⚠ **WARNING: Cancer and Reproductive Harm – www.P65Warnings.ca.gov**

SECTION 16: OTHER INFORMATION

The information contained within this document is provided for your information only. In case of any discrepancy, the information provided in the battery cell Safety Data Sheet takes precedence over the information provided in the battery pack Technical Data Sheet.

Prepared by: Techtronic Industries Power Equipment

The batteries referenced herein are considered exempt articles and are not subject to the OSHA Hazard Communication Standard; therefore an SDS is not required. This sheet is being provided as a service to our customers.

The information and recommendations set forth are made in good faith and believed to be accurate as of the date of preparation. TECHTRONIC INDUSTRIES POWER EQUIPMENT makes no warranty, expressed or implied, regarding the accuracy of this data or the results to be obtained from the use thereto.

PONY

Pony Testing International Group

Report No.: MDIKXCJN51541716

MSDS Report

Sample
Description & Model
Lithium-ion Cell ICR18650/20P

Applicant
EVE Energy Co., Ltd

Address
NO.36,HuiFeng7thRoad,ZhongkaiHi-TechZone,HuiZhou,
Guangdong,China

No.: MDIKXCJN51541716
Code: mt92f0z



PONY 博尼测试
Pony Testing International Group

www.ponytest.com

☎Hotline: 400-819-5688

北京分公司: 0100-8878116

上海分公司: 0212218701886

天津分公司: 0222-2726100

广州分公司: 020-8117517008

深圳分公司: 0755-26680008

杭州分公司: 0571-22035560

长沙分公司: 0731-6882599

成都分公司: 028-87526100

武汉分公司: 027-87219006

西安分公司: 029-2620000

重庆分公司: 0230-8921110

南京分公司: 025-81591122



Pony Testing International Group

Report No.: MDIKXCJN51541716 Date: 03.28.2016 Page 1 of 13

Material Safety Data Sheet

Reference to GHS/AC.10/30/Rev.6 (GHS)

Section 1 - Chemical Product and Company Identification

Chemical product identification

Sample Description: Lithium-Ion Cell

Sample Model: ICR18650/ZOP

Recommended Uses: N/A

Restrictions on Use: N/A

Supplier name: EVE Energy Co., Ltd

Address: NO.36, HuiFeng 7th Road, Zhongkai Hi-Tech Zone, HuiZhou, Guangdong, China

Phone number: 0752-5751932

FAX: 0752-2608033

E-mail: 018138@evebattery.com

Emergency phone number: 0752-5751932

Section 2 - Hazards Identification

Emergency overview: This product is an article which contains a chemical substance. Safety information is given for exposure to the article as sold. Intended use of the product should not result in exposure to the chemical substance. This is a battery. In case of rupture, the below hazards exist.

CAS# 1333-86-4

Classification according to GHS

Carcinogenicity (2)

Specific target organ toxicity, repeated exposure (1) (lung)

Label elements

Hazard pictogram(s):



Signal word:

Danger

Hazard statement(s):

H351 Suspected of causing cancer

H372 Causes damage to organs through prolonged or repeated exposure (lung)



PONY

Report No. : MDKXGJN51541716 Date:03.28.2016 Page 2 of 13

Pony Testing International Group

Precautionary statement(s):

Prevention:

- P201 Obtain special instructions before use.
- P202 Do not handle until all safety precautions have been read and understood.
- P280 Wear protective gloves, protective clothing, eye protection and face protection.
- P260 Do not breathe dust.
- P264 Wash skin and clothing thoroughly after handling.
- P270 Do not eat, drink or smoke when using this product.

Response:

- P308 + P313 IF exposed or concerned: Get medical advice.
- P314 Get medical advice if you feel unwell.

Storage

- P405 Store locked up.

Disposal:

- P501 Contents handling to approved waste treatment plants.

CAS# 616-38-6

Classification according to GHS

Flammable liquids (2)

Specific target organ toxicity, single exposure; Narcotic effects (3)

Reproductive toxicity (2)

Label elements

Hazard pictogram(s):



Signal word:

Danger

Hazard statement(s):

- H225 Highly flammable liquid and vapour.
- H336 May cause drowsiness or dizziness.
- H361 Suspected of damaging fertility or the unborn child.

Precautionary statement(s):

Prevention:

- P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- P233 Keep container tightly closed.
- P240 Ground and bond container and receiving equipment.
- P241 Use explosion-proof equipment.

PONY 尼测试
Pony Testing International Group

www.ponytest.com

Hotline 400-819-5688

北京分公司: 010-88111116	西安分公司: 029-88111116	上海分公司: 021-68811116	深圳分公司: 0755-88111116
天津分公司: 022-88111116	成都分公司: 028-88111116	广州分公司: 020-88111116	武汉分公司: 027-88111116
南京分公司: 025-88111116	重庆分公司: 023-88111116	杭州分公司: 0571-88111116	青岛分公司: 0532-88111116
沈阳分公司: 024-88111116	昆明分公司: 0871-88111116	福州分公司: 0591-88111116	郑州分公司: 0371-88111116



Pony Testing International Group

- P242 Use non-sparking tools.
- P243 Take action to prevent static discharges.
- P280 Wear protective gloves, protective clothing, eye protection and face protection.
- P261 Avoid breathing gas, mist, vapours and spray.
- P271 Use only outdoors or in a well-ventilated area.
- P201 Obtain special instructions before use.
- P202 Do not handle until all safety precautions have been read and understood.

Response:

- P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.
- P370 + P378 In case of fire: Use the appropriate media put out the fire.
- P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
- P312 Call a POISON CENTER or doctor, if you feel unwell.
- P308 + P313 IF exposed or concerned: Get medical advice.

Storage

- P403 + P235 Store in a well-ventilated place. Keep cool.
- P403 + P233 Store in a well-ventilated place. Keep container tightly closed.
- P405 Store locked up.

Disposal:

- P501 Contents handling to approved waste treatment plants.

CAS# 7440-60-8

Classification according to GHS

- Specific target organ toxicity, single exposure; Respiratory tract irritation (3)
- Specific target organ toxicity, repeated exposure (1) (liver)
- Hazardous to the aquatic environment, long-term hazard (3)

Label elements

Hazard pictogram(s):



Signal word: Danger

Hazard statement(s):

- H335 May cause respiratory irritation
- H372 Causes damage to organs through prolonged or repeated exposure (liver)
- H412 Harmful to aquatic life with long lasting effects

Precautionary statement(s):



Pony Testing International Group

Prevention:

- P271 Use only outdoors or in a well-ventilated area.
- P260 Do not breathe dust.
- P264 Wash skin and clothing thoroughly after handling.
- P270 Do not eat, drink or smoke when using this product.
- P273 Avoid release to the environment.

Response:

- P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
- P312 Call a POISON CENTER or doctor, if you feel unwell.

Storage

- P403 + P233 Store in a well-ventilated place, Keep container tightly closed.

Disposal:

- P501 Contents or container handling to approved waste treatment plants.

CAS# 7429-90-6

Classification according to GHS

Specific target organ toxicity, repeated exposure (1) (Lung)
 Hazardous to the aquatic environment, long-term hazard (4)

Label elements

Hazard pictogram(s):



Signal word:

Danger

Hazard statement(s):

- H372 Causes damage to organs through prolonged or repeated exposure (Lung)
- H413 May cause long-lasting harmful effects to aquatic life

Precautionary statement(s):

Prevention:

- P260 Do not breathe dust.
- P264 Wash skin and clothing thoroughly after handling.
- P270 Do not eat, drink or smoke when using this product.
- P273 Avoid release to the environment.

Response:

- P314 Get medical advice if you feel unwell.

Storage

None.

Disposal:

www.ponytest.com

Hotline 400-819-8688



北京办事处 (010) 80181116	成都办事处 (028) 87150918	广州办事处 (020) 61052999	深圳办事处 (0755) 26052000
天津办事处 (022) 84700566	杭州办事处 (0571) 81010001	武汉办事处 (027) 87726600	佛山办事处 (0757) 83274210
郑州办事处 (0371) 27100730	长沙办事处 (0731) 84050020	昆明办事处 (0871) 67211000	海口办事处 (0898) 81997127
青岛办事处 (0532) 89611166	重庆办事处 (023) 68300070	西安办事处 (029) 63997900	银川办事处 (0951) 8560018



Pony Testing International Group

P501 Contents handling to approved waste treatment plants.

Other hazards

Physical and chemical hazards: See Section 10

Human health hazards: See Section 11

Environmental hazards: See Section 12

Section 3 - Composition/Information on Ingredients

Chemical characterization: Mixture.

Chemical Composition	CAS No.	EC#	Weight (%)
Lithium Manganese Nickel And Cobalt	---	---	<35
Carbon black	1333-86-4	215-609-9	<5
Sodium carboxy methyl cellulose	9004-32-4	618-378-6	<2
Polyvinylidene fluoride resin	24937-78-9	607-458-6	<2
Graphite	7782-42-5	231-955-3	<20
Phosphate(1-), hexafluoro-, lithium	21324-40-3	244-334-7	<5
1,3-Dioxolan-2-one	96-49-1	202-510-0	<5
Carbonic acid, dimethyl ester	616-35-6	210-478-4	<5
Copper	7440-50-8	231-169-6	<15
Aluminium	7429-90-5	231-072-3	<10

Section 4 - First Aid Measures

Description of first aid measures

General information No special measures required.

After eye contact

Flush eyes with plenty of water for several minutes while holding eyelids open. Get medical attention if irritation persists.

After skin contact

Remove contaminated clothing and shoes. Immediately wash with water and soap and rinse thoroughly. Wash clothing and shoes before reuse. If irritation occurs, get medical attention.



www.ponytest.com

☎Hotline 400-819-5688

北京总部: 010-82028118	天津总部: 022-58519999	上海总部: 021-50321000	深圳总部: 0755-26650099
广州总部: 020-87339000	武汉总部: 027-87111161	成都总部: 028-87726699	济南总部: 0531-82523119
大连总部: 0411-88667788	杭州总部: 0571-82523119	青岛总部: 0532-82523119	西安总部: 029-85991127
烟台总部: 0535-6666116	南京总部: 025-12345678	苏州总部: 0512-66667788	郑州总部: 0371-88889999



PONY

Pony Testing International Group

Report No.: MDIKXCJN51541716 Date:03.28.2016 Page 6 of 13

After inhalation

Remove victim to fresh area. Administer artificial respiration if breathing is difficult. Seek medical attention.

After swallowing

Do not induce vomiting. Get medical attention.

Personal protective equipment for first-aid responders: No data available.

Most important symptoms/effects, acute and delayed: No data available.

Indication of immediate medical attention and special treatment needed: No data available.

Section 5 - Fire Fighting Measures

Suitable extinguishing media:

Use extinguishing agent suitable for local conditions and the surrounding environment. Such as dry powder, CO₂.

Unsuitable extinguishing media:

No data available.

Specific Hazards arising from the chemical:

Special hazards arising from the substance or mixture

Battery may burst and release hazardous decomposition products when exposed to a fire situation. Lithium ion batteries contain flammable electrolyte that may vent, ignite and produce sparks when subjected to high temperature (>150°C (302°F)), when damaged or abused (e.g. mechanical damage or electrical overcharging); may burn rapidly with flare-burning effect; may ignite other batteries in close proximity.

Specific protective actions for fire-fighters:

Protective equipment: Wear self-contained respirator. Wear fully protective impervious suit.

Section 6 - Accidental Release Measures

Personal precautions:

Wear protective equipment. Keep unprotected persons away. Ensure adequate ventilation.

Protective equipment:

No data available.

Emergency procedures:

Remove ignition sources, evacuate area. Sweep up using a method that does not generate dust. Collect as much of the spilled material as possible, placed the spilled material into a suitable disposal container. Keep spilled material out of sewers, ditches and bodies of water.

PONY 谱尼测试
Pony Testing International Group

www.ponytest.com

Hotline: 400-819-5688

北京分公司: 010-83511116	天津分公司: (022) 83100088	上海分公司: 021-60851999	深圳分公司: 0755-26050809
青岛分公司: 0532-88750866	烟台分公司: 0535-380-0150	宁波分公司: 0574-87704499	广州分公司: 020-39026830
大连分公司: 0411-23509730	武汉分公司: 027-83460829	杭州分公司: 0571-82219090	武汉分公司: 027-83460829
济南分公司: 0531-6881180	郑州分公司: 0371-59350050	苏州分公司: 0512-69597002	厦门分公司: 0592-5834000



PONY

Pony Testing International Group

Report No. : MDIKXCJN51541716

Date:03.28.2016

Page 7 of 13

Environmental precautions:

Do not allow material to be released to the environment without proper governmental permits.

Methods and materials for containment and cleaning up:

All waste must refer to the United Nations, the national and local regulations for disposal.

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

Section 7 - Handling and Storage

Precautions for safe handling:

Consumption of food and beverage should be avoided in work areas.

Wash hands with soap and water before eating, drinking.

Ground containers when transferring liquid to prevent static accumulation and discharge.

Information about fire and explosion protection:

Batteries may explode or cause burns, if disassembled, crushed or exposed to fire or high temperatures. Do not short or install with incorrect polarity.

Conditions for safe storage, including any incompatibilities:

Requirements to be met by storerooms and receptacles

Store in a cool, dry, well-ventilated place.

Information about storage in one common storage facility

Keep away from heat, avoiding the long time of sunlight.

Further information about storage conditions

Keep container tightly sealed.

Specific and use

No data available.

Section 8 - Exposure Controls/Personal Protection

Control parameters

CAS No.	ACGIH	NIOSH	OSHA
1333-86-4	TLV-TWA 3.5mg/m ³	REL-TWA 3.5mg/m ³	PEL-TWA 3.5mg/m ³
9004-32-4	N/A	N/A	N/A
24937-79-9	N/A	N/A	N/A

PONY 潜尼测试
Pony Testing International Group

www.ponytest.com

☎ Hotline 400-819-5688

北京分公司: 010-82015210
广东分公司: 010-82015210
天津分公司: 022-27340710
深圳分公司: 0755-26621186

武汉分公司: 027-85380608
成都分公司: 028-188138661
大连分公司: 0411-84888820
杭州分公司: 0571-56915620

上海分公司: 021-69411998
广州分公司: 020-87721690
南京分公司: 025-87210956
重庆分公司: 023-26709700

烟台分公司: 0535-2602000
青岛分公司: 0532-89724310
西安分公司: 029-83501123
沈阳分公司: 024-26215688



Pony Testing International Group

7782-42-6	TLV-TWA 2mg/m ³	REL-TWA 2.5mg/m ³	PEL-TWA 15mppcf PEL-TWA 20mppcf
21324-40-3	N/A	N/A	N/A
96-49-1	N/A	N/A	N/A
616-38-6	N/A	N/A	N/A
7440-50-8	TLV-TWA 0.2mg/m ³ TLV-TWA 1mg/m ³	REL-TWA 1mg/m ³ REL-TWA 0.1mg/m ³	PEL-TWA 0.1mg/m ³ PEL-TWA 1mg/m ³
7429-90-5	TLV-TWA 10mg/m ³ TLV-TWA 5mg/m ³	REL-TWA 2mg/m ³ REL-TWA 5mg/m ³ REL-TWA 10mg/m ³	PEL-TWA 5mg/m ³ PEL-TWA 15mg/m ³

Appropriate engineering controls:

The usual precautionary measures for handling chemicals should be followed.

Keep away from foodstuffs, beverages and food.

Remove all soiled and contaminated clothing immediately.

Wash hands before breaks and at the end of work.

Personal Protective Equipment

Respiratory protection: Wear suitable protective mask in order to reduce the respiratory system. A large number of leakage, wear chemical protective clothing, including self-contained breathing apparatus.

Hand Protection: Wear appropriate protective gloves to reduce skin contact.

Eyes Protection: Wear safety goggles or eye protection combined with respiratory protection.

Skin and Body Protection: Working environment required, wear suitable protective clothing to minimize contact with skin. The type of protective equipment must be according to the concentration and the content of certain hazardous substances in the workplace.

Section 9 - Physical and Chemical Properties

Information on basic physical and chemical properties

- Colour: Green.
- Physical State: Cylindrical.
- Odour: Not available.
- Odour threshold: Not available.
- pH: Not available.