

CONCRETE POLISH

USES

- ★ Polished interior concrete floors
- ★ Enhance newly stained floors
- ★ Restore luster to worn areas of previously sealed and polished floors

DESCRIPTION

EAGLE CONCRETE POLISH is a water-based acrylic & wax co-polymer which forms a tough abrasion resistant clear non-yellowing top coat polish to protect existing sealers and finishes as a finish on interior concrete floors. This co-polymer offers excellent gloss and can be stripped with conventional wax polish removers. Its toughness protects the existing finish and acts as a sacrificial coating for the hard sealed substrate. EAGLE CONCRETE POLISH resists scuffs and mars while enhancing the gloss of the finish below. EAGLE CONCRETE POLISH also increases slip resistance. It is designed to be applied on top of existing acrylic, polyurethane, and epoxy sealers. It is used on newly sealed floors and to restore shine on previously sealed concrete floors. EAGLE CONCRETE POLISH is available in GLOSS and MATTE finishes in one-gallon jugs and 5-gallon pails. MATTE will better hide scuffing and GLOSS will reflect more shine.

SURFACE PREPARATION

Floor should be clean, sealed and dry.

APPLICATION

Apply with lamb's wool, sponge mop, or micro-fiber applicator. 2 or 3 initial coats are preferred. Allow 30-60 minutes between coats to dry. Eagle CONCRETE POLISH can be buffed with high speed buffing machine but is not necessary. Allow 4 hours to cure and dry before foot traffic resumes. Re-apply as needed. High traffic areas can be touched up as needed.

Note: Streaking may occur if applied too thin. If streaking occurs apply another coat.

NET COVERAGE RATE

1000 ft² per gallon per coat. 2-3 coats may be preferred.

CLEAN UP

Clean up with water immediately after use.

MAINTENANCE

Cleaning of the polished surface should be accomplished using ONLY water or Pledge Multi-Surface cleaner and a soft mop. DO NOT USE aggressive cleaning agents, such as citrus-based, ammonia, or 409/Simple Green cleaners. Using an abrasive cleaning tool will scratch and dull the polished surface, requiring re-application of EAGLE CONCRETE POLISH to restore the shine.

TECHNICAL DATA

VOC: 67g/L
Flash Point: Non-combustible

HMIS

Health 0 Flammability 0
Reactivity 0 Protection 0

DISCLAIMER: Since manufacturer has no control over handling, use or storage; no guarantee expressed or implied, is offered. Eagle IFP warrants the product to be free of defects and will replace or refund the purchase price of said products proven defective. Labor cost and/or other consequential damages are not covered by this warranty. Responsibility for claims of any kind is strictly limited to the purchase price of the product. The suitability of the product for any extended use shall be solely up to the user.

Made in U.S.A

EAGLE IFP COMPANY

www.eaglesealer.com