T•A•P <sup>®</sup> PEST CONTROL INSULATION COVERAGE CHART (ATTICS)BAG WEIGHT: 30LBS												
R-Value @ 75°F	Initial Installed Thickness (in.)	Minimum Settled Thickness (in.)	Bags/ 1,000 Sq. Ft. 2"x6" Joists 16" On Ctr.	Net Coverage Sq. Ft./ Bag	2"v6" Injete	Net Coverage Sq. Ft. / Bag	Bags/ 1,000 Sq. Ft. No Joists	Net Coverage Sq. Ft. / Bag	Minimum Weight Per Sq. Ft. (Lbs.)			
11	3.4	3.1	11.9	84.3	12.2	81.7	13.1	76.5	0.39			
13	4.0	3.6	14.0	71.4	14.5	69.1	15.4	64.7	0.46			
19	5.8	5.3	20.5	48.8	21.1	47.3	22.6	44.3	0.68			
22	6.7	6.1	24.1	41.4	24.8	40.3	26.1	38.3	0.78			
30	9.2	8.3	33.6	29.7	34.3	29.2	35.6	28.1	1.07			
32	9.8	8.9	36.0	27.8	36.7	27.3	38.0	26.3	1.14			
38	11.6	10.6	43.2	23.2	43.8	22.8	45.2	22.1	1.35			
40	12.2	11.1	45.5	22.0	46.2	21.7	47.5	21.0	1.43			
44	13.4	12.2	50.3	19.9	50.9	19.6	52.3	19.1	1.57			
48	14.7	13.3	55.0	18.2	55.7	18.0	57.0	17.5	1.71			
49	15.0	13.6	56.2	17.8	56.9	17.6	58.2	17.2	1.75			
50	15.3	13.9	57.4	17.4	58.1	17.2	59.4	16.8	1.78			
60	18.3	16.7	69.3	14.4	69.9	14.3	71.3	14.0	2.14			

The listed values above are based on settled thickness and can be obtained only by an insulation applicator using equipment supplied by the manufacturer and specifically designed for the product and application techniques. R-Value (@4") 3.6 Attic Settled Density (LB/FT3) 1.7

T·A·P <sup>®</sup> PEST CONTROL INSULATION COVERAGE CHART (WALLS) BAG WEIGHT: 30LBS											
Dry Dense Pack Wall Applications											
Wall	Thermal Installed Resistance Thickness		Minimum Wt Per Square Foot	Maximum Coverage po Bag (Sq Ft)							
	R Value	Inches	lb/ft2	16" oc	24" oc						
2x4	13	3.5	1.02	32.0	31.3						
2x6	21	5.5	1.60	20.0	19.5						

This wall coverage chart is for dry applications only and is based on a minimum installed density of 3.55 lbs. pcf.



www.TAPinsulation.com