OLYMPIC® WATERGUARD® Clear Multi-Surface Waterproofer

WHERE TO USE: Recommended for use on exterior surfaces, such as concrete, brick, stucco, masonry, grout, mortar, terrazzo, wood, wood shingles, and outdoor wood furniture. Great for small projects, hard-to-reach areas, and touch-ups. DO NOT use on plastic, rubber, vinyl, tile, asphalt, or any sealed, nonporous surface.

COVERAGE: One can covers approximately 25 sq. ft. (2.3 sq. meters). Coverage figures do not include material loss due to surface irregularities and porosity, or material loss due to application method.

SURFACE PREPARATION: Surface must be clean and dry. Remove all dust, dirt, mildew, oil, loose peeling paint, and other contaminants. Previous coatings must be completely removed. To ensure proper penetration, weathered, dirty, or mildewed surfaces should be cleaned prior to application. After rinsing, allow to dry. Sand all glossy, rough, and patched surfaces.

WARNING! If you scrape, sand, or remove old paint, you may release lead dust or fumes. LEAD IS TOXIC. EXPOSURE TO LEAD DUST OR FUMES CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a properly fitted, NIOSH-approved respirator and prevent skin contact to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the USEPA National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead. Follow these instructions to control exposure to other hazardous substances that may be released during surface preparation.

PRETEST: To ensure proper penetration, apply on a small area before treating the entire surface. If the product is not quickly absorbed into the surface, the surface is not suitable for a waterproofing sealant.

APPLICATION: Use outdoors or in a well-ventilated area, such as an open garage. Cover surrounding area to protect from spray mist. Apply when no precipitation is expected for 24 hours, and when air and surface temperatures are 50°F (10°C) to 90°F (32°C) and will remain above 50°F (10°C) for the next 24 hours. Avoid spraying in very windy, dusty conditions. Shake can vigorously for one to two minutes. Shake often during use. Hold can upright 10" to 16" from the surface and spray in a steady back-and-forth motion, slightly overlapping each stroke. Keep the can the same distance from the surface. Keep the can in motion while spraying. Apply one light coat over the entire surface. Do not saturate surface. Tackiness will result if over applied, applied to a wet or damp surface, or if temperature falls below 50°F (10°C) within 24 hours of application.

DRYING: Normally dries to touch in five minutes at 77°F (25°C) and 50% relative humidity. Allow to dry 24 to 48 hours before putting in use. Drying times listed may vary depending on temperature, humidity, film build, and air movement. Heavier application may take longer to dry.

CLOGGING: If valve clogs, twist and pull off spray tip and rinse in a solvent, such as mineral spirits. Do not stick a pin or other objects in the stem.

CLEANUP: When finished spraying, hold can upside down and spray until clear gas appears, then wipe off tip before storing. Clean up wet paint with mineral spirits or paint thinner.

DISPOSAL: Contact your local environmental regulatory agency for guidance on disposal of empty can. Do not burn or place in home trash compactor.

U-9305-01

PRECAUTIONS AND FIRST AID: In a fire or if heated, a pressure increase will occur and the container may burst or explode. Can enter lungs and cause damage. Keep away from heat, sparks and flame. Keep away from flames, such as a pilot light, and any object that sparks, such as an electric motor. Do not puncture or incinerate container. Do not expose to heat or store at temperatures above 120°F (49°C). Do not breathe vapor or mist. Do not swallow. Avoid contact with eyes. Keep container tightly closed and sealed until ready for use. Wash thoroughly after handling. Provide fresh air ventilation during and after application and drying. Avoid the inhalation of dust, particulates, spray or mist arising from the application of this preparation. Use personal protective equipment as required. **FIRST AID:** If swallowed, rinse mouth with water (only if the person is conscious). Call physician immediately. Do not induce vomiting unless directed to do so by medical personnel. If in eyes, rinse with water for 15 minutes. Check for and remove any contact lenses. If on skin, rinse well with water. Wash with soap and water. Get medical attention if irritation develops. If inhaled, remove to fresh air. If experiencing respiratory symptoms call a POISON CENTER or doctor/physician. Contains: distillates (petroleum), hydrotreated light (64742-47-8); propane (74-98-6); acetone (67-64-1); butane (106-97-8); (octadecanoato-O) oxoaluminium (13419-15-3); paraffin waxes and hydrocarbon waxes (8002-74-2); toluene (108-88-3). Keep out of the reach of children. For workplace use, an SDS is available from your retailer or by calling (412) 492-5555. EMERGENCY SPILL INFORMATION: (412) 434-4515.

⚠ **WARNING:** Reproductive Harm – www.P65Warnings.ca.gov.

***SATISFACTION GUARANTEED - LIMITED LIFETIME WARRANTY**

Backed by a tradition of quality, PPG Architectural Finishes, Inc. guarantees your complete satisfaction with the performance of this product when applied to a properly prepared surface in accordance with label directions. PPG ARCHITECTURAL FINISHES, INC. MAKES NO OTHER EXPRESS WARRANTIES. FOR AS LONG AS YOU OWN YOUR SINGLE FAMILY HOME, IF THE PRODUCT FAILS TO CONFORM TO THIS LIMITED WARRANTY, PPG ARCHITECTURAL FINISHES, INC. WILL, AT YOUR OPTION, FURNISH REPLACEMENT PRODUCT OR REFUND THE PURCHASE PRICE. THIS LIMITED WARRANTY EXCLUDES (1) LABOR OR COSTS OF LABOR FOR THE APPLICATION OR REMOVAL OF ANY PRODUCT AND (2) ALL OTHER DIRECT, INDIRECT, INCIDENTAL, SPECIAL, OR CONSEQUENTIAL DAMAGES. This Limited Warranty gives you specific legal rights; you may have other rights which vary by state. Some states do not allow the exclusion or limitation of incidental or consequential damages, so the above exclusion or limitation may not apply to you. To make a claim under this Limited Warranty, supply dated proof of purchase to the store of purchase or to PPG Architectural Finishes, Inc., One PPG Place, Pittsburgh, PA 15272.

Visit our website at www.olympic.com

Maximum PWMIR CCP < 0.85

SAP Code: 00421413

1 91894 94427 0

1280144

Manufactured For: PPG Architectural Finishes, Inc.
One PPG Place, Pittsburgh, PA 15272.

© 2018 PPG Industries, Inc. All Rights Reserved. The *PPG Logo* is a registered trademark of PPG Industries Ohio, Inc. *Olympic*, *Olympic & Design* and *WaterGuard* are registered trademarks of PPG Architectural Finishes, Inc. (16418)