



## Cabinet & Trim Enamel Interior Semi-Gloss

NO. 7120 White  
NO. 7123 Deep

- Door Won't Stick After 2 Hours of Dry Time
- Excellent Flow & Leveling
- Dries to a Hard, Durable Finish
- Easy Clean Surface
- Sandable
- Soap & Water Clean-Up
- Mildew-Resistant Finish



**2 Coats Recommended**  
for Optimal Durability



**Spread Rate:**  
Up to 400 sq ft Coverage



**Dry Time:**  
1 Hr. Dry to Touch  
2 Hr. Recoat



**Clean-Up:**  
Soap & Water

**WHITE BASE: READY TO USE OR ADD TINTING COLORANTS.**

**DEEP BASE: DO NOT USE WITHOUT THE ADDITION OF TINTING COLORANTS.**

### WHERE TO USE

Recommended for interior wood, drywall, masonry, vinyl and other properly prepared and primed surfaces. Ideal for kitchen and bathroom cabinets and doors, windows, trim & molding.

### SURFACE PREPARATION<sup>†</sup> (Proper Surface Preparation is Required.)

- All surfaces must be clean, sound, dry and free of any dirt, oil and grease stains.
- Remove mildew stains with a mildew stain removing product.
- Remove all loose and peeling paint; scuff sand glossy surfaces; caulk and repair imperfections. <sup>†</sup>Sand all wood surfaces in the direction of the wood grain to the desired smoothness. Remove all dust from sanded surfaces with a damp, lint free cloth and allow to dry.

### PRIME

- Priming is recommended on all surfaces. On previously painted surface and on new wood, masonry and vinyl surfaces, or on surface with heavy stains, prime with a product such as BEHR® PRIMER COATINGS™ Kitchen, Bath & Trim Primer & Sealer No. 75 prior to topcoating with this product. Follow all label instructions. For best results, sand primer coat prior to topcoating.

### APPLICATION

- Apply when air temperature is between 50-90° F (10-32° C).
- Stir before and during application.
- When working with more than one can of the same product, intermix to ensure color uniformity.
- Do not thin.
- Brush: Apply a thin coat using a high quality synthetic brush. For best results, apply paint with a high quality 100% Nylon brush.
- Roller: Use a high quality 1/4" nap roller cover.
- Airless Sprayer: .009" - .015" spray tip, 60 mesh filter.
- OPTIONAL: In between coats, sand lightly with 320-400 grit sand paper.
- Certain colors may require 2 or more coats to achieve complete hide.
- NOTE: If touch-up is necessary, same application method is recommended.

### DRY TIME

- Darker colors may require additional dry time. Longer dry time required in cooler temperatures and higher humidity.
- Cabinets, doors and windows can be closed as early as 2 hours after final topcoat.
- After 2 weeks, cured paint film may be cleaned with a mild, non-abrasive liquid detergent. Dry paint film is mildew resistant.
- Do not use on floors.

### DISPOSAL

- Properly dispose of all soiled rags.
- For disposal of empty containers and unused product, contact your household refuse collection service.
- To reduce waste, consult with your retailer or an online paint calculator to determine the correct amount of paint to purchase.

### LIMITED WARRANTY

- Visit [www.behr.com/warranty](http://www.behr.com/warranty) or call 1-800-854-0133 Ext. 2 for more information.

**† WARNING** If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC Contact the National Lead Information Center at 1-800-424-LEAD or log on to [www.epa.gov/lead](http://www.epa.gov/lead).

**⚠ WARNING** Cancer and Reproductive Harm – [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

**CAUTION IRRITANT** MAY CAUSE EYE, NOSE AND THROAT IRRITATION. AVOID CONTACT WITH SKIN AND EYES AND AVOID BREATHING OF VAPORS AND SPRAY MIST. WEAR EYE PROTECTION AND PROTECTIVE CLOTHING. USE ONLY WITH ADEQUATE VENTILATION. To avoid breathing vapors and spray mist, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches or dizziness, increase fresh air. If properly used, a respirator (NIOSH approved for organic vapor with P series particulate pre-filter) may offer additional protection; obtain professional advice before using. A dust mask does not provide protection against vapors. Avoid contact with eyes and skin. Wash thoroughly after handling. Close container after each use. **FIRST AID:** If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical assistance immediately. In case of eye contact, flush immediately with plenty of water for at least 20 minutes and get medical attention; for skin, wash thoroughly with soap and water. If swallowed, get medical attention immediately.

**CAUTION: KEEP OUT OF REACH OF CHILDREN – DO NOT TAKE INTERNALLY.**



©2019 Behr Process Corporation  
Santa Ana, CA 92705 U.S.A. • [www.behr.com](http://www.behr.com)  
V.O.C. <50 g/L • REV. 9/19