



SINGLESHOT™ TEXTURE AEROSOL

PRODUCT INFORMATION

ETX® SingleShot™ is an All-in-One aerosol texture spray ideal for drywall patches that require texture. The aerosol spray can system features an adjustable nozzle to provide an assortment of texture patterns from a fine Orange Peel to a heavy Knockdown, allowing for ultimate control over the amount of texture applied. This water-based, low odor formula provides professional-grade results with effortless clean-up for all your projects.

RECOMMENDED USES:

Ideal for use on properly prepared surfaces such as:

- Drywall

PRODUCT SPECIFICATIONS:

301344 SingleShot™ Wall Texture 12 oz

303044 SingleShot™ Wall & Ceiling Texture 20 oz

Resin Type: PVA

Net Weight: 12 oz / 340 g

% Solids by Volume: 37% ± 3%

% Solids by Weight: 50% ± 3%

Max Product-Weighted MIR:

Flat: 0.80

Coverage:

12 oz up to 60 sq ft

20 oz up to 80 sq ft

Coverage varies depending on the amount of texture applied.

SURFACE PREPARATION:

- The surface must be clean and dry before spraying SingleShot™.


WARNING! If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Center at 1-800-424-LEAD or log on to www.epa.gov/lead.

APPLICATION:

- Always keep nozzle pointed away from face. The use of personal protective equipment is required.
- Shake can vigorously for 10–15 seconds. This product works best when contents are between 75°F and 90°F.


- The adjustable nozzle allows for infinite adjustability. (See Diagram Below).
- Holding the can upright approximately 30–34 inches from the wall/ceiling, depress the nozzle to begin spraying. Test SINGLE SHOT in an inconspicuous spot to achieve the desired pattern. If the flow decreases, repeat shaking the can for 10–15 seconds. Spray using a circular motion to disperse evenly. Overlap the spray onto the existing texture to help blend in. A second coat may be applied for a heavier texture.
- Drying times will differ, depending on the surface, heaviness of texture, humidity, etc. Paint when completely dry with your choice of paint. For better results, prime area before painting. Coverage and dry time will vary depending on pattern applied.

OrangePeel



Cáscara de Naranja

KnockDown



Acabado Planchado

OrangePeel



Cáscara de Naranja

KnockDown



Acabado Planchado

CLEAN-UP/DISPOSAL:

- Clear spray valve immediately after use by turning can upside down and spraying until only clear gas is released.
- Do not stick pins or wire into spray nozzle opening.
- Do not burn or place in home trash compactor.
- For recycling or disposal information, contact your household refuse collection service.

CAUTIONS/LIMITATIONS:

- Apply if surface, air and product temperatures are between 75° – 90°F.
- Ensure adequate ventilation when spraying indoors.
- Cover adjacent areas to avoid overspray.

GENERAL INFORMATION:

DANGER! EXTREMELY FLAMMABLE. MAY CAUSE FLASH FIRE. IRRITANT. CONTENTS UNDER PRESSURE. VENTILATION REQUIRED: To avoid inhalation and combustion hazards, DO NOT use this product unless you can achieve cross ventilation by opening windows and doors during application and drying. **CONTAINS DIMETHYL ETHER and CRYSTALLINE SILICA. VAPOR HARMFUL.** May affect the brain or nervous system causing dizziness, headache or nausea. Causes eye, skin and respiratory tract irritation. Avoid contact with skin and eyes. Do not swallow. Do not breathe dusts, vapor or spray, mists. Sanding, grinding or abrading may release sanding dust, which may be harmful if inhaled and has been shown to cause lung damage or cancer with long term exposure. If you experience eye watering, headaches or dizziness, increase fresh air, wear respiratory protection (NIOSH approved) or leave the area. **VAPORS MAY IGNITE EXPLOSIVELY.** Do not spray near sparks, heat or open flame. Do not smoke. Vapors are heavier than air and can travel at floor level to distant ignition sources. Extinguish all flames and pilot lights and turn off stoves, heaters, electric motors, high intensity lights and other sources of ignition during use and until all vapors are gone **CONTENTS UNDER PRESSURE.** Do not puncture or incinerate container. Do not expose to heat or store at elevated temperatures above 120°F. Prolonged exposure to sun may cause bursting.

FIRST AID: If you have difficulty breathing, leave area to obtain fresh air. If difficulty continues, get medical attention immediately. If swallowed, call physician immediately. In case of eye contact, flush immediately with plenty of water for at least 15 minutes and get medical attention. For skin contact, wash thoroughly with soap and water.

KEEP OUT OF REACH OF CHILDREN.