

Date: 0327/18

SAFETY DATA SHEET

SDS PREPARATION DATE: 03/27/2018, Version 1

Section 1 - Identification

GHS product identifier : Brick Transformation - Whitewash
 Chemical name : Mixture
 Synonyms : Coatings
 Product type :
 Material use : Paint and Coatings

Supplier's details : Giani, Inc.
 ADDRESS : 2216 North Broadway
 St. Louis, MO 63102
 Information (314) 241-7771

Emergency telephone number : CHEMTREC 800-424-9300 or 703-527-3887

Section 2 – Hazardous Identification**GHS Classification**

According to Regulation 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)
 No need for classification according to GHS criteria for this product.

Physical hazards Flammable Liquids - Category 4
 Serious Eye Damage - Category 1

Health hazards Not Classified
Environmental hazards Not Classified
Label Elements

**Signal Word**

Danger

Hazard Statements:

H318 Causes serious eye damage.

Precautionary Statements: Disposal

P501 Dispose of contents/container according to applicable local, national, and international regulations.

Precautionary Statements: Prevention

P233 Keep container tightly closed.
 P280 Wear protective gloves/protective clothing/eye protection/face protection.
 P261 Avoid breathing dust/fume/gas/mist/vapors/spray.
 P264 Wash skin thoroughly after handling.

Precautionary Statements: Response

P303+P361+P353 If on skin (or hair): Rinse skin with water/shower.
 P370+P378 In case of fire: use recommended media to extinguish.
 P304+P340 If Inhaled: Remove person to fresh air and keep comfortable for breathing.
 P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
 P312 Call a POISON CONTROL CENTER/doctor if you feel unwell.
 P314 Get medical advice/attention if you feel unwell.
 P302+P352 IF ON SKIN: Wash with plenty of soap and water.
 P321 Specific treatment (see supplemental first aid instruction on this label).
 P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
 P363 Wash contaminated clothing before reuse.

Precautionary Statements: Storage

P403+P235 Store in a well-ventilated place. Keep cool.
 P403+P233 Store in a well-ventilated place. Keep container tightly closed.

Hazards not otherwise classified

No specific dangers known, if the regulations/notes for storage and handling are considered

Section 3 – Composition/information on ingredients

| Component | Concentration | CAS number | GHS Symbols | GHS Statements |
|--|-------------------|---------------------------|-------------|----------------|
| Water | 36.83% - 41.83% | 7732-18-5 | N.A. | N.A |
| Vehicle | 13.68% - 17.68% | non-hazardous proprietary | N.A. | N.A. |
| Ethoxylated 2,4,7,9-tetramethyl 5 decyn-4,7-diol | 00.86% - 01.86% | 9014-85-1 | GHS05 | H318 |
| Polypropylene glycol | 00.22% - 00.72% | 25322-69-4 | N.A. | N.A. |
| Propylene glycol | 02.50% - 03.50% | 57-55-6 | N.A. | N.A. |
| Dipropylene glycol monomethyl ether | 00.78% - 01.78% | 34590-94-8 | N.A. | N.A. |
| Titanium Dioxide | 29.87% - 31.87% | 13463-67-7 | N.A. | N.A. |
| Carbon Black (amorphous) | 00.003% - 00.013% | 1333-86-4 | N.A. | N.A. |
| talc | 02.98% - 04.98% | 14807-96-6 | N.A. | N.A. |
| Calcium Carbonate | 12.08% - 16.08% | 1317-65-3 | N.A. | N.A. |
| Bentonite | 00.34% - 00.84% | 1302-78-9 | N.A. | N.A. |

All concentrations are percent by weight
 The identity of components and / or exact percentage composition may have been withheld as a trade secret.

Section 4 - First Aid Measures**Description of first aid measures****General advice:**

Remove contaminated clothing

If inhaled:

Remove the affected individual into fresh air and keep the person calm. Seek medical attention.

If on skin:

Wash thoroughly with soap and water. If irritation develops, seek medical attention.

If in eyes:

Wash affected eyes for at least 15 minutes under running water with eyelids held open.

If irritation develops, seek medical attention.

If swallowed:

Rinse mouth and then drink plenty of water. Do not induce vomiting. Seek medical attention if necessary.

Most important symptoms and effects, both acute and delayed

Symptoms: The most important known symptoms and effects are described in the labeling (see section 2) and/or in section 11

Indication of any immediate medical attention and special treatment neededNote to physician

Treatment: Treat according to symptoms (decontamination, vital functions), no known specific antidote.

Section 5 - Fire Fighting Measures

Suitable Extinguishing Media CO2, dry powder, dry sand, foam.

Unsuitable Extinguishing Media Water in a jet

Flash Point 75 °C / 167 °F

Autoignition Temperature 207 °C / 405 °F

Explosion Limits Not determined

Upper 14.0 vol%

Lower 1.1 vol%

Sensitivity to Mechanical Impact None expected

Sensitivity to Static Discharge None expected

Specific Hazards Arising from the substance or mixture

Hazards during fire-fighting:

Harmful vapors

Evolution of fumes/fog. The substances/groups of substances mentioned can be released in case of fire.

Protective Equipment and Precautions for Firefighters

Firefighters should be equipped with self-containing breathing apparatus and turn-out gear.

Further information:

Contaminated extinguishing water must be disposed of in accordance with official regulations.

| NFPA | Health 2 | Flammability 1 | Instability 0 | Physical hazards |
|------|-------------|-------------------|------------------|------------------|
|------|-------------|-------------------|------------------|------------------|

Section 6 - Accidental Release Measures

Further accidental release measures:

High risk of slipping due to leakage/spillage of product.

Personal Precautions

Use personal protective clothing.

Environmental Precautions

Do not discharge into drains/surface waters/ground water.

Methods for Containment and Clean up

For small amounts: Pick up with absorbent material (e.g. sand, sawdust, general-purpose binder). Dispose of absorbent material in accordance with regulations.

For large amounts: Pump off product.

Section 7 - Handling and Storage



Handling

Wear personal protective equipment. Do not breathe gas/fumes/vapor/spray. Avoid contact with eyes, skin, and clothing. Do not taste or swallow. Avoid prolonged exposure. Use only with adequate ventilation. Wash thoroughly after handling. DO NOT handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. When using, do not eat, drink or smoke. Avoid release to the environment.

Storage

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well ventilated area, away from incompatible materials (see Section 10) and food and drink. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.
Keep from freezing.

Section 8 - Exposure Controls, Personal Protection

Ingredients Occupational exposure limits:

| Chemical Name | ACGIH TLV-TWA | ACGIH-TLV STEL | OSHA PEL-TWA | OSHA PEL-CEILING |
|--|-------------------------------|----------------|-------------------------------|------------------|
| Bentonite | 3 mg/m3(Respirable particles) | N.E. | 5 mg/m3(Respirable fraction) | N.E. |
| Propylene glycol | N.E. | N.E. | N.E. | N.E. |
| Ethoxylated 2,4,7,9-tetramethyl 5 decyn-4,7-diol | N.E. | N.E. | N.E. | N.E. |
| Polypropylene glycol | N.E. | N.E. | N.E. | N.E. |
| Dipropylene glycol Monomethyl ether | 100 ppm | 150 ppm | 600 mg/m3 | N.E. |
| Talc | 2 mg/m3(Respirable particles) | N.E. | 2 mg/m3(Respirable particles) | N.E. |
| Calcium Carbonate | N.E. | N.E. | 5 mg/m3(Respirable dust) | N.E. |
| Carbon Black (amorphous) | 3 mg/m3 (inhalable dust) | N.E. | 3.5 mg/m3 (inhalable dust) | N.E. |
| Titanium Dioxide | 10 mg/m3 | N.E. | 15 mg/m3 (dust) | N.E. |

Personal Protective Equipment



Respiratory Protection: A NIOSH/MSHA approved air purifying respirator with an organic vapor cartridge or canister may be permissible under certain circumstances where airborne concentrations are expected to exceed

exposure limits. Protection provided by air purifying respirators is limited. Use a positive pressure air supplied respirator if there is any potential for an uncontrolled release, exposure levels are not known, or any other circumstances where air purifying respirators may not provide adequate protection. A respiratory protection program that meets OSHA 1910.134 and ANSI Z88.2 requirements must be followed whenever workplace conditions warrant a respirator's use.



Skin Protection: Chemical resistant protective gloves.



Eye Protection: Wear safety glasses with side shields (or goggles).



Other Protective Equipment: Wear protective clothing as necessary to minimize contact.



Hygienic Practices: Wash hands before eating. Remove contaminated clothing and wash before reuse. Use only in a well ventilated area. Follow all SDS/label precautions even after container is emptied because they may retain product residues. Avoid prolonged or repeated contact with skin. Avoid breathing vapors from heated material. Avoid contact with eyes, skin, and clothing.

Section 9 - Physical and Chemical Properties

| | |
|--|--------------------------|
| Physical State | Liquid |
| Appearance | White |
| Odor | odorless |
| Odor Threshold | No information available |
| pH | 8.0 – 10.50 |
| Melting Point/Range | No information available |
| Boiling Point/Range | 100 °C / 212 °F |
| Flash Point (closed cup Setaflash) | 75 °C / 167 °F |
| Evaporation Rate | Slower than ether |
| Flammability (solid,gas) | N.A. |
| Flammability or explosive limits | |
| Upper | 14.0 vol% |
| Lower | 01.1 vol% |
| Vapor Pressure mmHg @ 21°C | not determined |
| Vapor Density | Heavier than air |
| Relative Density | 1.54 |
| Formula Weight per Volume | 12.82 Pound/Gallon |
| VOC g/l / lb./gallon | 120.51 / 1.005 |
| HAPS | 0.00% |
| Percent Volatile by Weight | 40.19% |
| Percent Volatile by Volume | 59.20% |
| Solubility | soluble in water |
| Partition coefficient; n-octanol/water | No data available |
| Autoignition Temperature | 405 °F / (207 °C) |
| Decomposition Temperature | No information available |
| Viscosity Krebs unit | 115 - 120 ku |

Section 10 - Stability and Reactivity

| | |
|----------------------------------|---|
| Reactive Hazard | No hazardous reactions if stored and handled as prescribed/indicated. |
| Oxidizing properties | Not an oxidizer. |
| Chemical Stability | Stable if stored and handled as prescribed/indicated. |
| Conditions to Avoid | See SDS section 7 – Handling and storage. |
| Incompatible Materials | Strong oxidizing agents, Acids, Bases |
| Hazardous Decomposition Products | Carbon monoxide (CO), Carbon dioxide (CO ₂), Sulfur oxides |
| Thermal decomposition | Stable up to boiling point. |
| Hazardous Reactions | No hazardous reactions when stored and handled according to instructions. |

Section 11 - Toxicological Information

Effect of Overexposure - inhalation: No adverse effects due to inhalation are expected.

Effect of Overexposure - skin contact: causes skin irritation. allergic reactions are possible. prolonged or repeated

contact can result in defatting and drying of the skin which may result in skin irritation and dermatitis (rash).

Effect of Overexposure - eye contact: liquid, aerosols and vapors of this product are irritating and can cause pain, tearing, reddening and swelling accompanied by a stinging sensation and/or a feeling like that of fine dust in the eyes.

Effect of overexposure - ingestion: this material may be harmful or fatal if swallowed. Irritating to mouth, throat and stomach.

Primary route(s) of entry: eye contact, ingestion, inhalation, skin absorption, skin contact

STOT - Single Exposure

Based on single exposure toxicity values, not classified.

STOT - Repeated Exposure

Target Organs:

Based on repeated exposure toxicity values, not classified.

Carcinogenicity: The information below indicates whether each agency has listed any ingredient as a carcinogen if present at levels greater than or equal to 0.1 %.

| CAS-No. | Name | NTP | OSHA | IARC |
|------------|------------------|--------------------|---------------------|----------|
| 13463-67-7 | Titanium Dioxide | Not labeled by NTP | Not labeled by OSHA | Group 2B |

National Toxicological Program (NTP), Occupational Safety & Health Association (OSHA), International Agency for Research on Cancer (IARC) Group 1: Carcinogenic to Humans, Group 2A: Probably Carcinogenic to Humans, Group 2B: Possibly Carcinogenic to Humans, Group 3: Not Classifiable as to its Carcinogenicity to Humans

Acute Toxicity Values

The acute effects of this product have not been tested. Data on individual components are tabulated below:

| CAS-No. | Name | Oral LD50 (mg/kg) | Dermal LD50 (mg/kg) | Vapor LC50 (mg/L) |
|------------|--|-------------------|---------------------|---------------------|
| 57-55-6 | Propylene Glycol | >5000 (rat) | >2000 (rabbit) | 4 h > 20 (rat) |
| 9014-85-1 | Ethoxylated 2,4,7,9-tetramethyl 5 decyn-4,7-diol | 6,300 (rat) | >2,000 (rabbit) | 1 h >20 (rabbit) |
| 34590-94-8 | dipropylene glycol monomethyl ether | >5,000 (rat) | 9510 mg/kg (rabbit) | 7 h 3.35 mg/l (rat) |
| 25322-69-4 | polypropylene glycol | 681 (rat) | N.D. | N.D. |
| 1333-86-4 | Carbon Black (amorphous) | >8000 (rat) | N.D. | N.D. |
| 13463-67-7 | Titanium Dioxide | >5000 (rat) | >5000 (rabbit) | 4 h > 6.8 (rat) |
| 1302-78-9 | Bentonite | >2000 (rat) | N.D. | >=5.27 (rat) |

Section 12 - Ecological Information

Ecotoxicity

Do not flush into surface water or sanitary sewer system.

Ecotoxicity Toxic to aquatic life. Based on acute aquatic toxicity values, not classified.

| | |
|--|--|
| Toxicity to fish (Acute toxicity) | Low acute toxicity to fish |
| Toxicity to daphnia and other aquatic invertebrates (Acute toxicity) | Low acute toxicity to aquatic invertebrates. |
| Toxicity to algae (Acute toxicity) | Low toxicity to algae. |
| Toxicity to fish (Chronic toxicity) | Data not available |
| Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) | Low chronic toxicity to aquatic invertebrates. Data not available |
| Toxicity to bacteria (Acute toxicity) | Low toxicity to sewage microbes. |
| Persistence and Degradability | Expected to be biodegradable |
| Bioaccumulation/ Accumulation | Not expected to bioaccumulate |
| Mobility | No information available |

Section 13 - Disposal Considerations



Waste Disposal Methods

Waste disposal of substance: Dispose of contents/container in accordance with local/regional/national regulations. Chemical waste generators must determine whether a discarded chemical is classified as a hazardous waste under RCRA.

Container disposal: Dispose of in a licensed facility. Recommend crushing, puncturing or other means to prevent unauthorized use of used containers.

Section 14 - Transport Information

Important Note: Shipping descriptions may vary based on mode of transport, quantities, package size, and/or origin and destination. Consult your company's Hazardous Materials/Dangerous Goods expert for information specific to your situation.

DOT – Not Regulated

DOT Proper Shipping Name: Paint Related Material Non Hazardous

DOT Hazard Class: Not Regulated

DOT UN/NA Number: Not Regulated

This material is not regulated as a dangerous good and can be shipped as a NON HAZARDOUS

Section 15 - Regulatory Information

FEDERAL REGULATIONS:

This product is considered non-hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

CERCLA - SARA Hazard Category

This product has been reviewed according to the EPA 'Hazard Categories' promulgated under Sections 311 and 312 of the Superfund Amendment and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the following categories:

None

SARA 302 Extremely Hazardous Material: No

SARA 304 CERCLA Product

| Chemical Name | CAS Number | Pct by Wt. | RQ (lbs) |
|--|------------|------------|----------|
| This product contains no known chemicals regulated under SARA 302/304. | | | |

SARA 311/312 Not Hazardous

Acute Health Hazard

SARA (313) Components in concentrations above the de minimus levels that are listed as toxic chemicals in 40 CFR Part 372 pursuant to the requirements in section 313 of SARA.

| Name | CAS-No. |
|--|---------|
| This product contains no known chemicals regulated under SARA 313. | |

State Regulations

New Jersey right-to-know:

| | |
|--------------------------|------------|
| Propylene Glycol | 57-55-6 |
| Polypropylene glycol | 25322-69-4 |
| Carbon Black (amorphous) | 1333-86-4 |
| Titanium Dioxide | 13463-67-7 |
| Talc | 14807-96-6 |

Pennsylvania right-to-know:

| | |
|-------------------------------------|------------|
| Propylene Glycol | 57-55-6 |
| Polypropylene glycol | 25322-69-4 |
| dipropylene glycol monomethyl ether | 34590-94-8 |
| Carbon Black (amorphous) | 1333-86-4 |
| Titanium Dioxide | 13463-67-7 |
| Talc | 14807-96-6 |

Massachusetts right-to-know:

| | |
|--------------------------|------------|
| Carbon Black (amorphous) | 1333-86-4 |
| Titanium Dioxide | 13463-67-7 |
| Talc | 14807-96-6 |

California Proposition 65 Carcinogens

Warning: This product contains, or may contain trace quantities of a substance known to the state of California to cause Cancer not limited to any that may be listed below:

| Chemical Name | CAS-No. | |
|------------------|------------|---|
| Titanium Dioxide | 13463-67-7 | The listing is for titanium dioxide (airborne, unbound particles of respirable size) and does not cover titanium dioxide when it remains within a product matrix. |

| | |
|--------|------------|
| Quartz | 14808-60-7 |
|--------|------------|

California Proposition 65 Reproductive Toxins

Warning: This product contains, or may contain trace quantities of a substance known to the state of California to cause birth defects, or other reproductive hazards not limited to any that may be listed below:

Quartz 14808-60-7

Toxic Substances Control Act:

This product contains the following chemical substances subject to the reporting requirements of TSCA 12(b) if exported from the United States:

No TSCA 12(b) components exist in this product.

| Country | Regulatory list | Notification |
|-------------|-----------------|--|
| USA | TSCA | This product, or its components, are listed on or are exempt from the Toxic Substance Control Act (TSCA) Chemical Substance Inventory. |
| EU | EINECS | This product, or its components, are not listed on or are exempt from the European Inventory of Existing Chemical Substances (EINECS) or the European List of Notified Chemical Substances (ELINCS). |
| Canada | DSL | This product, or its components, are listed on or are exempt from the Canadian Domestic Substance List (DSL). |
| Australia | AICS | This product, or its components, are listed on or are exempt from the Australian Chemical Substance List (AICS). |
| Japan | ENCS | This product, or its components, are not listed on or are exempt from the Japanese Chemical Substance List (ENCS). |
| South Korea | ECL | This product, or its components, are not listed on or are exempt from the Korean Chemical Substance List (ECL). |
| China | SEPA | This product, or its components, are listed on or are exempt from the Chinese Chemical Substance List (SEPA). |
| Philippines | PICCS | This product, or its components, are not listed on or are exempt from the Philippine Chemical Substance List (PICCS). |

No other Regulatory Information!

Section 16 - Other Information

HMIS® Hazard Ratings: Health - 2, Flammability - 1, Physical Hazard – 0
 HMIS® rating involves data interpretations that may vary from company to company. They are intended only for rapid, general identification of the magnitude of the specific hazard. To deal adequately with the safe handling of this material, all the information contained in this SDS must be considered.

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks.

CONEG Heavy Metal: We confirm that we use packaging and/or packaging components in which the sum of the incidental concentration levels of lead, mercury, cadmium and hexavalent chromium do not exceed 100 parts per million by weight.

Prepared By Environmental, Health and Safety Department
 Email: info@espinc.us

Creation Date 03/27/18
Revision Date
Print Date 03/27/18

Replacing the current legislation under 29 CFR 1910.1200 to align with the Globally Harmonized System of Classification and Labeling of Chemicals (GHS)

Disclaimer

The information provided on this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text.

NON-WARRANTY: Any recommendation of Giani, Inc. contained herein covering use, utilization, chemical or physical properties and other qualities of the products sold is believed reliable; however, Giani, Inc. makes no warranty or representation with respect thereto. Use or application of any Giani, Inc. product is at the discretion of the Buyer without liability or obligation whatsoever of Giani, Inc.