



# VARATHANE® CLASSIC WOOD HARDENER

## DESCRIPTION AND USES

Varathane® Classic Wood Hardener is a professional deep penetrating formula to stop, seal and strengthen wood rot and decay. Dries to a hard solid surface for filling. Recommended for interior and exterior wood surfaces, including wood furniture, doors, decks, cabinets and more.

## PRODUCT FEATURES AND BENEFITS

- Penetrates deep to stop wood rot
- Creates solid surface for filling
- Interior & Exterior use

## PRODUCT

SKU	DESCRIPTION (16 fl. oz.)
340229	Wood Hardener

## PRODUCT APPLICATION

### SURFACE PREPARATION

Completely remove any decayed or soft wood. Remaining wood surface should also be dry and free of grease and loose paint.

**WARNING!** If you scrape, sand or remove old paint from any surface, you may release lead paint dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE; ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to [www.epa.gov/lead](http://www.epa.gov/lead).

### APPLICATION

Shake thoroughly. Saturate affected area using a disposable bristle brush. If desired, multiple coats can be applied for added strength. Allow each coat to harden for 2-4 hours.

### CLEAN UP

Acetone is recommended

## PHYSICAL PROPERTIES

		CLASSIC WOOD HARDENER
Resin		Polyketone
Pigment		NA
Solvents		Acetone
Solids By Volume		18.4%
VOC		0 g/l
Dry Times at 77°F (25°C) and 50% Relative Humidity	Recoat	2-4 hours
	Full Cure	4 hours
Shelf Life		5 years
Flash Point		-4°F
Safety Information		For additional information, see SDS

The technical data and suggestions for use contained herein are correct to the best of our knowledge, and offered in good faith. The statements of this literature do not constitute a warranty, express, or implied, as to the performance of these products. As conditions and use of our materials are beyond our control, we can guarantee these products only to conform to our standards of quality, and our liability, if any, will be limited to replacement of defective materials. All technical information is subject to change without notice.