

DIRECTIONS:

Clean and dry surfaces to be bonded. Shake well before use. Apply glue generously to the surface. Join and clamp for 20-30 minutes. Parts should fit tightly. Excess glue can be removed with clean, wet cloth or scraped off after glue dries. Allow bond to dry for 24 hours. Remove applicator tip to clean out glue build up.

Storage: Close cap after use. Store at room temperature. If glue thickens or separates, shake vigorously until restored to original consistency.

STORE AWAY FROM CHILDREN AND ANIMALS.

Note: Application temperature should be at or above 50°F. Before finishing, sand surfaces to minimize glue exposure. Not recommended for structural or load bearing applications and not for continuous submersion or below-waterline use.

CAUTION: Avoid contact with eyes and skin. Do not breathe vapors. Do not swallow. **KEEP OUT OF REACH OF CHILDREN.** In case of eye contact, flush thoroughly with water. In case of skin contact, flush thoroughly with water. If breathed in, move person into fresh air. If swallowed, do not induce vomiting. Call a doctor immediately. For medical emergencies only, call 800-420-7186.

PRECAUCIÓN: Evitar el contacto con la piel y los ojos. No inhalar los vapores. No ingerir. **MANTENER FUERA DEL ALCANCE DE LOS NIÑOS.** En caso de contacto con los ojos, enjuagar con abundante agua. En caso de contacto con la piel, enjuagar con abundante agua. Si se inhala, llevar a la persona al aire libre. En caso de ingesta, no inducir el vómito. Llamar a un médico de inmediato. Solo en caso de emergencias médicas, llame al 800-420-7186.

VOC: <0.1 g/L

Conforms to ASTM D-4236

©2020 THE GORILLA GLUE COMPANY
CINCINNATI, OH 45241
1-800-966-3458 • www.gorillatough.com