



TECHNICAL DATA SHEET

2400 Boston Street | Suite 200 | Baltimore, MD | 21224

DAP® ULTRA CLEAR All Purpose Waterproof Liquid Rubber Sealant

PRODUCT DESCRIPTION

DAP® ULTRA CLEAR™ ALL PURPOSE WATERPROOF LIQUID RUBBER SEALANT is a premium, all purpose, ultra elastic, ultra clear sealant for sealing a wide variety of surfaces & projects. Clearer than silicone and non-yellowing, it can be used to seal out air, water and moisture for a durable, 100% waterproof and weatherproof seal. Stays flexible & crackproof even in cold weather. Tack free in 10 minutes & cures completely in 7 days. Paintable. Interior/exterior use.



Packaging	5.0 fl. Oz. (147 mL) squeeze tube
Color	Crystal Clear
UPC Number	0 70798 18387 2

KEY FEATURES & BENEFITS

- Adheres to Wet Surfaces
- Stays Crystal Clear/Non-Yellowing
- Clearer than Silicone
- Ultra-Flexible & Crackproof even in Cold Weather
- Immediate Water Ready – Won't Wash Out
- Strong Multi-Surface Adhesion
- Cured Sealant is Mildew Resistant
- Paintable
- Interior/Exterior



TECHNICAL DATA SHEET

2400 Boston Street | Suite 200 | Baltimore, MD | 21224

SUGGESTED USES

USE FOR SEALING: Windows, Doors, Siding, Trim, Gutters, Flashing, Roof Penetrations, Shingles, Eaves, Ducts, Vents, Skylights, Sinks, Showers, Tubs, Countertops

ADHERES TO: Asphalt, Wood, Fiber Cement, Aluminum, Vinyl, Metal, Glass, Fiberglass, Plexiglas®, Lexan®, PVC, Most Plastics, ABS, Formica®, Ceramic, Concrete, Brick, Tile, Stone, Stucco

FOR BEST RESULTS

1. Apply in temperatures above 20°F.
2. Do not use for below waterline applications.
3. Do not use on polystyrene products or plastics.
4. Joint size should not exceed 3/8" wide by 3/8" deep. If joint depth exceeds 3/8", use foam backer rod.
5. Painting is not required. If painting, allow at least 24 hours before painting with a latex paint only. (Longer in cool or humid climate conditions.)
6. Store unused sealant away from extreme heat or cold.

APPLICATION

Surface Preparation

Remove old caulk, dirt, oily residue, frost and loose material or debris from surface.

Product Application

Ensure adequate ventilation when applying indoors and avoid working near excessive heat, sparks, open flame and any ignition source. Wear gloves and eye protection. Wear clothing to prevent skin contact.

1. Remove cap and cut nozzle at 45° angle to desired bead size..
2. Squeeze sealant into joint, gap or crack.
3. Tooling is not required. If tooling is desired, smooth with finishing tool before sealant skins over (approx. 5-10 minutes).
4. Clean up excess uncured sealant with mineral spirits. Do not use mineral spirits to clean skin. Cured sealant must be cut or scraped away.
5. Allow to dry 24 hours (longer in cool/humid climate conditions) before painting with latex paint only.
6. Reseal tube for storage and reuse.

Product Painting

DAP® ULTRA CLEAR can be painted after drying for 24 hours with latex paint only.



TECHNICAL DATA SHEET

2400 Boston Street | Suite 200 | Baltimore, MD | 21224

TYPICAL PHYSICAL & CHEMICAL PROPERTIES

Typical Uncured Physical Properties	5.0 fl oz
Appearance/Consistency	Clear smooth paste
Base Polymer:	Synthetic Rubber
Filler:	N/A
Volatile:	Hydrocarbon, xylene
Weight % Solids	55%
Density (lbs per gallon)	7.5 lbs/gal
Odor	strong solvent
Clean Up	Mineral Spirits
Flash Point	81°F
Freeze Thaw Stability:	will not freeze
Shelf Life	12 months when stored below 80 °F
Coverage	27 linear feet at 3/16" diameter bead
Typical Application Properties	
Application Temperature Range:	40°F to 120°F
Return to Service Time	24 hours
Typical Cured Performance Properties	
Service Temperature Range:	-40°F to 200°F
Maximum Elongation:	400%

CLEAN UP & STORAGE

Before curing, remove excess material from surface and tools with mineral spirits. Do not use mineral spirits to clean skin. After product has cured, excess material must be cut or scraped away. Clean hands with soap and water. Store sealant away from extreme heat or cold.

SAFETY



TECHNICAL DATA SHEET

2400 Boston Street | Suite 200 | Baltimore, MD | 21224

See product label or Safety Data Sheet for health and safety information. You can request a SDS sheet by calling 888-DAP-TIPS or by visiting our website at dap.com.

WARRANTY

LIMITED WARRANTY: If product fails to perform when used as directed, within one year of date of purchase, call 1-888-DAP-TIPS, with your sales receipt and product container available, for replacement product or sales price refund. DAP Products, Inc. will not be responsible for incidental or consequential damages.

COMPANY IDENTIFICATION

Manufacturer: DAP Products Inc., 2400 Boston Street, Baltimore, Maryland 21224

Usage Information: Call 888-DAP-TIPS or visit dap.com & click on “Ask the Expert”

Order Information: 800-327-3339 or orders@dap.com

Fax Number: 410-558-1068

Also, visit the DAP website at dap.com