

INSECO, Inc.
WOOD Rx
Clear Water Repellent
Longest Lasting Wood Sealer & Water Repellent
Product #670
Technical Data Sheet

WOOD Rx Clear Water Repellent is a water based, non-yellowing, water repellent designed to penetrate, seal and protect exterior wood surfaces from water damage. **WOOD Rx Clear Water Repellent** employs silicone technology which produces long lasting water repellency and it also contains an increased level of fungicide which resists mildew growth in the harshest climates.

RECOMMENDED USES:

For use on virtually all exterior wood surfaces such as decks, docks, sidings, specialty hardwoods, pressure treated lumber, garden furniture, playhouses and log/timber frame homes. Do not apply over previously painted or stained wood surfaces without proper preparation. Contact an INSECO representative for detailed specifications.

SURFACE PREPARATION:

1. Apply a solution of 1 part household bleach or bleach alternative, 1 part dishwashing soap and 4 parts water.
2. Scrub and/or pressure wash as necessary to remove any surface contaminants. This is must step on new pressure treated lumber.
3. Apply a test sample of WOOD Rx *ultra* to insure proper adhesion. If beading or crawling occurs, contact INSECO prior to applying.

APPLICATION:

1. Stir thoroughly before use.
2. Apply with a brush, roller, foam pad, pump garden sprayer or airless sprayer
3. Saturate the entire surface but avoid puddling.
4. Apply 1-2 coats as required. Two coats are recommended for maximum performance. Allow 1-2 hours between coats.
6. **WOOD Rx Clear Water Repellent may** be applied to damp or dry wood.

CLEAN UP:

Clean up drips and spills immediately using a damp cloth. Clean tools and equipment with soap and fresh water.

CAUTION:

Do not apply if the threat of rain exists. Keep from freezing. Keep out of reach of children. Do not use if temperature is below 40 degrees F.

TECHNICAL DATA:

Finish: Matte

Vehicle Type: Proprietary

% Solids By Weight: 19% +/- 2%

% Solids By Volume: 17% +/- 2%

Viscosity @ 75 deg. F (24 deg. C): Waterlike

V.O.C. : Less than 50 g/l

Pigment Type: None

Solvent Type: Water

Flash Point, Minimum: Not Flammable

Density: 8.4 lbs. Per gallon

Average Dry Time @ 75 deg. F (24 deg. C): Touch 30 minutes. Recoat 1-2 hours. Foot traffic 12 hours.

Flame Spread: Class A rating on non-combustible substratum

Recommended Dry Film Thickness Per Coat: **WOOD Rx Clear Water Repellent** is designed to penetrate and seal.

Coverage (Theoretical): Coverage will depend on porosity and contour of the surface being coated.

Coverage typically averages 300 square feet per gallon. Two coats are always recommended for maximum performance.

RESISTANCE TO:

Moisture Penetration :Excellent

Peeling/Flaking/Blistering :Excellent

Mildew :Excellent

Technical data contained herein is true and accurate at the date of issue, but is subject to change without notice. An INSECO representative should be contacted with any questions concerning product information or application procedures. Our products conform to INSECO quality standards, but no other warranty is expressed or implied. Liability, if any, is limited to the replacement of product or purchase price.

02/02/09

INSECO, Inc.
5601 Banner Drive
Ft. Myers, FL 33912
800-883-5150