Page 1

Date: 0327/18

SAFETY DATA SHEET

SDS PREPARATION DATE: 03/27/2018, Version 1

Section 1 - Identification

GHS product identifier Brick Transformation - Whitewash

Chemical name Mixture Coatings

Synonyms

Product type

Paint and Coatings Material use

Supplier's details Giani Inc.

ADDRESS 2216 North Broadway St. Louis, MO 63102

Information (314) 241-7771

Emergency telephone number CHEMTREC 800-424-9300 or 703-527-3887

Section 2 - Hazardous Identification

GHS Classification

This product is classified as hazardous according to OSHA Hazard Communication Standard (29 CFR 1910.1200)

Physical hazards

Serious Eye Damage - Category 1

Health hazards Not Classified Not Classified **Environmental hazards** Label Elements



Signal Word Danger

Hazard Statements:

H318 Causes serious eye damage.

Precautionary Statements: Disposal

Dispose of contents/container according to applicable local, national, and international P501

regulations.

Precautionary Statements: Prevention

P233 Keep container tightly closed.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

Avoid breathing dust/fume/gas/mist/vapors/spray. P261

Wash skin thoroughly after handling. P264

Precautionary Statements: Response

P303+P361+P353 If on skin (or hair): Rinse skin with water/shower.

P370+P378 In case of fire: use recommended media to extinguish.

P304+P340 If Inhaled: Remove person to fresh air and keep comfortable for breathing.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention. Call a POISON CONTROL CENTER/doctor if you feel unwell. P312

Get medical advice/attention if you feel unwell. P314

P302+P352 IF ON SKIN: Wash with plenty of soap and water.

P321 Specific treatment (see supplemental first aid instruction on this label).

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

Wash contaminated clothing before reuse. P363

Precautionary Statements: Storage

P403+P235 Store in a well-ventilated place. Keep cool.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

Hazards not otherwise classified

No specific dangers known, if the regulations/notes for storage and handling are considered

Section 3 - Composition/information on ingredients

Component Water	Concentration 42.83% - 47.83%	CAS number 7732-18-5	GHS Symbols N.A.	GHS Statements N.A
Vehicle	13.68% - 17.68%	non-hazardous proprietary	N.A.	N.A.
Ethoxylated 2,4,7,9- tetramethyl 5 decyn-4,7	00.86% - 01.86% '-diol	9014-85-1	GHS05	H318
Polypropylene glycol	00.22% - 00.72%	25322-69-4	N.A.	N.A.
Propylene glycol	02.50% - 03.50%	57-55-6	N.A.	N.A.
Dipropylene glycol monomethyl ether	00.78% - 01.78%	34590-94-8	N.A.	N.A.
Titanium Dioxide	29.87% - 31.87%	13463-67-7	N.A.	N.A.
Carbon Black (amorpho	ous) 00.003% - 00.013%	1333-86-4	N.A.	N.A.
talc	02.98% - 04.98%	14807-96-6	N.A.	N.A.
Calcium Carbonate	12.08% - 16.08%	1317-65-3	N.A.	N.A.
Bentonite	00.34% - 00.84%	1302-78-9	N.A.	N.A.

All concentrations are percent by weight

The identity of components and / or exact percentage composition may have been withheld as a trade secret.

Section 4 - First Aid Measures



Description of first aid measures

General advice:

Remove contaminated clothing

If inhaled:

Remove the affected individual into fresh air and keep the person calm. Seek medical attention.

Wash thoroughly with soap and water. If irritation develops, seek medical attention.

If in eves:

Wash affected eyes for at least 15 minutes under running water with eyelids held open.

If irritation develops, seek medical attention.

If swallowed:

Rinse mouth and then drink plenty of water. Do not induce vomiting. Seek medical attention if necessary.

Most important symptoms and effects, both acute and delayed

Symptoms: The most important known symptoms and affects are described in the labeling (see section 2) and/or in section 11 Indication of any immediate medical attention and special treatment needed

Treatment: Treat according to symptoms (decontamination, vital functions), no known specific antidote.

Section 5 - Fire Fighting Measures

Suitable Extinguishing Media CO2, dry powder, dry sand, foam.

Unsuitable Extinguishing Media Water in a jet Flash Point 75 °C / 167 °F Autoignition Temperature 207 °C / 405 °F **Explosion Limits** Not determined Upper 14.0 vol%

Lower 1.1 vol% Sensitivity to Mechanical Impact None expected Sensitivity to Static Discharge None expected Specific Hazards Arising from the substance or mixture

Hazards during fire-fighting:

Harmful vapors

Evolution of fumes/fog. The substances/groups of substances mentioned can be released in case of fire.

Protective Equipment and Precautions for Firefighters

Firefighters should be equipped with self-containing breathing apparatus and turn-out gear.

Further information:

Contaminated extinguishing water must be disposed of in accordance with official regulations.

NFPA

Health Instability Physical hazards 0 2

Section 6 - Accidental Release Measures

Further accidental release measures:

High risk of slipping due to leakage/spillage of product.

Personal Precautions Use personal protective clothing

Environmental Precautions Do not discharge into drains/surface waters/ground water.

Methods for Containment and Clean up For small amounts: Pick up with absorbent material (e.g. sand, sawdust, general-purpose binder). Dispose of absorbent material in accordance with

regulations

For large amounts: Pump off product.

Section 7 - Handling and Storage





Handling

Wear personal protective equipment. Do not breathe

gas/fumes/vapor/spray. Avoid contact with eyes, skin, and clothing. Do not taste or swallow. Avoid prolonged exposure. Use only with adequate ventilation. Wash thoroughly after handling. DO NOT handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. When using, do not eat, drink or smoke. Avoid release

to the environment.

Store in accordance with local regulations. Store in original container Storage

protected from direct sunlight in a dry, cool and well ventilated area, away from incompatible materials (see Section 10) and food and drink. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

Keep from freezing.

Section 8 - Exposure Controls, Personal Protection

Ingredients Occupational exposure limits:

-				
Chemical Name Bentonite	ACGIH TLV-TWA 3 mg/m3(Respirable particles)	ACGIH-TLV STEL N.E.	OSHA PEL-TWA 5 mg/m3(Respirable fraction)	OSHA PEL-CEILING N.E.
Propylene glycol	N.E.	N.E.	N.E.	N.E.
Ethoxylated 2,4,7,9- tetramethyl 5 decyn-		N.E.	N.E.	N.E.
Polypropylene glyco	I N.E.	N.E.	N.E.	N.E.
Dipropylene glycol Monomethyl ether	100 ppm	150 ppm	600 mg/m3	N.E.
Talc	2 mg/m3(Respirable particles)	N.E.	2 mg/m3(Respirable particles)	N.E.
Calcium Carbonate	N.E.	N.E.	5 mg/m3(Respirable dust)	N.E.
Carbon Black (amorp	phous) 3 mg/m3 (inhalable dust) N.E.	3.5 mg/m3 (inhalable dust)	N.E.
Titanium Dioxide	10 mg/m3	N.E.	15 mg/m3 (dust)	N.E.

Personal Protective Equipment



Respiratory Protection: A NIOSH/MSHA approved air purifying respirator with an organic vapor cartridge or canister may be permissible under certain circumstances where airborne concentrations are expected to exceed exposure limits. Protection provided by air purifying respirators is limited. Use a positive pressure air supplied

respirator if there is any potential for an uncontrolled release, exposure levels are not known, or any other circumstances where air purifying respirators may not provide adequate protection. A respiratory protection program that meets OSHA 1910.134 and ANSI Z88.2 requirements must be followed whenever workplace conditions warrant a respirator's use.



Skin Protection: Chemical resistant protective gloves.



Eye Protection: Wear safety glasses with side shields (or goggles).



Other Protective Equipment: Wear protective clothing as necessary to minimize contact...



Hygienic Practices: Wash hands before eating. Remove contaminated clothing and wash before reuse. Use only in a well ventilated area. Follow all SDS/label precautions even after container is emptied because they may retain product residues. Avoid prolonged or repeated contact with skin. Avoid breathing vapors from heated material. Avoid contact with eyes, skin, and clothing.

Section 9 - Physical and Chemical Properties

Physical State Liquid Appearance White

Odor odorless

Odor Threshold No information available 8.0 - 10.50

рΗ Melting Point/Range No information available Boiling Point/Range 100 °C / 212 °F

Flash Point (closed cup Setaflash) 75 °C / 167 °F **Evaporation Rate** Slower than ether N.A.

Flammability (solid,gas)

Flammability or explosive limits

Upper 14.0 vol% Lower 01.1 vol% Vapor Pressure mmHg @ 21°C not determined Vapor Density Heavier than air

Relative Density 1.54

Formula Weight per Volume 12.82 Pound/Gallon 120.51 / 1.005 VOC g/l / lb./gallon HAPS 0.00% Percent Volatile by Weight 40.19%

Percent Volatile by Volume 59.20% Solubility soluble in water Partition coefficient; n-octanol/water No data available 405 °F / (207 °C) **Autoignition Temperature Decomposition Temperature** No information available

Viscosity Krebs unit 115 - 120 ku

Section 10 - Stability and Reactivity

Reactive Hazard No hazardous reactions if stored and handled as prescribed/indicated

Oxidizing properties Not an oxidizer.

Chemical Stability Stable if stored and handled as prescribed/indicated.

Conditions to Avoid See SDS section 7 - Handling and storage. Incompatible Materials Strong oxidizing agents, Acids, Bases

Hazardous Decomposition Products Carbon monoxide (CO), Carbon dioxide (CO2), Sulfur oxides

Thermal decomposition Stable up to boiling point.

Hazardous Reactions No hazardous reactions when stored and handled according to instructions.

Section 11 - Toxicological Information

Effect of Overexposure - inhalation: No adverse effects due to inhalation are expected.

Effect of Overexposure - skin contact: causes skin irritation. allergic reactions are possible. prolonged or repeated contact can result in defatting and drying of the skin which may result in skin irritation and dermatitis (rash).

Effect of Overexposure - eye contact: liquid, aerosols and vapors of this product are irritating and can cause pain, tearing, reddening and swelling accompanied by a stinging sensation and/or a feeling like that of fine dust in the eyes.

Effect of overexposure - ingestion: this material may be harmful or fatal if swallowed. irritating to mouth, throat and

Primary route(s) of entry: eye contact, ingestion, inhalation, skin absorption, skin contact

STOT - Single Exposure

Based on single exposure toxicity values, not classified.

STOT - Repeated Exposure

Target Organs:

Based on repeated exposure toxicity values, not classified.

Carcinogenicity: The information below indicates whether each agency has listed any ingredient as a carcinogen if present at

levels greater than or equal to 0.1 %. CAS-No. Name

Titanium Dioxide

Not labeled by NTP

OSHA Not labeled by OSHA Group 2B

National Toxicological Program (NTP), Occupational Safety & Health Association (OSHA), International Agency for Research on Cancer (IARC) Group 1: Carcinogenic to Humans, Group 2A: Probably Carcinogenic to Humans, Group 2B: Possibly Carcinogenic to Humans, Group 3: Not Classifiable as to its Carcinogenicity to Humans

13463-67-7

The acute effects of this product have not been tested. Data on individual components are tabulated below:

CAS-No.	Name	Oral LD50 (mg/kg)	Dermal LD50 (mg/kg)	Vapor LC50 (mg/L)
57-55-6	Propylene Glycol	>5000 (rat)	>2000 (rabbit)	4 h > 20 (rat)
9014-85-1	Ethoxylated 2,4,7,9- tetramethyl 5 decyn-4,7-diol	6,300 (rat)	>2,000 (rabbit)	1 h >20 (rabbit)
34590-94-8	dipropylene glycol monomethyl ether	>5,000 (rat)	9510 mg/kg (rabbit)	7 h 3.35 mg/l (rat)
25322-69-4	polypropylene glycol	681 (rat)	N.D.	N.D.
1333-86-4 Carbon Black (amorphous)		>8000 (rat)	N.D.	N.D.
13463-67-7	Titanium Dioxide	>5000 (rat)	>5000 (rabbit)	4 h > 6.8 (rat)
1302-78-9	Bentonite	>2000 (rat)	N.D.	>=5.27 (rat)

Section 12 - Ecological Information

Ecotoxicity Do not flush into surface water or sanitary sewer system.

Ecotoxicity Toxic to aquatic life. Based on acute aquatic toxicity values, not classified.

Toxicity to fish (Acute toxicity) Low acute toxicity to fish

Toxicity to daphnia and other

Low acute toxicity to aquatic invertebrates.

Low chronic toxicity to aquatic invertebrates.

aquatic invertebrates (Acute

toxicity)

Toxicity to algae (Acute toxicity) Low toxicity to algae.

Toxicity to fish (Chronic toxicity) Data not available

Toxicity to daphnia and other

aquatic invertebrates (Chronic

toxicity)

Toxicity to bacteria (Acute

Data not available Low toxicity to sewage microbes.

toxicity)

Persistence and Degradability

Bioaccumulation/ Accumulation Mobility

Expected to be biodegradable Not expected to bioaccumualte No information available

Section 13 - Disposal Considerations



Waste Disposal Methods

Waste disposal of substance: Dispose of contents/container in accordance with local/regional/national regulations. Chemical waste generators must determine whether a discarded chemical is classified as a hazardous waste under RCRA. Container disposal: Dispose of in a licensed facility. Recommend crushing, puncturing or other means to prevent unauthorized use of used containers.

Section 14 - Transport Information

Important Note: Shipping descriptions may vary based on mode of transport, quantities, package size, and/or origin and destination. Consult your company's Hazardous Materials/Dangerous Goods expert for information specific to your situation.

DOT - Not Regulated

DOT Proper Shipping Name: Paint Related Material Non Hazardous

DOT Hazard Class: Not Regulated

DOT UN/NA Number: Not Regulated

This material is not regulated as a dangerous good and can be shipped as a NON HAZARDOUS

Section 15 - Regulatory Information

FEDERAL REGULATIONS:

This product is considered non-hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200

CERCLA - SARA Hazard Category

This product has been reviewed according to the EPA 'Hazard Categories' promulgated under Sections 311 and 312 of the Superfund Amendment and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the following categories:

SARA 302 Extremely Hazardous Material: No

SARA 304 CERCLA Product

Chemical Name CAS Number Pct by Wt. RQ (lbs)

This product contains no known chemicals regulated under SARA 302/304.

SARA 311/312 Not Hazardous

Acute Health Hazard

SARA (313) Components in concentrations above the de minimus levels that are listed as toxic chemicals in 40 CFR Part 372 pursuant to the requirements in section 313 of SARA.

This product contains no known chemicals regulated under SARA 313.

State Regulations

New Jersey right-to-know:

Propylene Glycol	57-55-6
Polypropylene glycol	25322-69-4
Carbon Black (amorphous)	1333-86-4
Titanium Dioxide	13463-67-7
Talc	14807-96-6

Pennsylvania right-to-know

i eilisyivailla rigitt-to-kilow.	
Propylene Glycol	57-55-6
Polypropylene glycol	25322-69-4
dipropylene glycol monomethyl ether	34590-94-8
Carbon Black (amorphous)	1333-86-4
Titanium Dioxide	13463-67-7
Talc	14807-96-6

Massachusetts right-to-know:

Carbon Black (amorphous)	1333-86-4
Titanium Dioxide	13463-67-7
Talc	14807-96-6

California Proposition 65 Carcinogens

Warning: This product contains, or may contain trace quantities of a substance known to the state of California to cause Cancer not limited to any that may be listed below:

Chemical Name CAS-No.

Titanium Dioxide 13463-67-7

The listing is for titanium dioxide (airborne, unbound particles of respirable size) and does not cover titanium dioxide when it remains within a product matrix.

14808-60-7 Quartz

DATE: 03/27/2018 COMPANY NAME: PRODUCT CODE: BRICK TRANSFORMATION - WHITEWASH GIANI, Inc. Page 4

California Proposition 65 Reproductive Toxins

Warning: This product contains, or may contain trace quantities of a substance known to the state of California to cause birth defects, or other reproductive hazards not limited to any that may be listed below:

Toxic Substances Control Act:

This product contains the following chemical substances subject to the reporting requirements of TSCA 12(b) if exported from the United States:

No TSCA 12(b) components exist in this product.

Country	Regulatory list	Notification
USA	TSCA	This product, or its components, are listed on or are exempt from the Toxic Substance Control Act (TSCA) Chemical Substance Inventory.
EU	EINECS	This product, or its components, are not listed on or are exempt from the European Inventory of Existing Chemical Substances (EINECS) or the European List of Notified Chemical Substances (ELINCS).
Canada	DSL	This product, or its components, are listed on or are exempt from the Canadian Domestic Substance List (DSL).
Australia	AICS	This product, or its components, are listed on or are exempt from the Australian Chemical Substance List (AICS).
Japan	ENCS	This product, or its components, are not listed on or are exempt from the Japanese Chemical Substance List (ENCS)
South Korea	ECL	This product, or its components, are not listed on or are exempt from the Korean Chemical Substance List (ECL).
China	SEPA	This product, or its components, are listed on or are exempt from the Chinese Chemical Substance List (SEPA).
Philippines	PICCS	This product, or its components, are not listed on or are exempt from the Philippine Chemical Substance List (PICCS).

No other Regulatory Information!

Section 16 - Other Information

Health - 2, Flammability - 1, Physical Hazard - 0

HMIS® rating involves data interpretations that may vary from company to company. They are intended only for rapid, general identification of the magnitude of the specific hazard. To deal adequately with the safe handling of this material, all the information contained in this SDS must be considered.

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks.

CONEG Heavy Metal: We confirm that we use packaging and/or packaging components in which the sum of the incidental concentration levels of lead, mercury, cadmium and hexavalent chromium do not exceed 100 parts per million by weight.

Environmental, Health and Safety Department Prepared By

Email: info@espinc.us

Creation Date 03/27/18 **Revision Date Print Date** 03/27/18

Replacing the current legislation under 29 CFR 1910.1200 to align with the Globally Harmonized System of Classification and Labeling of Chemicals (GHS)

The information provided on this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified

NON-WARRANTY: Any recommendation of Giani, Inc. contained herein covering use, utilization, chemical or physical properties and other qualities of the products sold is believed reliable; however, Giani, Inc. makes no warranty or representation with respect thereto. Use or application of any Giani, Inc. product is at the discretion of the Buyer without liability or obligation whatsoever of Giani, Inc.