



SOLID COLOR HOUSE & FENCE WOOD STAIN

NO. 11 WHITE BASE



PRODUCT INFORMATION

BEHR® Solid Color House & Fence Wood Stain creates a durable film that resists cracking and peeling on your home's vertical surfaces. It's available in more than 1,600 custom and computer-matched colors.

RECOMMENDED USES:

Ideal for use on properly prepared smooth or rough sawn exterior vertical surfaces such as:

- Wood
- Engineered (Synthetic) Wood
- Pressured Treated Lumber

PRODUCT SPECIFICATIONS:

Tint Bases/Max Tint Load:

- No. 11 Tintable White 124 oz / 4 oz
- No. 30 Deep Base 116 oz / 12 oz

Resin Type: Oil-Latex

Weight per Gallon: 10.7 lb

% Solids by Volume: 38% ± 2%

% Solids by Weight: 51% ± 2%

VOC: <100 g/L

Flash Point: N/A

Viscosity: 70-80 KU

Recommended Film Thickness:

- Wet: 8.0 mils / Dry: 3.0 mils @ 200 sq ft/gal
- Wet: 4.0 mils / Dry: 1.5 mils @ 400 sq ft/gal

Coverage: 200-400 sq ft/gal depending on application method and substrate porosity. Does not include the loss of material from spraying.

APPLICATION:

Brush: Nylon/polyester

Roller: 3/4" nap roller cover

Airless Spray:

Tip: .015"-.019"

Filter: 60 mesh

Fluid Pressure: 1,400 – 2,400 psi

Follow spraying immediately with back brushing or back rolling for a uniform appearance.

Thinning: DO NOT THIN.

Dry Time: @ 77° & 50% RH

To Touch: 2-3 hours

To Recoat: 6-8 hours

Dry times are temperature, humidity, and film thickness dependent.

SURFACE PREPARATION:

The following steps and products are required: If you use a product such as BEHR PREMIUM® Wood Stain & Finish Stripper No. 64 to remove loose wood fibers, latex, oil-based and 100% acrylic coating on new or weathered wood, then you must use BEHR PREMIUM® All-In-One Wood Cleaner No. 63 to clean, brighten & neutralize wood. If you do not use BEHR PREMIUM Wood Stain & Finish Stripper No. 64 as described above, then use a product such as BEHR PREMIUM All-In-One Wood Cleaner No. 63 to clean and brighten the wood surface and to remove light to medium exterior stains caused by mold, mildew, algae & fungus. Rinse thoroughly and allow to dry before coating. On new wood, use a product such as BEHR PREMIUM All-In-One Wood Cleaner No. 63 to remove mill glaze and open the pores of the wood. Lightly sand to remove remaining wood fibers/fuzz.

WARNING! If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Center at 1-800-424-LEAD or log on to www.epa.gov/lead.

SYSTEM RECOMMENDATIONS:

Wood:

- No primer needed on most woods. However, redwood, cedar, cypress and other "bleeding" woods contain water soluble extractives which may cause discoloration of white and pastel colors. Therefore, prime the above type wood.

For Severe Tannin Bleed/Stainblocking:

- BEHR PREMIUM PLUS® Exterior Multi-Surface Primer & Sealer No. 436

PREVIOUSLY PAINTED SURFACES:

- Use a full coat or spot prime with BEHR PREMIUM PLUS Exterior Multi-Surface Primer & Sealer No. 436 on properly prepared surfaces.

COMPLIES WITH THE BELOW AS OF 1/1/2020

| SCAQMD | YES | OTC | YES |
|---------------|-----|-------|-----|
| CARB SCM 2007 | YES | LADCO | YES |
| CARB | YES | AIM | YES |
| OTC Phase II | YES | | |

CLEAN-UP/DISPOSAL:

Clean all tools and equipment with warm, soapy water. Do not dispose of this product down a drain. If spilled, contain material and remove with an inert absorbent. Dispose of contaminated absorbent, container and unused product in accordance with all current federal, state and local regulations. For recycling or disposal of empty containers, unused product and soiled rags, contact your household refuse collection service.

CAUTIONS/LIMITATIONS:

- Protect from freezing.
- For best results, apply when air, material and surface temperatures are between 40°F and 90°F. Avoid applying stain in direct sunlight or to hot surfaces. Temperatures above 90°F can cause the paint to dry too fast. Do not apply if rain is expected within 24 hours of product application.
- Always test product on an inconspicuous area before proceeding with entire project.
- Over-application of BEHR® Solid Color House & Fence Stain results in film forming on the wood surface and therefore subject to peeling and flaking.
- Shelf life under normal conditions is 2 years unopened.

GENERAL INFORMATION:

WARNING IRRITANT HARMFUL IF SWALLOWED. CONTAINS: ETHYLENE GLYCOL. MAY CAUSE EYE, NOSE AND THROAT IRRITATION. AVOID CONTACT WITH SKIN AND EYES AND AVOID BREATHING OF VAPORS AND SPRAY MIST. WEAR EYE PROTECTION AND PROTECTIVE CLOTHING. USE ONLY WITH ADEQUATE VENTILATION. To avoid breathing vapors and spray mist, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches or dizziness, increase fresh air. If properly used, a respirator (NIOSH approved for organic vapor with P series particulate pre-filter) may offer additional protection; obtain professional advice before using. A dust mask does not provide protection against vapors. Avoid contact with eyes and skin. Wash thoroughly after handling. Close container after each use.





SOLID COLOR HOUSE & FENCE WOOD STAIN

NO. 11 WHITE BASE

FIRST AID: If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical assistance immediately. In case of eye contact, flush immediately with plenty of water for at least 15-20 minutes and get medical attention; for skin, wash thoroughly with soap and water. If swallowed, get medical attention immediately.

CAUTION: KEEP OUT OF REACH OF CHILDREN – DO NOT TAKE INTERNALLY.

