

UNPOLISHED NATURAL STONE AND TERRACOTTA



- PROTECTS SURFACES AGAINST STAINS AND DIRT.
- HIGHLY RESISTANT TO UV RAYS AND HEAVY TRAFFIC.



Coverage:

1 QT (0.95 L)

Unpolished natural stone, terracotta

> 100-200 sq.ft. (9-19 m²)

Coverage rates are indicative and per coat.



Packaging:

1 QT (946 ml) 5 plastic bottles per box

WHAT IT'S FOR

- Seals indoor and outdoor unpolished natural stone, terracotta.
- Gives the surface a wet-look, gloss finish.
- Protects from dirt and stains.
- Intensifies the color of unpolished natural stone.
- Ideal for use in kitchens, under barbeques, on driveways and in high traffic areas both indoors and outdoors.

ADVANTAGES

- Eco-friendly: water-based.
- Weather resistant.
- Is not affected by residual humidity: can be applied 24-48 hours after initial cleaning.
- Very low VOC emissions: contributes towards LEED credits

HOW TO USE IT

Ready to use, no dilution necessary.

Instructions: Shake well before using. On a clean, dry surface apply FILAWET ECO with a flat brush, lambswool applicator or roller. Carefully rub the product onto the material surface and into the grout joints. Wait 2-3 hours, then apply a second coat. The surface can be walked on after 12 hours.

Caution: When using the product on surfaces with high porosity (Slate, Carrara marble, Botticino marble), dilute 1:1. Do not use on polished surfaces.

Storage temperature: between 41°F and 86°F (5°C and 30°C). Must be applied at temperatures between 50°F and 86°F (10°C and 30°C).

Fila Chemicals USA, Corp. Miami, FL 33172 tel +1-305-513-0708 filausa@filasolutions.com



