

GRAY

GRAY

GRAY

GRAY

GRAY



PATIOS

DRIVEWAYS

SIDEWALKS

FOUNDATIONS

ADVERTENCIA: CONTIENE DESTILADOS DE PETROLEO. Puede causar irritaciones en los ojos, la piel, la nariz, la garganta y tracto respiratorio. Utilice en un área con buena ventilación. Garantizar la entrada de aire fresco. Proporcionar aire fresco suficiente para que los olores químicos no sean detectados durante su uso y mientras seca. Puede dañino si se absorbido por la piel. Evite el contacto con los ojos, la piel y la ropa. No lo ingiere. Use guantes y utilice protección para los ojos con protectores laterales. Lávese bien después de manipular el producto. Mantenga el envase cerrado cuando no esté en uso. **PRIMEROS AUXILIOS:** INHALACIÓN: Trasládese al aire fresco. PIEL: Lávese con agua y jabón. OJOS: Enjuague inmediatamente con abundante cantidad de agua. INGESTION: Busque atención médica de inmediato. NO INDUZCA EL VOMITO. **En caso de emergencia,** llame al centro de control de veneno al 1-800-222-1222. Consulte a la Hoja de Datos de Seguridad (SDS) para obtener información adicional. Para obtener una SDS, comuníquese con su proveedor o visite dap.com. **MANTENGA FUERA DEL ALCANCE DE LOS NIÑOS.** **⚠️ ADVERTENCIA Cáncer y Daños al Sistema Reproductivo –** www.P65warnings.ca.gov

WARRANTY: If product fails to perform when used as directed within one year of date of purchase, call 1-888-DAP-TIPS, with your sales receipt and product container available, for product replacement or sales price refund. DAP is not liable for incidental or consequential damages.

QUESTIONS/¿PREGUNTAS? Call/Llame al 1-888-DAP-TIPS or visit/o visite dap.com and click on/y pulse en "Ask the Expert."

Para obtener las instrucciones y garantía en español, llame al 1-888-DAP-TIPS o visite dap.com.

DAP Products Inc.,
Baltimore, MD 21224

Made in the USA
with U.S. and globally
sourced materials.

dap.com

CONCRETE

CONCRETE SILICONIZED FILLER & SEALANT



- FILL & SEAL CRACKS & HOLES IN CONCRETE
- PAINTABLE
- EXCELLENT FLEXIBILITY & ADHESION
- EASY WATER CLEAN-UP & LOW ODOR
- INTERIOR/EXTERIOR

Read back panel carefully for other cautions.

Lea atentamente el panel posterior para otras precauciones.

10.1 fl oz (300 mL)

DAP® CONCRETE Filler & Sealant is a durable sealant specifically formulated to repair cracks & holes in concrete, mortar & masonry surfaces. It is easy to apply, paintable & low in odor. Adheres to concrete, mortar, cinderblock, stucco, brick, wood, stone.

FOR BEST RESULTS: Apply in temps. above 40°F. Do not apply when rain or freezing temps. are forecasted before full cure can occur. Not for continuous underwater use. Joint size should not exceed 1/2" wide by 1/2" deep. If joint depth exceeds 1/2", use foam backer rod. Allow to cure 24 hours before direct exposure to water. Serviceable for pedestrian & vehicular traffic after 24 hours (minimum). Sealant fully cures in 7-14 days, depending on temp., humidity & depth of fill. Store away from extreme heat or cold.

INSTRUCTIONS: 1. Remove loose or damaged concrete from surface. 2. Apply sealant to a clean, dry surface. 3. Cut nozzle at a 45° angle to desired bead size. 4. Load into caulking gun. 5. Fill crack or gap with sealant. 6. Smooth bead of sealant if necessary. 7. Clean up excess uncured sealant with damp sponge before it skins over. Cured sealant must be cut or scraped away. 8. Paintable after 2 hours (longer in cool/humid conditions) w/latex or oil-based paints. 9. Reuse cartridge for storage & reuse. **COVERAGE:** 55 linear feet at 3/16" diameter bead.

WARNING: CONTAINS PETROLEUM, DISTILLATES. May cause eye, skin, nose, throat & respiratory tract irritation. Use in a well-ventilated area. Ensure fresh entry. Provide fresh air such that chemical odors cannot be detected during use & while drying. May be harmful if absorbed through skin. Avoid contact w/eyes, skin & clothing. Do not ingest. Wear gloves & eye protection w/side shields. Wash thoroughly after handling. Keep container closed when not in use. **FIRST AID:** INHALATION: Remove to fresh air. SKIN: Wash w/soap & water. EYE: Flood w/large quantities of water. INGESTION: Get medical attention immediately. **DO NOT INDUCE VOMITING.** In case of emergency, call you poison control center at 1-800-222-1222. See Safety Data Sheet (SDS) for additional information. For an SDS, contact your supplier or visit dap.com. **KEEP OUT OF REACH OF CHILDREN.**

⚠️ WARNING Cancer & Reproductive Harm – www.P65warnings.ca.gov

Calif. ARB VOC <1.5 wt/wt%
(VOC 37 g/L)

