

# INTELLIGENT BATTERY CHARGERS

## MAINTAIN BATTERY CHARGE, EXTEND BATTERY LIFE!

Keep your car or boat battery charged and maintained during periods of unuse. Our Intelligent Charging System detects change in temperature and voltage, tailoring your battery's maintenance with up to 9 separate charging stages.

### 1.5A INTELLIGENT BATTERY CHARGER

WET AGM GEL  
3 STAGE CHARGING



Item No. 7402

### 4A INTELLIGENT BATTERY CHARGER

WET AGM GEL  
LiFePO<sub>4</sub>  
9 STAGE CHARGING



Item No. 7403

### 8A INTELLIGENT BATTERY CHARGER

WET AGM GEL  
LiFePO<sub>4</sub>  
6 STAGE CHARGING



Item No. 7406

### 15A INTELLIGENT BATTERY CHARGER

WET AGM GEL  
LiFePO<sub>4</sub>  
6 STAGE CHARGING



Item No. 7407



	1.5A INTELLIGENT BATTERY CHARGER	4A INTELLIGENT BATTERY CHARGER	8A INTELLIGENT BATTERY CHARGER	15A INTELLIGENT BATTERY CHARGER
Item No.	7402	7403	7406	7407
Charging Rates	12V, 1.5A	12V, 1A or 4A 6V, 4A	12V, 2A or 8A 6V, 2A	12V, (2A, 8A or 15A)
Input Voltage	110-240V AC	110-140V AC	110-140V AC	110-140V AC
Battery types	Lead Acid (wet, AGM, Gel)	Lead Acid (wet, AGM, Gel) Lithium (LiFePO4)	Lead Acid (wet, AGM, Gel) Lithium (LiFePO4)	Lead Acid (wet, AGM, Gel) Lithium (LiFePO4)
# of Charging Stages	3	9	6	6
Charging Stages	Bulk, Absorption, Maintenance	Diagnostic, Recovery, Soft Start, Pulse, Recondition, Bulk, Absorption, Check, Maintenance	Soft Start, Bulk, Absorption, Check, Reconditioning, Maintenance	Soft Start, Bulk, Absorption, Check, Reconditioning, Maintenance
Safety Features	Short Circuit, Reverse Connection	Short Circuit, Reverse Connection	Short Circuit, Reverse Connection, Over Charge, Over Heat	Short Circuit, Reverse Connection, Over Charge, Over Heat
Connectors	Battery clamps, ring connectors	Battery clamps, ring connectors	Battery clamps	Battery clamps
Cable length	AC Cord: 6 ft DC Clamps: 6 ft	AC Cord: 6 ft DC Clamps: 6 ft	AC Cord: 6 ft DC Clamps: 6 ft	AC Cord: 6 ft DC Clamps: 6 ft
Dimensions (HWD)	5.3 x 2.6 x 1.5 in	7.3 x 3.3 x 1.7 in	8.0 x 4.0 x 7.0 in	9.0 x 5.0 x 8.0 in
Weight	0.9 lbs	1.2 lbs	2.2 lbs	3.2 lbs