



Thermoquiet is easy to install. The integrated lip and tape make for quick vapor-tight lap joint, and can be glued on one side, two sides for commercial applications or floated.

Amvic Thermoquiet meets code requirements for both residential and high rise applications. The cushion layer improves sound and thermal insulation properties while reducing standing fatigue, while the reinforced reflective FOIL middle layer reflects heat back into the room in winter. Thermoquiet is both mold and mildew resistant and contains no V.O.C.S

Cushion layer with fire retardant additive; for high rise and commercial applications

Integrated reflective radiant / vapor barrier

Wear and acoustic layer. (faces floor)
Can be laid directly on concrete or wooden subfloors.

Additional HD Poly layer with integral self-adhesive tape lip (speeds large installs)

Specifications are printed directly onto the product.

IDEAL FOR USE UNDER:
LAMINATE, ENGINEERED OR HARDWOOD, CARPET OR CERAMIC TILE FLOOR

5 in 1 Underlay Solution

- 1** Certified vapor barrier
- 2** Certified thermal barrier
- 3** Certified acoustic barrier
STC 68 / Δ IIC 20
- 4** Dual density foam for superior cushioning and wear resistance
- 5** Certified fire retardant
(ASTM E84 / GB 8410 – 2006)

Roll Specs:

9/64in x 48in x 25ft - (100 Sq ft)

3.5mm x 1.22m x 7.62m - (9.3 m²)

Caution:

This product should NOT be used ABOVE radiant floor heating.

THERMOQUIET® HIGH PERFORMANCE UNDERLAY



IMPROVE YOUR LIVING ENVIRONMENT
REDUCE YOUR HEATING COST

