



DensShield® Tile Backer helps protect your walls and subfloor from moisture intrusion in any area where humidity is present. Its specialized acrylic coating provides a built-in water barrier that stops moisture at the surface.

- Does not require purchase of a separate moisture barrier
- Lightweight, easy-to-handle material
- Fastens with any galvanized roofing nail or corrosion resistant screw
- Easily cuts, like drywall, with a utility knife

IDEAL FOR

Pro Customers

- Tile & Flooring Contractors
- Commercial Contractors

Homeowners

- Do-It-Yourselfers
- Do-It-For-Me

Questions?

Contact gpgypsumretail@gapac.com



Where to find DensShield® Tile Backer

DensShield® can be found in the Drywall aisle of the Building Products section of select stores, through Quote Center and select FDCs.

• DensShield® 1/2 x 4' x 8' Tile Backer

Store SKU 358349
OMSID 100560885
Model # 855000

• DensShield® 1/2 x 32" x 5' Tile Backer

Store SKU 358348
OMSID 100322694
Model # 008590

• DensShield® 5/8 x 4' x 8' Tile Backer

Store SKU 1004639311
OMSID 309783715
Model # 8551

DensShield® vs. Cement Board



**DensShield®
Tile Backer**



**Cement
Board**

Weight	Lighter than competing fiber cement and cement products	Leading cement board weighs ~20% more ¹ than DensShield® Tile Backer ²
Ease of Cutting	Easy to cut	Hard, requires special tools
Moisture Barrier	Built in	Separate
Special Fasteners	No Use any galvanized roofing nail or corrosion resistant screw	Yes Requires cement board screws

¹ Based on 1/2" comparison

² Source: USG Durock® 1/2" x 4' x 8'