

HyperBC-2C-X05 - 82100060X
HyperBC-2F-X05 - 82200060X



2FT DOUBLE ENDED LED TUBE

HYPERIKON®

SPECIFICATIONS

Model Name	Hyperikon Code	Wattage	Lumens	Efficacy	Kelvin
HyperBC-2C-405	821000603	8W	1150 Lm	115 Lm/W	4000K
HyperBC-2C-505	821000604	8W	1150 Lm	115 Lm/W	5000K
HyperBC-2F-405	822000603	8W	1000 Lm	100 Lm/W	4000K
HyperBC-2F-505	822000604	8W	1000 Lm	100 Lm/W	5000K

All Hyperikon® LED T8 are UL Listed [E359780]. For proper installation, the tombstones need to be rewired, and the ballast bypassed for all variations except for the 2ft tubes.

MODEL DESIGN



Voltage
120-277V



Base
G13



Beam Angle
120°-140°



CRI
84+



Dimmer Not
Recommended



Temperature
-22 °F to 130 °F

- Suitable for damp locations outside as well as inside.
- 45,000+ hours of lifespan, more than 41.1 years based on 3Hrs/day average

82100060X
Clear, 120°

2 ft (610 mm)



82200060X
Frosted, 140°



WARNINGS AND CAUTIONS

- Turn power off before inspection, installation or removal. Risk of electric shock - do not use where directly exposed to water or weather.
- This device is not intended for use with emergency exit fixtures or emergency exit lights.

HYPERIKON®

(888) 846-4973
info@hyperikon.com
707 Broadway Suite 800
San Diego, CA 92101
www.hyperikon.com

