

## D1200-2 Series Aluminum Multi Section Extension Ladders




The D1200-2 series aluminum extension ladders have a duty rating of 225 lbs and interlocking side rails. The TRACTION-TRED® D rungs are slip resistant. Spring-loaded locks operate smoothly for easy operation. Shoes rest flat or are held in spur position with SHU-LOK® feature. Mar-resistant end caps help protect the surface ladder is leaning against. Exclusive ALFLO® rung joint means TWIST-PROOF® performance every time.

### Features

- Alflo rung joint for Twist-Proof performance
- Interlocking side rails
- Mar-resistant molded end caps
- Modified I-beam rails
- Rope and pulley system
- Rope clamp ties rope to rung
- Slip-resistant shoe with Shu-lok feature and spur plate
- Slip-resistant Traction-Tred D-rungs
- Spring loaded locks

### Specifications

Model No.	Size	Reach Height	Max Working Length	Max. Open Extended Length	Approx. Closed Length	Approx. Shipping Weight Lbs.
D1216-2 	16 ft	15 ft	13 ft	13 ft	8 ft	22
D1220-2	20 ft	19 ft	17 ft	17 ft	10 ft	27
D1224-2	24 ft	23 ft	21 ft	21 ft	12 ft	33.5
D1228-2	28 ft	27 ft	25 ft	25 ft	14 ft	43
D1232-2	32 ft	31 ft	29 ft	29 ft	16 ft	54
D1236-2	36 ft	34 ft	32 ft	32 ft	18 ft	62.5
D1240-2	40 ft	37 ft	35 ft	35 ft	20 ft	73.5