



Technical Bulletin

2400 Boston Street, Suite 200, Baltimore, Maryland 21224
Phone: 410-675-2100 or 800-543-3840

Revised: 7/27/05

DAP® PATCH STICK® Spackling Stick

- Dries in minutes
- Will not crack or shrink
- Comes with finishing tool

Company Identification:

Manufacturer: DAP Inc., 2400 Boston St., Baltimore, Maryland 21224
Usage Information: DAP HELPLINE: 888-DAP-TIPS, 9:00 am to 7:00 pm EST.
Order Information: 800-327-3339
Fax Number: 410-534-2650
Also, visit the DAP website at www.dap.com.

Packaging: 2.8 oz, 1oz
Color: White
UPC Number: 12316, 12320, 12324, 97010

Product Description:

DAP® PATCH STICK® Spackling Stick offers a quick and easy method of patching interior surfaces. Fill nail holes, minor dents or cracks in walls, ceilings or woodwork prior to painting or wallpapering. It dries in minutes, does not require sanding and won't crack or shrink.

Suggested Uses:

- Ideal for filling nail holes and small dents.
- Excellent for ceiling applications.

Surface Preparation & Application:

- Surface must be clean, dry and free of loose paint, plaster, wax, dust and dirt.
- Remove top, grip tube bottom, and "twist-up" small amount (about 1/16") of spackling patch.
- Either apply directly to surface, or using spackling knife provided in the top, scrape off spackling patch from top of tube and apply to wall.
- Dries in minutes, won't crack or shrink.
- Paint immediately with latex paint. To sand or paint with oil-base paint, allow to dry thoroughly. PATCH STICK® typically dries in approximately 3 hours depending on relative humidity and depth of fill.

Physical & Chemical Characteristics:

Consistency: Thick Paste
Vehicle: Latex Polymer
Volatile: Water
Filler: Glass bubbles
Odor: Pleasant
Weight/gallon: 4.0 ± 0.2 lbs.
Solids: 53 ± 1%

Shelf Life: 9 Months Minimum
Freezing: Freeze/Thaw 3 Cycles @ 0°F.
Temperature
Service Range: 0° to 160°F.

MSDS No.: 000 10410 002

Clean Up:

Clean up immediately after use with soap and water. Be sure container is sealed tightly. Store in a cool dry place. Dry material must be cut, scraped or sanded away.

Safety:

See product label and Material Safety Data Sheet (MSDS) for safety information. You can request an MSDS by visiting our website at www.dap.com or by calling 888-DAP-TIPS.

Warranty Information:

If you are not satisfied with this product's performance when used as directed, return used container and sales receipt to DAP Inc., Technical Customer Service, 2400 Boston Street, Suite 200, Baltimore, MD 21224 for product replacement or sales price refund. DAP will not be liable for incidental or consequential damages.