


### Features

- Single control actuation.
- Part of the Kelston® collection.
- Includes the K-72776 Artifacts handshower and 60" hose.

### Required Accessories

K-97339 Multiproduct Mounting-block



### Codes/Standards




ASME A112.18.1/CSA B125.1  
DOE - Energy Policy Act 1992  
EPA WaterSense®


### KOHLER® Faucet Lifetime Limited Warranty

See website for detailed warranty information.

### Available Color/Finishes

*Color tiles intended for reference only.*

Color	Code	Description
	CP	Polished Chrome
	BN	Vibrant® Brushed Nickel
	2BZ	Oil-Rubbed Bronze



### Technical Information

All product dimensions are nominal.

Valve body: Composite  
Spout reach: 8-13/16" (224 mm)

### Faucet:

Flow rate: 6 gal/min (22.7 l/min)  
Pressure: 45 psi (3.1 bar)

### Handshower:

Rated maximum flow: 2 gal/min (7.6 l/min)

### Notes

Install this product according to the installation guide.

Adequate floor support is required. The wood support must be a minimum of 2" (51 mm) thick by 6" (152 mm) wide. 2x6 lumber is NOT adequate for this application.

Concrete can be used as the floor support.

Requires 3/16" masonry drill bit and six 1/4" x 1-3/4" concrete screws, not included.