

D6200-2 Series Fiberglass Multi Section Extension Ladders



The D6200-2 fiberglass extension ladders have non-conductive rails making these ladders ideal for working near electricity. With a duty rating of 300 lbs, the D6200-2 series is durable and long lasting. The exclusive ALFLO® rung joint means TWIST-PROOF® performance on the job. The TRACTION-TRED® D rungs are slip resistant and the side rails are interlocking. The dual action feet are for use on hard or penetrable surfaces and swivel easily. The base and fly sections separate easily to use the base section as a single ladder. The durable rail shield bracket and shoe help protect the bottom of the rail. The fly section rails are pre-pierced at the top for easy field installation of accessories.

Features

- Alflo rung joint for Twist-Proof performance
- Base section may be used as a single ladder
- Direct rung to rail connections
- Electrically non-conductive side rails
- Guides at top of base section
- Guides on bottom of fly section
- Interlocking side rails
- Mar-resistant molded end caps
- Rail shield and shoe bracket protects rail
- Rope and pulley system
- Rope clamp ties rope to rung
- Rugged gravity spring locks
- Shoe with slip-resistant pad and spur plate
- Slip-resistant Traction-Tred D-rungs
- Spring loaded locks

Specifications

Model No.	Size	Reach Height	Max Working Length	Max. Open Extended Length	Approx. Closed Length	Approx. Shipping Weight Lbs.
D6216-2 	16 ft	15 ft	13 ft	13 ft	8 ft	36.5
D6220-2	20 ft	19 ft	17 ft	17 ft	10 ft	44.5
D6224-2	24 ft	23 ft	21 ft	21 ft		52
D6228-2	28 ft	27 ft	25 ft	25 ft		59.5
D6232-2	32 ft	31 ft	29 ft	29 ft		71.5
D6236-2	36 ft	34 ft	32 ft	32 ft	18 ft	80.5
D6240-2	40 ft	37 ft	35 ft	35 ft		88.5