

HOW TO ASSEMBLE THE DOUBLE BAGGER ON AN XT™ LAWN TRACTOR

- 1** START BY LAYING OUT THE PARTS. ALWAYS READ YOUR OWNER'S MANUAL.



- 2** ASSEMBLE MOUNTING BRACKETS
- a. Attach the two side brackets to the rear attachment, use two carriage bolts and the wing knobs to secure them



- b. Flip over the assembly and mount the hitch support bracket, use the holes furthest away from the rear hooks and use two carriage bolts and the wing knobs to secure them



- 3** MOUNT ASSEMBLY ON TRACTOR
- a. Place hooked ends of the mounting assembly over the shoulder bolts, use the clevis bolt and hairpin clip to secure bracket to tractor



- 4** INSTALL HANGER ASSEMBLY
- a. Use hanger position C, secure using the carriage bolt and wing knob
- b. Place hanger assembly onto the upright support bracket, secure using two carriage bolts and two 1/2" lock nuts and washers



(CONTINUED ON NEXT PAGE)

5 ASSEMBLE REMAINING BAGGER

- a. Snap the upper chute support into place



- b. Slide the left side into the upper chute support using the tabs



- c. Align the cover tabs with the chute support, slide hinge pin in place



- d. Add the bags

6 INSTALLING THE CHUTE

- a. Install the boot rod mount using the 7/16" nuts (2 wrenches are used)

- b. Slide the boot rod into the deck, secure the boot with a wing knob



- c. Slide the chute into the opening, turn counterclockwise until secure

