

connect to auxiliary faucet

Use and Care



Brita® Reverse Osmosis Filtration System USS-335

Usage and quality of water in your incoming water line affect the life of filter cartridges. Cartridges should be replaced sooner if water pressure at the faucet begins to drop noticeably or if the filter fails to perform satisfactorily.

After prolonged periods of non-use, it is recommended that the filter system be flushed thoroughly. Let water run for 10 minutes before using.

The Red-Twist™ filters used with this filter system has a limited service life. Changes in taste, odor, and/or flow of the water being filtered indicate that the filters should be replaced.

Please see the Performance Data Sheet for the certified performance of specific systems with stated cartridges.

System	Filter Model Numbers
USS-335 Reverse Osmosis Filtration System	
Replace filters every six months or sooner.	Stages 1 & 2: USF-201 - Carbon Filter
Replace membrane every 12 months or sooner.	Stage 3: USF-205 RO Membrane Filter

Replacement Parts Part Number	Description
WFBAS-300	Mounting Screws (Package of 2)
WFBAS-200	Eyedropper
WFBAS-400	Nitrate Test Strip
WFBAF-400	Kitchen Faucet Adapter
WFBAF-500	RO Air-Gap Faucet (no tubing attached)
WFBAF-300	1/4" Plastic Tubing (6 Feet - white)
WFBAF-350	1/4" Plastic Tubing (5 Feet - red)
WFBAF-375	3/8" Plastic Tubing (2.5 Feet - white)
WFBAF-425	Drain Connector Assembly
WFBAH-360	Red-Twist™ 3 Stage RO Head Assembly (no shroud)
WFBAH-170	RO Auto Shut-Off Diaphragm and Piston Parts
WFBAR-100	RO Flow Restrictor
WFBAT-300	RO Water Storage Tank
WFBAT-100	RO Storage Tank Fitting
FCT-102	Filtered Water Faucet - Chrome Color (1/4" connection)