Safety Data Sheet according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations Date of issue: 09/10/2014

SECTION 1: IDENTIFICATION

Product Identifier Product Form: Mixture

Product Name: RUST EATER & CONVERTER

Product Code: 923XX

Intended Use of the Product

Rust remover.

Name, Address, and Telephone of the Responsible Party

Company

Star brite Inc.

4041 SW 47th Avenue Fort Lauderdale, FL 33314

(954)587-6280

www.starbrite.com

Emergency Telephone Number

Emergency number : US: (800) 424-9300; International: (703) 527-3887 (CHEMTREC)

SECTION 2: HAZARDS IDENTIFICATION

Classification of the Substance or Mixture

Classification (GHS-US)

Met. Corr. 1 H290 Skin Corr. 1B H314 Eve Dam. 1 H318 Skin Sens. 1 H317

Label Elements

GHS-US Labeling

Hazard Pictograms (GHS-US)





Signal Word (GHS-US) : Danger

Hazard Statements (GHS-US) : H290 - May be corrosive to metals

> H314 - Causes severe skin burns and eye damage H317 - May cause an allergic skin reaction

H318 - Causes serious eye damage

Precautionary Statements (GHS-US) : P234 - Keep only in original container.

P260 - Do not breathe mist, spray, vapors.

P264 - Wash hands, forearms, and exposed areas thoroughly after handling. P272 - Contaminated work clothing should not be allowed out of the workplace. P280 - Wear eye protection, face protection, protective clothing, protective gloves.

P301+P330+P331 - IF SWALLOWED: rinse mouth. Do NOT induce vomiting.

P302+P352 - IF ON SKIN: Wash with plenty of soap and water.

P303+P361+P353 - IF ON SKIN (or hair): Remove/Take off immediately all contaminated

clothing. Rinse skin with water/shower.

P304+P340 - IF INHALED: Remove person to fresh air and keep at rest in a position

comfortable for breathing.

P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing. P310 - Immediately call a POISON CENTER or doctor/physician.

P321 - Specific treatment (see Section 4).

EN (English US) 09/10/2014 RTATAA-CC 1/11

Version: 1.0

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

P333+P313 - If skin irritation or rash occurs: Get medical advice/attention.

P362+P364 - Take off contaminated clothing and wash it before reuse.

P363 - Wash contaminated clothing before reuse.

P390 - Absorb spillage to prevent material damage.

P405 - Store locked up.

P406 - Store in corrosive resistant container with a resistant inner liner.

P501 - Dispose of contents/container according to local, regional, national, territorial,

provincial, and international regulations.

Other Hazards

Other Hazards Not Contributing to the Classification: Corrosive to the respiratory tract.

Unknown Acute Toxicity (GHS-US) Not available.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

Mixture

Name	Product identifier	% (w/w)	Classification (GHS-US)
Phosphoric acid	(CAS No) 7664-38-2	15 - 35	Met. Corr. 1, H290
			Acute Tox. 4 (Oral), H302
			Skin Corr. 1B, H314
			Eye Dam. 1, H318
Dibutyl thiourea	(CAS No) 109-46-6	0.1 - 1	Acute Tox. 4 (Oral), H302
			Skin Irrit. 2, H315
			Eye Irrit. 2A, H319
			Skin Sens. 1, H317
			Aquatic Chronic 3, H412

Full text of H-phrases: see section 16

SECTION 4: FIRST AID MEASURES

Description of First Aid Measures

General: Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label if possible).

Inhalation: Remove to fresh air and keep at rest in a position comfortable for breathing. Immediately call a POISON CENTER or doctor/physician. Ventilate the area.

Skin Contact: Rinse cautiously with water for at least 30 minutes. Remove contaminated clothing and shoes. Wash contaminated clothing before reuse. Seek medical attention immediately.

Eye Contact: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing for at least 60 minutes. Immediately call a POISON CENTER or doctor/physician.

Ingestion: Rinse mouth. Do NOT induce vomiting. Immediately call a POISON CENTER or doctor/physician.

Most Important Symptoms and Effects Both Acute and Delayed

General: Causes severe skin burns and eye damage. May cause an allergic reaction in sensitive individuals. Effects of exposure (inhalation, ingestion or skin contact) to substance may be delayed.

Inhalation: May be corrosive to the respiratory tract.

Skin Contact: Causes severe skin burns and eye damage. May cause an allergic skin reaction.

Eye Contact: Causes serious eye damage.

Ingestion: Ingestion is likely to be harmful or have adverse effects. **Chronic Symptoms:** None expected under normal conditions of use.

Indication of Any Immediate Medical Attention and Special Treatment Needed

If medical advice is needed, have product container or label at hand.

SECTION 5: FIRE-FIGHTING MEASURES

Extinguishing Media

Suitable Extinguishing Media: Use extinguishing media appropriate for surrounding fire.

Unsuitable Extinguishing Media: Do not use a heavy water stream. A heavy water stream may spread burning liquid.

Special Hazards Arising From the Substance or Mixture

Fire Hazard: Not considered flammable but may burn at high temperatures.

09/10/2014 RTATAA-CC EN (English US) 2/11

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Explosion Hazard: Product is not explosive, however in contact with incompatabilities may release explosive hydrogen gas. **Reactivity:** Phosphoric acid violently polymerizes under the influence of azo compounds and epoxides. On combustion, forms toxic fumes (phosphorous oxides). The substance decomposes on contact with alcohols, aldehydes, cyanides, ketones, phenols, esters, sulfides, halogenated organics producing toxic fumes. Attacks many metals forming flammable/explosive hydrogen gas. The substance is a medium strong acid. Reacts violently with bases. Do not add water to the solution; if diluting, slowly add the solution to water. Adding water to solution may generate large amounts of heat.

Advice for Firefighters

Precautionary Measures Fire: Exercise caution when fighting any chemical fire.

Firefighting Instructions: Use water spray or fog for cooling exposed containers. DO not get water into containers or allow water to enter source of leak (causes an exothermic reaction, generating large ammounts of heat). Do not breath fumes from fires or vapors from decomposition. Do not allow run-off from fire fighting to enter drains or water sources.

Protection During Firefighting: Do not enter fire area without proper protective equipment, including respiratory protection.

Hazardous Combustion Products: Carbon oxides (CO, CO₂). Phosphorus oxides. Corrosive vapors.

Reference to Other Sections

Refer to section 9 for flammability properties.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment and Emergency Procedures

General Measures: Do not get in eyes, on skin, or on clothing. Do not breathe vapor or mist. Avoid contact with metals and other incompatibles.

For Non-Emergency Personnel

Protective Equipment: Use appropriate personal protection equipment (PPE).

Emergency Procedures: Evacuate unnecessary personnel.

For Emergency Personnel

Protective Equipment: Use appropriate personal protection equipment (PPE).

Emergency Procedures: Evacuate unnecessary personnel. Eliminate ignition sources. Stop leak if safe to do so. Ventilate area.

Environmental Precautions

Prevent entry to sewers and public waters.

Methods and Material for Containment and Cleaning Up

For Containment: Cautiously neutralize spilled material with a weak base. Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams.

Methods for Cleaning Up: Cautiously neutralize spilled liquid. Clear up spills immediately and dispose of waste safely. Absorb and/or contain spill with inert material, then place in suitable container for disposal. Ventilate area.

Reference to Other Sections

See heading 8, Exposure Controls and Personal Protection. Concerning disposal elimination after cleaning, see section 13.

SECTION 7: HANDLING AND STORAGE

Precautions for Safe Handling

Additional Hazards When Processed: May be corrosive to metals.

Hygiene Measures: Handle in accordance with good industrial hygiene and safety procedures. Wash hands and other exposed areas with mild soap and water before eating, drinking, or smoking and again when leaving work. Do no eat, drink or smoke when using this product. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse.

Conditions for Safe Storage, Including Any Incompatibilities

Technical Measures: Ensure all national/local regulations are observed. Storage areas should be periodically checked for corrosion and integrity.

Storage Conditions: Store in a dry, cool and well-ventilated place. Keep container closed when not in use. Keep/Store away from direct sunlight, extremely high or low temperatures, ignition sources, and incompatible materials.

Incompatible Materials: Strong acids. Strong bases. Strong oxidizers. Metals.

Special Rules on Packaging: Store in original container or corrosive resistant and/or lined container.

Specific End Use(s)

Rust remover.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

Control Parameters

09/10/2014 RTATAA-CC EN (English US) 3/11

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Phosphoric acid (7664-38-2)		
USA ACGIH	ACGIH TWA (mg/m³)	1 mg/m³
USA ACGIH	ACGIH STEL (mg/m³)	3 mg/m³
USA OSHA	OSHA PEL (TWA) (mg/m³)	1 mg/m³
USA NIOSH	NIOSH REL (TWA) (mg/m³)	1 mg/m³
USA NIOSH	NIOSH REL (STEL) (mg/m³)	3 mg/m³
USA IDLH	US IDLH (mg/m³)	1000 mg/m ³
Alberta	OEL STEL (mg/m³)	3 mg/m³
Alberta	OEL TWA (mg/m³)	1 mg/m³
British Columbia	OEL STEL (mg/m³)	3 mg/m³
British Columbia	OEL TWA (mg/m³)	1 mg/m³
Manitoba	OEL STEL (mg/m³)	3 mg/m³
Manitoba	OEL TWA (mg/m³)	1 mg/m³
New Brunswick	OEL STEL (mg/m³)	3 mg/m³
New Brunswick	OEL TWA (mg/m³)	1 mg/m³
Newfoundland & Labrador	OEL STEL (mg/m³)	3 mg/m³
Newfoundland & Labrador	OEL TWA (mg/m³)	1 mg/m³
Nova Scotia	OEL STEL (mg/m³)	3 mg/m³
Nova Scotia	OEL TWA (mg/m³)	1 mg/m³
Nunavut	OEL STEL (mg/m³)	3 mg/m³
Nunavut	OEL TWA (mg/m³)	1 mg/m³
Northwest Territories	OEL STEL (mg/m³)	3 mg/m³
Northwest Territories	OEL TWA (mg/m³)	1 mg/m³
Ontario	OEL STEL (mg/m³)	3 mg/m³
Ontario	OEL TWA (mg/m³)	1 mg/m³
Prince Edward Island	OEL STEL (mg/m³)	3 mg/m³
Prince Edward Island	OEL TWA (mg/m³)	1 mg/m³
Québec	VECD (mg/m³)	3 mg/m³
Québec	VEMP (mg/m³)	1 mg/m³
Saskatchewan	OEL STEL (mg/m³)	3 mg/m³
Saskatchewan	OEL TWA (mg/m³)	1 mg/m³
Yukon	OEL STEL (mg/m³)	3 mg/m³
Yukon	OEL TWA (mg/m³)	1 mg/m³

Exposure Controls

Appropriate Engineering Controls: Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Ensure adequate ventilation, especially in confined areas. Ensure all national/local regulations are observed.

Personal Protective Equipment: Avoid all unnecessary exposure. Gloves. Protective goggles. Face shield. Protective clothing. Insufficient ventilation: wear respiratory protection.











Materials for Protective Clothing: Chemically resistant materials and fabrics.

Hand Protection: Wear chemically resistant protective gloves. **Eye Protection:** Chemical goggles or safety glasses. Face shield.

Skin and Body Protection: Chemical resistant suit.

Respiratory Protection: Use a NIOSH-approved respirator or self-contained breathing apparatus whenever exposure may exceed

established Occupational Exposure Limits.

Consumer Exposure Controls: Do not eat, drink, or smoke during use

09/10/2014 RTATAA-CC EN (English US) 4/11

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Information on Basic Physical and Chemical Properties

Physical State : Liquid
Appearance : Clear

Odor: CharacteristicOdor Threshold: Not available

pH : 1

Relative Evaporation Rate (butylacetate=1) Not available **Melting Point** Not available **Freezing Point** Not available > 100 °C (> 212 °F) **Boiling Point Flash Point** > 100 °C (> 212 °F) **Auto-ignition Temperature** Not available **Decomposition Temperature** Not available Not available Flammability (solid, gas) **Lower Flammable Limit** Not available **Upper Flammable Limit** Not available Vapor Pressure Not available Relative Vapor Density at 20 °C Not available

Specific Gravity/Relative Density : 1.15

Solubility: Soluble in waterPartition coefficient: n-octanol/water: Not availableViscosity: Not available

Explosion Data – Sensitivity to Mechanical Impact : Not expected to present an explosion hazard due to mechanical impact : Not expected to present an explosion hazard due to static discharge

SECTION 10: STABILITY AND REACTIVITY

Reactivity: Phosphoric acid violently polymerizes under the influence of azo compounds and epoxides. On combustion, forms toxic fumes (phosphorous oxides). The substance decomposes on contact with alcohols, aldehydes, cyanides, ketones, phenols, esters, sulfides, halogenated organics producing toxic fumes. Attacks many metals forming flammable/explosive hydrogen gas. The substance is a medium strong acid. Reacts violently with bases. Do not add water to the solution; if diluting, slowly add the solution to water. Adding water to solution may generate large amounts of heat.

Chemical Stability: Stable under normal conditions.

Possibility of Hazardous Reactions: Hazardous polymerization will not occur.

Conditions to Avoid: Prolonged contact with metals. Direct sunlight, extremely high or low temperatures, open flames, sources of ignition and incompatible materials.

Incompatible Materials: Strong acids. Strong bases. Strong oxidizers. Metals – may be corrosive to metals.

Hazardous Decomposition Products: Carbon oxides (CO, CO₂). Nitrogen compounds. Sulfer compounds. Phosphorus oxides. Thermal decomposition generates: Corrosive vapors. May produce explosive hydrogen gas on contact with incompatibilities or upon thermal decomposition.

SECTION 11: TOXICOLOGICAL INFORMATION

Information on Toxicological Effects - Product

Acute Toxicity: Not classified.

LD50 and LC50 Data: Not available.

Skin Corrosion/Irritation: Causes severe skin burns and eye damage.

pH: 1

Serious Eye Damage/Irritation: Causes serious eye damage.

pH: 1

Respiratory or Skin Sensitization: May cause an allergic skin reaction.

Germ Cell Mutagenicity: Not classified.

09/10/2014 RTATAA-CC EN (English US) 5/11

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Teratogenicity: Not available. **Carcinogenicity:** Not classified.

Specific Target Organ Toxicity (Repeated Exposure): Not classified.

Reproductive Toxicity: Not classified.

Specific Target Organ Toxicity (Single Exposure): Not classified.

Aspiration Hazard: Not classified.

Symptoms/Injuries After Inhalation: Inhalation of fumes or vapors may cause respiratory irritation. **Symptoms/Injuries After Skin Contact:** Causes severe skin burns. May cause an allergic skin reaction.

Symptoms/Injuries After Eye Contact: Causes serious eye damage.

Symptoms/Injuries After Ingestion: Ingestion is likely to be harmful or have adverse effects.

Chronic Symptoms: None expected under normal conditions of use.

Information on Toxicological Effects - Ingredient(s)

LD50 and LC50 Data:

Phosphoric acid (7664-38-2)		
LD50 Oral Rat	1530 mg/kg	
LD50 Dermal Rabbit	2730 mg/kg	
LC50 Inhalation Rat	> 850 mg/m³ (Exposure time: 1 h)	
Dibutyl thiourea (109-46-6)		
ATE US (oral)	500.00 mg/kg body weight	

SECTION 12: ECOLOGICAL INFORMATION

Toxicity Not classified.

Persistence and Degradability

RUST EATER & CONVERTER	
Persistence and Degradability	Not established.

Bioaccumulative Potential

RUST EATER & CONVERTER	
Bioaccumulative Potential	Not established.

Mobility in Soil Not available.

Other Adverse Effects

Other Information: Avoid release to the environment.

SECTION 13: DISPOSAL CONSIDERATIONS

Waste Disposal Recommendations: Dispose of waste material in accordance with all local, regional, national, provincial, territorial and international regulations.

Additional Information: Avoid release to the environment. RCRA Waste Code: D002 (Corrosive Material).

SECTION 14: TRANSPORT INFORMATION

In Accordance With ICAO/IATA/DOT/TDG

UN Number

 UN-No.(DOT)
 : 1805

 DOT NA no.
 : UN1805

 UN-No. (TDG)
 : UN1805

 UN-No. (IMDG)
 : 1805

 UN-No.(IATA)
 : 1805

UN Proper Shipping Name

Proper Shipping Name (DOT): PHOSPHORIC ACID SOLUTIONProper Shipping Name (TDG): PHOSPHORIC ACID, LIQUIDProper Shipping Name (IATA): PHOSPHORIC ACID, SOLUTIONProper Shipping Name (IMDG): PHOSPHORIC ACID SOLUTION

Transport Document Description (DOT) : UN1805 PHOSPHORIC ACID SOLUTION, 8, III

Transport Document Description (TDG) : UN1805 PHOSPHORIC ACID, LIQUID, 8, III

Transport Document Description (adr) (IMDG/IATA) : UN 1805 PHOSPHORIC ACID, SOLUTION, 8, III, (E)

09/10/2014 RTATAA-CC EN (English US) 6/11

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Transport Hazard Class(es)

Department Of Transportation (DOT) Hazard Classes : 8 - Class 8 - Corrosive material 49 CFR 173.136

Hazard Labels (DOT) : 8 - Corrosive



Packing Group (DOT) : III - Minor Danger

DOT Special Provisions (49 CFR 172.102) : A7 - Steel packaging must be corrosion-resistant or have protection against

IB3 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1 and 31HA2, 31HB2, 31HN2, 31HD2 and 31HH2). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized, except for UN2672 (also see Special Provision IP8 in Table 2 for UN2672).

N34 - Aluminum construction materials are not authorized for any part of a packaging which is normally in contact with the hazardous material.

T4 - 2.65 178.274(d)(2) Normal...... 178.275(d)(3)

TP1 - The maximum degree of filling must not exceed the degree of filling determined by the following: Degree of filling = 97 / (1 + a (tr - tf)) Where: tr is the maximum mean bulk temperature during transport, and tf is the temperature in degrees celsius of the liquid during filling.

DOT Packaging Exceptions (49 Cfr 173.xxx) : 154 DOT Packaging Non Bulk (49 Cfr 173.xxx) : 203 DOT Packaging Bulk (49 Cfr 173.xxx) : 241

TDG Primary Hazard Classes : 8 - Class 8 - Corrosives Hazard Labels (TDG) : 8 - Corrosive substances



Packing Group (TDG) : III - Minor Danger

Explosive Limit And Limited Quantity Index : 5 : 5 **Passenger Carrying Road Vehicle Or Passenger Carrying Railway Vehicle Index**

Class (IMDG) : 8

Danger Labels (IMDG) 8



Packing Group (IMDG) : III - Minor Danger

Class (IATA) : 8

Hazard Labels (IATA)

Packing Group (IATA) : III - Minor Danger

Additional Information

Emergency Response Guide (ERG) Number : 154

09/10/2014 RTATAA-CC EN (English US) 7/11

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Other Information

: This product meets the limited quantity exceptions as follows:DOT: Not regulated as dangerous goods except when shipped in bulk (LQ of up to 5L). Otherwise, the above descriptions apply.

Transport by sea

Dot Vessel Stowage Location : A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a

passenger vessel.

Limited Quantities (IMDG) : 5L

Special Provisions (IMDG) : 223

Excepted Quantities (IMDG) : E1

IBC Packing Instructions (IMDG) : IBC03

Packing Instructions (IMDG) : P001,LP01

Tank Instructions (IMDG) : T4

Tank Instructions (IMDG) : 14
Tank Special Provisions (IMDG) : TP1
Stowage Category (IMDG) : A

Properties and Observations (IMDG) : Miscible in water. Mildly corrosive to most metals.

 EMS-NO. (1)
 : F-A

 MFAG-NO
 : 154

 EMS-NO. (2)
 : S-B

 Marine Pollutant
 : No

Air transport

DOT Quantity Limitations Passenger Aircraft/Rail (49 CFR 173.27) : 5 L **DOT Quantity Limitations Cargo Aircraft Only (49 CFR 175.75)** : 60 L **CAO Packing Instructions (IATA)** : 856 CAO Max Net Quantity (IATA) : 60L **PCA Packing Instructions (IATA)** : 852 **PCA Limited Quantities (IATA)** : Y841 **PCA Limited Quantity Max Net Quantity (IATA)** : 1L PCA Max Net Quantity (IATA) : 5L PCA Excepted Quantities (IATA) : E1 : 60L **CAO Max Net Quantity (IATA) CAO Packing Instructions (IATA)** : 856 Special Provision (IATA) : A3,A803 : 8L Erg Code (IATA)

SECTION 15: REGULATORY INFORMATION

US Federal Regulations

RUST EATER & CONVERTER	
SARA Section 311/312 Hazard Classes Immediate (acute) he	ealth hazard

Phosphoric acid (7664-38-2)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

Dibutyl thiourea (109-46-6)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

US State Regulations

Phosphoric acid (7664-38-2)

- U.S. California SCAQMD Toxic Air Contaminants Non-Cancer Chronic
- U.S. California Toxic Air Contaminant List (AB 1807, AB 2728)
- U.S. Connecticut Hazardous Air Pollutants HLVs (30 min)
- U.S. Connecticut Hazardous Air Pollutants HLVs (8 hr)
- U.S. Delaware Pollutant Discharge Requirements Reportable Quantities
- U.S. Idaho Non-Carcinogenic Toxic Air Pollutants Acceptable Ambient Concentrations
- U.S. Idaho Non-Carcinogenic Toxic Air Pollutants Emission Levels (ELs)
- U.S. Idaho Occupational Exposure Limits TWAs

09/10/2014 RTATAA-CC EN (English US) 8/11

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

- U.S. Louisiana Reportable Quantity List for Pollutants
- U.S. Massachusetts Allowable Ambient Limits (AALs)
- U.S. Massachusetts Allowable Threshold Concentrations (ATCs)
- U.S. Massachusetts Oil & Hazardous Material List Groundwater Reportable Concentration Reporting Category 1
- U.S. Massachusetts Oil & Hazardous Material List Groundwater Reportable Concentration Reporting Category 2
- U.S. Massachusetts Oil & Hazardous Material List Reportable Quantity
- U.S. Massachusetts Oil & Hazardous Material List Soil Reportable Concentration Reporting Category 1
- U.S. Massachusetts Oil & Hazardous Material List Soil Reportable Concentration Reporting Category 2
- RTK U.S. Massachusetts Right To Know List
- U.S. Massachusetts Threshold Effects Exposure Limits (TELs)
- U.S. Massachusetts Toxics Use Reduction Act
- U.S. Michigan Occupational Exposure Limits STELs
- U.S. Michigan Occupational Exposure Limits TWAs
- U.S. Michigan Polluting Materials List
- U.S. Minnesota Chemicals of High Concern
- U.S. Minnesota Hazardous Substance List
- U.S. Minnesota Permissible Exposure Limits STELs
- U.S. Minnesota Permissible Exposure Limits TWAs
- U.S. New Hampshire Regulated Toxic Air Pollutants Ambient Air Levels (AALs) 24-Hour
- U.S. New Hampshire Regulated Toxic Air Pollutants Ambient Air Levels (AALs) Annual
- U.S. New Jersey Discharge Prevention List of Hazardous Substances
- RTK U.S. New Jersey Right to Know Hazardous Substance List
- U.S. New Jersey Special Health Hazards Substances List
- U.S. New York Occupational Exposure Limits TWAs
- U.S. New York Reporting of Releases Part 597 List of Hazardous Substances
- U.S. North Dakota Air Pollutants Guideline Concentrations 1-Hour
- U.S. North Dakota Air Pollutants Guideline Concentrations 8-Hour
- U.S. Oregon Permissible Exposure Limits TWAs
- RTK U.S. Pennsylvania RTK (Right to Know) Environmental Hazard List
- RTK U.S. Pennsylvania RTK (Right to Know) List
- U.S. Rhode Island Air Toxics Acceptable Ambient Levels Annual
- U.S. South Carolina Toxic Air Pollutants Maximum Allowable Concentrations
- U.S. South Carolina Toxic Air Pollutants Pollutant Categories
- U.S. Tennessee Occupational Exposure Limits STELs
- U.S. Tennessee Occupational Exposure Limits TWAs
- U.S. Texas Effects Screening Levels Long Term
- U.S. Texas Effects Screening Levels Short Term
- U.S. Vermont Permissible Exposure Limits STELs
- U.S. Vermont Permissible Exposure Limits TWAs
- U.S. Washington Permissible Exposure Limits STELs
- U.S. Washington Permissible Exposure Limits TWAs
- U.S. Wisconsin Hazardous Air Contaminants All Sources Emissions From Stack Heights 25 Feet to Less Than 40 Feet
- U.S. Wisconsin Hazardous Air Contaminants All Sources Emissions From Stack Heights 40 Feet to Less Than 75 Feet
- U.S. Wisconsin Hazardous Air Contaminants All Sources Emissions From Stack Heights 75 Feet or Greater
- U.S. Wisconsin Hazardous Air Contaminants All Sources Emissions From Stack Heights Less Than 25 Feet

Dibutyl thiourea (109-46-6)

- U.S. Texas Effects Screening Levels Long Term
- U.S. Texas Effects Screening Levels Short Term

Canadian Regulations

RUST EATER & CONVERTER	
WHMIS Classification	Class D Division 2 Subdivision B - Toxic material causing other toxic effects
	Class E - Corrosive Material

09/10/2014 RTATAA-CC EN (English US) 9/11

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations





Phosphoric acid (7664-38-2)

Listed on the Canadian DSL (Domestic Substances List) inventory.

Listed on the Canadian Ingredient Disclosure List

IDL Concentration 1 %

WHMIS Classification Class E - Corrosive Material

Class D Division 2 Subdivision B - Toxic material causing other toxic effects

Dibutyl thiourea (109-46-6)

Listed on the Canadian DSL (Domestic Substances List) inventory.

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the SDS contains all of the information required by CPR.

SECTION 16: OTHER INFORMATION, INCLUDING DATE OF PREPARATION OR LAST REVISION

Revision date : 09/10/2014

Other Information : This document has been prepared in accordance with the SDS requirements of the OSHA

Hazard Communication Standard 29 CFR 1910.1200.

GHS Full Text Phrases:

Acute Tox. 4 (Oral)	Acute toxicity (oral) Category 4
Aquatic Chronic 3	Hazardous to the aquatic environment - Chronic Hazard Category 3
Eye Dam. 1	Serious eye damage/eye irritation Category 1
Eye Irrit. 2A	Serious eye damage/eye irritation Category 2A
Met. Corr. 1	Corrosive to metals Category 1
Skin Corr. 1B	Skin corrosion/irritation Category 1B
Skin Irrit. 2	Skin corrosion/irritation Category 2
Skin Sens. 1	Skin sensitization Category 1
H290	May be corrosive to metals
H302	Harmful if swallowed
H314	Causes severe skin burns and eye damage
H315	Causes skin irritation
H317	May cause an allergic skin reaction
H318	Causes serious eye damage
H319	Causes serious eye irritation
H412	Harmful to aquatic life with long lasting effects

NFPA Health Hazard : 2 - Intense or continued exposure could cause temporary


incapacitation or possible residual injury unless prompt

medical attention is given.

NFPA Fire Hazard : 0 - Materials that will not burn.

NFPA Reactivity : 0 - Normally stable, even under fire exposure conditions,

and are not reactive with water.



Party Responsible for the Preparation of This Document

09/10/2014 RTATAA-CC EN (English US) 10/11

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Star brite Inc. (954)587-6280

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.

North America GHS US 2012 & WHMIS 2

09/10/2014 RTATAA-CC EN (English US) 11/11